non-return valves without positive means of closing, provided that the inboard valve is situated above the deepest subdivision dra ught and is always accessible for examination under service conditions. Where avalve with positive means of closing is fitted, the operating position above the bulkhead deck shall always be readily accessible and means shall be provided for indicating whether the valve is open or closed. RESOLUTION MSC.216(82) (adopted on 8 December 2006) AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED- 43 - 8.2.2 The requirements of th e International Convention on Load Lines in force shall apply to discharges led through the shell pla ting from spaces above the bulkhead deck of passenger ships and the freeboard deck of cargo ships. 8.3 Machinery space, main and auxiliary sea inlets and discharges in connection with the operation of machinery shall be fitted with readily accessible valves between the pipes - 8.3 Machinery space, main and auxiliary sea inlets and discharges in connection with the operation of machinery shall be fitted with readily accessible valves between the pipes and the shell plating or betw een the pipes and fabricated boxes attached to the shell plating. In manned machinery spaces the valves may be controlled locally and shall be provided with indicators showing whether they are open or closed. 8.4 Moving parts penetrating the shell plating below the deepest subdivision draught shall be fitted with awatert ight sealing arrangement acceptable to the Administration. The inboard gland shall be located within awatertight space of such volume that, if flooded, the bulkhead deck will not be submer ged. The Administration may require that if such compartment is flooded, essential or emergency power and lighting, internal communication, signals or other emergency devi ces must remain available in other parts of the ship. - if such compartment is flooded, essential or emergency power and lighting, internal communication, signals or other emergency devi ces must remain available in other parts of the ship. 8.5 All shell fittings and valves required by this regulation sh all be of steel, bronze or other approved ductile material. Valves of or dinary cast iron or similar material are not acceptable. All pipes to which this regulation re fers shall be of steel or other equivalent material to the satisfaction of the Administration. 9 Gangway, cargo and fuelling ports fitted below the bulkhead deck of passenger ships and the freeboard deck of cargo ships shall be watertight and in no case be so fitted as to have their lowest point below the deepest subdivision draught. 10.1 The inboard opening of each ash-chute, rubbish-chute, etc., shall be fitted with an efficient cover. 10.2 If the inboard opening is situated below the bulkhead deck of passen