THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO resolution MSC.268(85) by which it adopted the International Maritime Solid Bulk Cargoes Code (hereinafter referred to as "the IMSBC Code"), which has become mandatory under chapter VI of the International Convention for the Safety of Life at Sea, 1974, as amended ("the Convention"), RECALLING FURTHER article VIII(b) and regulation VII/1.1 of the Convention concerning the procedure for amending the IMSBC Code, HAVING CONSIDERED, at its 105th session, amendments to the IMSBC Code, proposed and --- procedure for amending the IMSBC Code, HAVING CONSIDERED, at its 105th session, amendments to the IMSBC Code, proposed and circulated in accordance with article VIII(b)(i) of the Convention, 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the IMSBC Code, the text of which is set out in the annex to the present resolution; 2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the said amendments shall be deemed to have been accepted on 1 June 2023, unless prior to that date more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world'smerchant fleet have notified their objections to the amendments; 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii )(2) of the Convention, the amendments shall enter into force --- article VIII(b)(vii )(2) of the Convention, the amendments shall enter into force on 1 December 2023 upon their acceptance in accordance with paragraph 2 above; 4 AGREES that Contracting Governments to the Convention may apply the aforementioned amendments in whole or in part on avoluntary basis as from 1 January 2023; 5 REQUESTS the Secretary -General, for the purpose of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention; 6 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention. RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 2 - ANNEX AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE --- - 2 - ANNEX AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE Table of contents For "Section 7", replace the text to read "Cargoes which may liquefy or undergo dynamic separation". For "Section 8", replace the text to read "Test procedures for group Acargoes". Section 1 General provisions 1.7 Definitions In the definition for " GHS", replace the word "seventh" with the word "ninth" and replace "ST/SG/AC.10/30/Rev.7" with "ST/SG/AC.10/30/Rev.9". In the definition for " Group A", replace the text to read " Group Aconsists of cargoes which possess ahazard due to moisture that may result in liquefaction or dynamic separation if shipped at amoisture content in excess of their transportable moisture limit." In the definition for "Group C", replace the text to read "Group Cconsists of cargoes which are classified as neither group Anor group B." --- In the definition for "Group C", replace the text to read "Group Cconsists of cargoes which are classified as neither group Anor group B." In the definition for " Manual of Tests and Criteria ", replace the definition to read " Manual of Tests and Criteria means the seventh revised edition of the United Nations publication entitled Manual of Tests and Criteria (ST/SG/AC.10/11/Rev.7 and Amend.1)." In the definition for "Transportable moisture limit (TML)", replace the text to read "Transportable moisture limit (TML) of agroup Acargo means the maximum moisture content of the cargo which is considered safe for carriage in ships not complying with the special provisions of 7.3.2. It is determined by the test procedures, approved by acompetent authority, such as those specified in paragraph 1 of appendix 2." Add the following new definitions in alphabetical order: "Cargoes which may undergo dynamic separation means cargoes which contain acertain --- Add the following new definitions in alphabetical order: "Cargoes which may undergo dynamic separation means cargoes which contain acertain proportion of fine particles and acertain amount of moisture, and may undergo dynamic separation if shipped at amoisture content in excess of their transportable moisture limit." "Dynamic separation means the phenomenon of forming aliquid slurry (water and fine solids) above the solid material, resulting in afree surface effect which may significantly affect the ship'sstability." RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 3 - Section 4 Assessment of acceptability of consignments for safe shipment 4.1 Identification and classification In 4.1.4, replace the words

"Manual of Tests and Criteria" with the words "Manual of Tests and Criteria". 4.2 Provision of information In 4.2.2.9, replace the existing text to read as follows: --- Criteria". 4.2 Provision of information In 4.2.2.9, replace the existing text to read as follows: "additional information in the form of acertificate on the moisture content of the cargo and its transportable moisture limit in the case of agroup Acargo;". In 4.2.3, in the table for "Form for cargo information for solid bulk cargoes", in the "Group of the cargo" box, delete the asterisks and the corresponding footnote text "For cargoes which may liquefy (group Aand group Aand Bcargoes)". Under "Transportable moisture limit", add the words "For group Aand Band group Acargoes". Under "Moisture content at shipment", add the words "For group Aand Band group Acargoes". 4.3 Certificates of test In 4.3.2, replace the first sentence to read as follows: "When agroup Acargo is carried, the shipper shall provide the ship'smaster or his representative with asigned certificate of the TML, and asigned certificate or --- representative with asigned certificate of the TML, and asigned certificate or declaration of the moisture content, each issued by an entity recognized by the competent authority of the port of loading." In 4.3.3, replace the first sentence to read as follows: "When agroup Acargo is carried, procedures for sampling, testing and controlling moisture content to ensure the moisture content is less than the TML when it is on board the ship shall be established by the shipper, taking account of the provisions of this Code." In 4.3.5, replace the first sentence to read as follows: "When agroup Acargo is to be loaded into more than one cargo space of aship, the certificate or the declaration of moisture content shall certify the moisture content of each type of finely grained material loaded into each cargo space." 4.4 Sampling procedures In 4.4.3, replace the existing text with the following: --- 4.4 Sampling procedures In 4.4.3, replace the existing text with the following: "For agroup Acargo, the shipper shall facilitate access to stockpiles for the purpose of inspection, sampling and subsequent testing by the ship'snominated representative." 4.8 Documentation required on board the ship carrying dangerous goods In 4.8.3, after the words "SOLAS regulation II-2/19.4", add the words "(or II-2/54.3)". RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 4 - Section 7 Cargoes which may liquefy In the heading for "Section 7", replace the words "Cargoes which may liquefy" with the words "Cargoes which may liquefy or undergo dynamic separation". 7.1 Introduction In 7.1.1, replace the existing text with the following: "The purpose of this section is to bring to the attention of masters and others with --- In 7.1.1, replace the existing text with the following: "The purpose of this section is to bring to the attention of masters and others with responsibilities for the loading and carriage of bulk cargoes, the risks associated with liquefaction or dynamic separation and the precautions to minimize the risk. Such cargoes may appear to be in arelatively dry granular state when loaded, and yet may contain sufficient moisture to become fluid or unstable under the stimulus of compaction and the vibration which occurs during avoyage." In 7.1.3, replace the existing text with the following: "Some group Acargoes may also heat spontaneously." 7.3 Provisions for cargoes that may liquefy In the heading for 7.3, replace the words "Provisions for cargoes that may liquefy" with the words "Provisions for cargoes which may liquefy or undergo dynamic separation". 7.3.1 General In 7.3.1.1, replace the existing text with the following: --- 7.3.1 General In 7.3.1.1, replace the existing text with the following: "Group Acargoes shall only be accepted for loading when the actual moisture content of the cargo is less than its TML. Notwithstanding this provision, cargoes having moisture content in excess of the TML may be carried on aspecially constructed or fitted cargo ship for confining cargo shift specified in 7.3.2." In 7.3.1.2, replace the existing text with the following: "Notwithstanding the provisions in 1.4 of this Code, the requirements in 4.2.2.9, 4.2.2.10, 4.3.2 to 4.3.5, 4.5, 4.6 and 8 of this Code need not apply to agroup Acargo provided that the cargo is carried on aspecially constructed or fitted cargo ship for confining cargo shift specified in 7.3.2 or on aspecially constructed ship for dry powdery cargoes specified in 7.3.3." Section 8 Test procedures for cargoes which may liquefy In the heading for "Section 8", replace the words "Test procedures for cargoes which may --- Section 8 Test procedures for cargoes which may liquefy In the heading for "Section 8", replace the words "Test procedures for cargoes which may liquefy" with the words "Test procedures for group Acargoes". RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 5 - Section 9 Materials possessing chemical hazards 9.2 Hazard classification 9.2.3 Materials hazardous only in bulk (MHB) 9.2.3.2 Combustible solids: MHB (CB) In 9.2.3.2.2, replace the word "33.2.1.4.3.1" with the word "33.2.4.3.1". 9.2.3.3 Self-heating solids: MHB (SH) In 9.2.3.3.2, replace the word "33.3.1.6" with the word "33.4.6". In 9.2.3.3.3, replace the

word "33.4.1.4.3.5" with the word "33.5.4.3.5". 9.2.3.4 Solids that evolve flammable gas when wet: MHB (WF) In 9.2.3.4.2, replace the word "33.4.1" with the word "33.5". 9.2.3.5 Solids that evolve toxic gas when wet: MHB (WT) --- In 9.2.3.4.2, replace the word "33.4.1" with the word "33.5". 9.2.3.5 Solids that evolve toxic gas when wet: MHB (WT) In 9.2.3.5.2, replace the word "33.4.1" with the word "33.5". 9.2.3.7 Corrosive solids: MHB (CR) In 9.2.3.7.3, replace the existing text with the following: "Amaterial shall be classified as MHB when the corros ion rate on asteel surface is between 4 mm and 6.25 mm ayear at atest temperature of 55°C. For the purposes of testing steel, type S235JR+CR (1.0037 resp. St 37 -2), S275J2G3+CR (1.0144 resp. St 44 -3), ISO 3574:1999, Unified Numbering Systems (UNS) G1020 0 or SAE 1020 shall be used. An acceptable test is prescribed in the United Nations Manual of Tests and Criteria, part III, section 37. Arepresentative sample of the cargo shall be tested at typical as -shipped cargo conditions, including moisture content by mass, bulk density, particle size distribution and atmospheric conditions. --- mass, bulk density, particle size distribution and atmospheric conditions. The assessment of localized corrosion occurring upon the steel surface shall be performed using national or international standards. The test shall be conducted taking into account the guidance developed by the Organization.", APPENDIX 1 INDIVIDUAL SCHEDULES OF SOLID BULK CARGOES Amendments to existing individual schedules Amend the following individual schedules as indicated below: ALFALFA In the individual schedule for "ALFALFA", in the section for "Characteristics", in the table, replace the words "Fine Powder" with the words "Fine powder". RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 6 - ALUMINIUM NITRATE UN 1438 In the individual schedule for "ALUMINIUM NITRATE UN 1438", in the section for "Emergency procedures", in the table, replace the word "overalls" with the word "coveralls". --- procedures", in the table, replace the word "overalls" with the word "coveralls". AMMONIUM NITRATE UN 1942 In the individual schedule for "AMMONIUM NITRATE UN 1942", in the section for "Description", in the "Note", replace the word " UN" by the word "UN". In the section for "Loading", delete the word "intrinsically". AMMONIUM NITRATE BASED FERTILIZER UN 2067 In the individual schedule for "AMMONIUM NITRATE BASED FERTILIZER UN 2067", in the section for "Loading", delete the word "intrinsically". AMMONIUM NITRATE BASED FERTILIZER UN 2071 In the individual schedule for "AMMONIUM NITRATE BASED FERTILIZER UN 2071", under the BCSN, replace the word " UN" by the word "UN". In the section for "Loading", delete the word "intrinsically". AMMONIUM NITRATE BASED FERTILIZER (non-hazardous) Delete the individual schedule for "AMMONIUM NITRATE BASED FERTILIZER (non-hazardous)". BARIUM NITRATE UN 1446 --- Delete the individual schedule for "AMMONIUM NITRATE BASED FERTILIZER (non-hazardous)". BARIUM NITRATE UN 1446 In the individual schedule for "BARIUM NITRATE UN 1446", in the section for "Emergency procedures", in the table, replace the word "overalls" with the word "coveralls". CASTOR BEANS or CASTOR MEAL or CASTOR POMACE or CASTOR FLAKE UN 2969 In the individual schedule for "CASTOR BEANS or CASTOR MEAL or CASTOR POMACE or CASTOR FLAKE UN 2969", move the sentence "Castor meal, castor pomace and castor flakes shall not be carried in bulk." from the section for "Precautions" to underneath the BCSN. COAL TAR PITCH In the individual schedule for "COAL TAR PITCH", under the section for "Description", replace the words "Coal Tar" with the words "coal tar" and replace the word "Cokes" with the word "cokes". CRUSHED CARBON ANODES In the individual schedule for "CRUSHED CARBON ANODES", under the section for --- "cokes". CRUSHED CARBON ANODES In the individual schedule for "CRUSHED CARBON ANODES", under the section for "Description", replace the words "Crushed Car bon Anodes" with the words "Crushed carbon anodes". FISH MEAL (FISH SCRAP), STABILIZED UN 2216 Anti-oxidant treated In the individual schedule for "FISH MEAL (FISH SCRAP), STABILIZED UN 2216 Anti-oxidant treated", under the BCSN, replace the word "fishmeal" with the words "fish meal". RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 7 - IRON ORE FINES In the individual schedule for "IRON ORE FINES", in the table for "Characteristics", regarding bulk density, replace the words "1,500 to 3,000" with the words "1,500 to 3,500". METAL SULPHIDE CONCENTRATES, CORROSIVE UN 1759 In the individual schedule for "METAL SULPHIDE CONCENTRATES, CORROSIVE UN 1759", --- METAL SULPHIDE CONCENTRATES, CORROSIVE UN 1759 In the individual schedule for "METAL SULPHIDE CONCENTRATES, CORROSIVE UN 1759", under the BCSN, replace the words "Packing Group" with the words "packing group". METAL SULPHIDE CONCENTRATES, SELF-HEATING UN 3190 In the individual schedule for "METAL SULPHIDE CONCENTRATES, SELF -HEATING UN 3190", under the BCSN, replace the words "Packing Group" with the words "packing group". Mineral concentrates In the individual schedule for "Mineral concentrates", replace the words "NEFELENE SYENITE (mineral)" with the words "NEPHELINE SYENITE (mineral)". PITCH PRILL In the individual schedule for " PITCH

PRILL", in the section for "Emergency procedures", in the table, replace the word "overalls" with the word "coveralls". SUPERPHOSPHATE (triple, granular) Delete the individual schedule for "SUPERPHOSPHATE (triple, granular)". SYNTHETIC CALCIUM FLUORIDE --- SUPERPHOSPHATE (triple, granular) Delete the individual schedule for "SUPERPHOSPHATE (triple, granular)". SYNTHETIC CALCIUM FLUORIDE In the individual schedule for "SYNTHETIC CALCIUM FLUORIDE", under the section for "Description", replace "70%-80%" with the words "70% to 80%", replace "5% -10%" with the words "5% to 10%" and replace "10%-20%" with the words "10% to 20%". New individual schedules Insert the following new individual schedules in alphabetical order: "AMMONIUM NITRATE BASED FERTILIZER This schedule shall only apply to ammonium nitrate based fertilizers which do not meet any of the criteria on dangerous goods or materials hazardous only in bulk specified in 9.2.2 or 9.2.3 of this Code, respectively. Ammonium nitrate based fertilizers transported in conditions mentioned in this schedule are straight nitrogen fertilizers or compound fertilizers within the following composition limits: --- straight nitrogen fertilizers or compound fertilizers within the following composition limits: Straight nitrogen fertilizers containing less than 2% chloride, and .1 not more than 70% ammonium nitrate with other inorganic materials; or RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 8 - .2 not more than 80% ammonium nitrate mixed with calcium carbonate and/or dolomite and/or mineral calcium sulphate and not more than 0.4% total combustible organic material calculated as carbon; or .3 mixtures of ammonium nitrate and ammonium sulphate with not more than 45% ammonium nitrate and not more than 0. 4% total combustible organic material calculated as carbon. Compound NPK/NK/NP fertilizers .1 mixtures of nitrogen with phosphate and/or potash containing not more than 70% ammonium nitrate and not more than 0.4% total combustible --- .1 mixtures of nitrogen with phosphate and/or potash containing not more than 70% ammonium nitrate and not more than 0.4% total combustible organic material calculated as carbon or not more than 45% ammonium nitrate and unrestricted combustible material; and .2 either less than 20% of ammonium nitrate content or less than 2% of chloride (as indicated in the grey area of the figure for NPK/NP/NK fertilizers below). The shipper shall declare the ammonium nitrate content and the chloride content in accordance with 4.2 of this Code. Notwithstanding the above, fertilizers within these composition limits are not subject to the provisions of this schedule, if they are assigned class 9 due to the hazard of self -sustaining decomposition based on the results of the trough test (referred to in the UN Manual of Tests and Criteria, part III, section 39). Description Crystals, granules or prills. Non-cohesive when dry. Wholly or partly soluble in water. Common --- and Criteria, part III, section 39). Description Crystals, granules or prills. Non-cohesive when dry. Wholly or partly soluble in water. Common products, listed (non-exhaustive) under this schedule are: .1 calcium ammonium nitrate; .2 ammonium sulphate nitrate; .3 ammonium nitrate with other sulphates (e.g. calcium or magnesium sulphate); and .4 compound NPK/NP/NK fertilizer. % Ammonium nitrate % Chloride 70 % 20 % 2 % ..... .... RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 9 - Characteristics Physical properties Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t) 1 to 5 mm 27° to 42° 1,000 to 1,200 0.83 to 1.00 Hazard classification Class Subsidiary hazard(s) MHB Group Not applicable Not applicable Not applicable C Hazard When this cargo is heated strongly, it will decompose and give off toxic gases with the risk of --- Hazard When this cargo is heated strongly, it will decompose and give off toxic gases with the risk of toxic fumes in the cargo hold, adjacent spaces and on deck. If decomposition is initiated in alocalized area, it is highly unlikely to spread throughout the mass of the fertilizer. Fertilizer dust might be irritating to skin and mucous membranes. It is ahygroscopic cargo and will cake if wet. Stowage and segregation "Separated from" sources of heat. Hold cleanliness Clean and dry as relevant to the hazards of the cargo. Weather precautions This cargo shall be kept as dry as practicable. This cargo shall not be handled during precipitation. During handling of this cargo, all non -working hatches of the cargo spaces into which this cargo is loaded, or to be loaded, shall be closed. Loading Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code. Precautions --- Loading Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code. Precautions "NO SMOKING" signs shall be displayed on deck whenever this cargo is on board. Smoking shall not be allowed on deck and in the cargo spaces. No welding, burning, cutting or other operations involving the use of fire, open flame, spark or arc-producing equipment shall be carried out on equipment or structures in direct contact with the fertilizer. In order to avoid heating the cargo, all electrical equipment or other equipmen tcapable of developing heat, other than that of approved

safe type, in the cargo spaces to be used for this cargo shall be electrically disconnected from the power source, by appropriate means other than afuse, at apoint external to the space. This situation shall be maintained while the cargo is on board. Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo. --- is on board. Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo. Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Due consideration shall be given to protect equipment from the dust of the cargo. Persons who may be exposed to the dust of the cargo shall wear goggles or other equivalent dust eye -protection and dust filter masks. Those persons shall wear protective clothing, as necessary. RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 10 - Ventilation The cargo spaces carrying this cargo shall not be ventilated during voyage, except in an emergency. Carriage No special requirements. Discharge This cargo is hygroscopic and may cake in overhangs, impairing safety during discharge. If this cargo has hardened, it shall be trimmed to avoid the formation of overhangs, as necessary. Clean-up --- If this cargo has hardened, it shall be trimmed to avoid the formation of overhangs, as necessary. Clean-up After discharge of this cargo, the bilge wells and the scuppers of the cargo spaces shall be checked and any blockage in the bilge wells and the scuppers shall be removed." "AMMONIUM NITRATE BASED FERTILIZER MHB Ammonium nitrate based fertilizers transported under conditions mentioned in this schedule are uniform mixtures of nitrogen with or without potash and/or phosphate within th efollowing composition limits: .1 not more than 70% ammonium nitrate and not more than 0.4% total combustible organic material calculated as carbon or not more than 45% ammonium nitrate and unrestricted combustible material; and .2 both the ammonium nitrate content is equal to or greater than 20% and the chloride content is equal to or greater than 2% (as indicated in the grey area of the figure below). --- chloride content is equal to or greater than 2% (as indicated in the grey area of the figure below). The shipper shall declare the ammonium nitrate content and the chloride content in accordance with 4.2 of this Code. Notwithstanding the above, fertilizers within these composition limits are not subject to the provisions of this schedule, if they are assigned class 9 due to the hazard of self -sustaining decomposition based on the results o fthe trough test (referred to in the UN Manual of Tests and Criteria, part III, section 39). % Ammonium nitrate % Chloride 70 % 20 % 2 % RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 11 - Description Crystals, granules or prills. Non -cohesive when dry. Wholly or partly soluble in water. Common products listed under this schedule are compound NPK/NK fertilizers. Characteristics Physical properties --- Common products listed under this schedule are compound NPK/NK fertilizers. Characteristics Physical properties Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t) 1 to 5 mm 27° to 42° 1,000 to 1,200 0.83 to 1.00 Hazard classification Class Subsidiary hazard(s) MHB Group Not applicable Not applicable OH B Hazard Although this cargo passes the trough test (referred to in the UN Manual of Tests and Criteria, part III, section 39), and hence does not fall in class 9, when carried in bulk in large quantities, it may still be subject to decomposition if strongly heated from external sources. Once initiated, decomposition might gradually spread through the remainder of the cargo, producing large volumes of toxic gases. This cargo is not subject to an explosion hazard. Fertilizer dust might be irritating to skin and mucous membranes. It is hygroscopic cargo and will cake if wet. Stowage and segregation --- Fertilizer dust might be irritating to skin and mucous membranes. It is hygroscopic cargo and will cake if wet. Stowage and segregation ■Separated from■ sources of heat (see also Loading). Not to be stowed immediately adjacent to any tank, double bottom or pipe containing heated fuel oil, unless there are permanent means and procedures to monitor and control the temperature so that it does not exceed 50°C. Fertilizers of this type shall be stowed out of direct contact with ametal engine-room boundary. This may be done, for example, by using flame-retardant bags containing inert materials or by any equivalent arrangement approved by the competent authority of the country of origin. This requirement does not apply if the bulkhead is class A-60 or to short international voyages. The hatches of the cargo spaces, including those of 'tween decks, shall be kept free at all times. In case of an emergency, whenever this material is on board, opening the hatches must --- times. In case of an emergency, whenever this material is on board, opening the hatches must be enabled (see 9.3.1.13 of this Code). Hold cleanliness Clean and dry as relevant to the hazards of the cargo. Weather precautions This cargo shall be kept as dry as practicable. This cargo shall not be handled during precipitation. During handling of this cargo, all non -working hatches of the cargo spaces into which this

cargo is loaded, or is to be loaded, shall be closed. Loading Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code. Prior to loading, the following provisions shall be complied with In order to avoid heating up of the cargo, all electrical equipment or other equipment capable of developing heat, other than that of approved safe type, in the cargo spaces to be used for this cargo, shall be electrically disconnected from the power source, by appropriate means --- this cargo, shall be electrically disconnected from the power source, by appropriate means other than afuse, at apoint external to the space. This situation shall be maintained while the cargo is on board. RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 12 - Due consideration shall be given to the necessity to open hatches in case of decomposition to provide maximum ventilation, release pressure and heat, and slow down the reaction. During loading, the following provisions shall be complied with Organic contamination aggravates decomposition behaviour in the presence of sources of heat, and therefore bunkering of fuel oil shall not be allowed during loading. Pumping of fuel oil in spaces adjacent to the cargo spaces for this cargo, other than the engine-room, shall not be allowed. Precautions ■NO SMOKING■ signs shall be displayed on deck whenever this cargo is on board. Smoking --- engine-room, shall not be allowed. Precautions ■NO SMOKING■ signs shall be displayed on deck whenever this cargo is on board. Smoking shall not be allowed on deck and in the cargo spaces. No welding, burning, cutting or other operations involving the use of fire, open flame, spark or arc-producing equipment shall be carried out on equipment or structures in direct contact with the fertilizer. The master and officers are to note that the ship'sfixed gas fire -fighting installation will be ineffective on decompositions involving this cargo and must not be used. If decomposition is identified, water must be applied without delay. Injection to the seat of decomposition is the first control measure because it uses less water and can be more effective in early decomposition stages. Total flooding is the final control measure but can introduce stability and stress issues. The consequential risk to the stability of the ship through fluidization of the --- and stress issues. The consequential risk to the stability of the ship through fluidization of the cargo must be taken into account in both cases. Application of water to the surface of the cargo is much less effective and can give afalse sense of safety. Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo. Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Due consideration shall be given to protect equipment from the dust of the cargo. Persons who may be exposed to the dust of the cargo shall wear goggles or other equivalent dust eye-protection and dust filter masks. Those persons shall wear protective clothing, as necessary. Ventilation The cargo spaces carrying this cargo shall not be ventilated during the voyage, except in an emergency. Carriage There shall be adaily monitoring, recording and assessment of the trends of the cargo --- emergency. Carriage There shall be adaily monitoring, recording and assessment of the trends of the cargo temperature and oxygen concentration in the cargo space(s) throughout the voyage. Increase of temperature and decrease of oxygen concentration give an early indication of adecomposition. In addition, should decomposition occur, the residue left after decomposition may have only half the mass of the original cargo. Due consideration shall be given to the effect of the loss of mass on the stability of the ship. Discharge Organic contamination aggravates decomposition behaviour in the presence of sources of heat, and therefore bunkering of fuel oil shall not be allowed during discharge. Pumping of fuel oil in spaces adjacent to the cargo spaces for this cargo, other than the engine-room, shall not be allowed during discharge. RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 13 - --- RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 13 - This cargo is hygroscopic and may cake in overhangs, impairing safety during discharge. If this cargo has hardened, it shall be trimmed to avoid the formation of overhangs, as necessary. Clean-up After discharge of this cargo, the bilge wells and the scuppers of the cargo spaces shall be checked, and any blockage in the bilge wells and the scuppers shall be removed. Emergency procedures Special emergency equipment to be carried Protective clothing (boots, gloves, coveralls and headgear) Self-contained breathing apparatus Emergency procedures Wear protective clothing and self-contained breathing apparatus Emergency action in the event of fire or decomposition Decomposition in acargo space containing this material : The master and officers are to --- Emergency action in the event of fire or decomposition Decomposition in acargo space containing this material : The master and officers are to note that the ship'sfixed gas fire -fighting installation will b eineffective on decompositions

involving this cargo and must not be used. If decomposition is identified, water must be applied without delay. Injection to the seat of decomposition is the first control measure (e.g. using Victor lance) because it uses le ss water and can be more effective in early decomposition stages. Total flooding is the final control measure but can introduce stability and stress issues. The consequential risk to the stability of the ship through fluidization of the cargo must be taken into account in both cases. Application of water to the surface of the cargo is much less effective and can give afalse sense of safety. Fire in an adjacent cargo space : Heat transferred from fire in an adjacent space can cause --- and can give afalse sense of safety. Fire in an adjacent cargo space : Heat transferred from fire in an adjacent space can cause the material to decompose with consequent evolution of toxic fumes. Open hatches to provide maximum ventilation. Dividing bulkheads should be cooled. Medical first aid Refer to the Medical First Aid Guide (MFAG), as amended " "CLAM SHELL This schedule shall only apply to whole clam shells. Description This cargo is aby -product generated in the process of clam farming. Dark grey to beige, granular in form, not soluble, solid and natural material. Characteristics Physical properties Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t) 5 mm to 30 mm 34° 1,058 0.945 Hazard classification Class Subsidiary hazard(s) MHB Group Not applicable Not applicable Not applicable C RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 14 - --- RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE - 14 - Hazard No special hazards. This cargo is non-combustible or has alow fire risk. Stowage and segregation No special requirements. Hold cleanliness No special requirements. Weather precautions No special requirements. Loading Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code. Precautions No special requirements. Ventilation No special requirements. Carriage No special requirements. Discharge No special requirements. Clean-up After discharge of this cargo, the cargo spaces and the bilge wells shall be swept clean and then thoroughly washed out." "LEACH RESIDUE CONTAINING LEAD Description Intermediate by-product formed as aresult of the hydrometallurgical production of zinc and/or --- "LEACH RESIDUE CONTAINING LEAD Description Intermediate by-product formed as aresult of the hydrometallurgical production of zinc and/or zinc compounds. Insoluble grey to brown granular substance obtained during dissolution of zinc ores or concentrate in sulphuric acid to produce zinc sulphate solutions after physical separation such as flotation and filtration. Characteristics Physical properties Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t) Fines up to 100 µm 45° to 52° 800 to 1,600 0.63 to 1.25 Hazard classification Class Subsidiary hazards MHB Group Not applicable TX and CR Aand B Hazard This cargo may liquefy if shipped at amoisture content in excess of its transportable moisture limit (TML). See sections 7 and 8 of this Code. Harmful if swallowed or inhaled. RESOLUTION MSC.500(105) (adopted on 28 April 2022) AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE --- RESOLUTION MSC.502(105) (adopted on 28 April 2022) AMENDMENTS TO THE CODE OF SAFETY FOR SPECIAL PURPOSE SHIPS, 1983 (1983 SPS CODE) MSC 105/20/Add.1 Annex 9, page 1 I:\MSC\105\MSC 105-20-Add.1.docx ANNEX 9 RESOLUTION MSC.502(105) (adopted on 28 April 2022) AMENDMENTS TO THE CODE OF SAFETY FOR SPECIAL PURPOSE SHIPS, 1983 (1983 SPS CODE) THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO resolution A.534(13), by which the Assembly, at its thirteenth session, adopted the Code of Safety for Special Purpose Ships, 1983 (1983 SPS Code), RECALLING FURTHER that the Assembly authorized the Committee to amend the Code as may be necessary, NOTING the amendments to the International Convention for the Safety of Life