Amendments related to application 1 Existing paragraphs 1.1.2 and 1.1.3 are repla ce dby the following: "1.1. 2 Unless expressly provided otherwise, the Code applies. to ships the keels of which are laid or which are at astage at whi ch: .1 construction identifiable with the ship begins; and .2 assembly of that ship has commenced comprising at least 50 teunes or l' of the estimated mass of all structural mate rial, whichever is the less; on or after 1 July 1998. Ships constructed before 1 July 1998 are to comply with resolution MSC.5(48) adopted on 1 7 June 1963 subject to amendment sby r esolution MSC.30(61) adopted on 11 December 1992. 1.1.3 Aship. irrespective of the date of construction, which is converted to agas carrier on or after 1 July 1998, should be treated as agas carrier constructed on the date on which such conversion commences." Amendments related to fillipg limits 2 The existing chapter 15 is replaced by the following: "CHAPTER 15 FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks should have ahigher filling limit (FL) than 98' at the reference temperature, except as permitted by 15.1. 3. - "CHAPTER 15 FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks should have ahigher filling limit (FL) than 98' at the reference temperature, except as permitted by 15.1. 3. 15.1.2 The maximum loading limit (LL) to which acargo tank may be loaded should be determined by the following formula: LL where: LL FL PR FL PL loading limit exp ressed as ape rcentage, being the maximum allowable liguid volume rela tive to the tank volume to which the tank may be loaded; filling limit as specified i n 15.1.1 or 15.1.3; RESOLUTION MSC.32(63) adopted on 23 May 1994 ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK (IGC CODE) PR PL ~ 3 ~ relative density of cargo at the reference temperature: and relative density of cargo at the loading temperature and pressure. 15.1.3 The Administration may allow ahigher filling limit (FL) than the limit of 98' specified in 15.1.1 at the reference temperature, taking int oaccount the shape of the tank, arrangements of pressure relief valves, accuracy of level and temperature gauging and the difference between the - limit of 98' specified in 15.1.1 at the reference temperature, taking int oaccount the shape of the tank, arrangements of pressure relief valves, accuracy of level and temperature gauging and the difference between the loading temperature and the temperature corresponding to the vapour pressure of the cargo at the set pressure of the pressure relief valves, provided the conditions specified in 8.2.17 are maintained. 15.1.4 For the purposes of this chapter only, "reference temperature" means: .1 the temperature corresponding to the vapour pressure of the cargo at the set pressure of the pressure relief valves when DO cargo vapour pressure/temperature control as referred to in chapter 7 is provided; .2 the temperature of the cargo upon termination of loading, during transport. or at unloading, whichever is the greatest. when acargo vapour pressure/temperature control as referred to in chapter 7 is provided. If this reference temperatur