Design and Equipment at its thirty-seventh session, 1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the text of which is set out in the Annex to the present resolution and which supersedes resolution A.535(13); 2. RECOMMENDS that all Governments concerned take appropriate steps to implement the Guidelines. WIl648n/EWP RESOLUTION MSC.35(63) (adopted on 20 May 1994) ADOPTION OF GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS MSC 63/23/Add.l ANNEX 7 Page 2 1 PURPOSE ANNEX GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS 1.1 Under regulation V/15-1 of the 1974 SOLAS Convention, as amended by resolution MSC.31(63) in 1994, new and existing tankers of 20,000 tonnes deadweight and above shall be fitted with an emergency towing arrangement, the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization. - the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization. 1.2 The present Guidelines are intended to provide standards for the design and construction of emergency towing arrangements which Administrations are recommended to implement. 1.3 For existing tankers fitted with the emergency towing arrangements in accordance with resolution A.535(13), the existing towing arrangements forward of the ship may be retained, but the towing arrangements aft of the ship should be upgraded to comply with the requirements of the present Guidelines. 2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS 2.1 General The emergency towing arrangements should be so designed as to facilitate salvage and emergency towing operations on tankers primarily to reduce the risk of pollution. The arrangements should at all times be capable of rapid deployment in the absence of main power on the ship to be towed and easy - risk of pollution. The arrangements should at all times be capable of rapid deployment in the absence of main power on the ship to be towed and easy connection to the towing vessel. Figure 1 shows arrangements which may be used as reference. 2.2 Towing components The major components of the towing arrangements should consist of the following: Forward of ship"' Aft of ship Pick-up gear Towing pennant Chafing gear Fairlead Strongpoint Roller pedestal optional optional Yes Yes Yes Yes See paragraph 3.1.4. W/1648n/EWP Yes Yes Depending on design Yes Yes Depending on design Strength requirements Yes Yes Yes Yes RESOLUTION MSC.35(63) (adopted on 20 May 1994) ADOPTION OF GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS M6C 63/23/Add.1 ANNEX 7 Page 3 2.3 Strenqth of the towinq components 2.3.1 Towing components as specified in 2.2 for strength should have aworking strength of at least 1,000 kN for tankers of 20,000 tonnes - ANNEX 7 Page 3 2.3 Strenqth of the towinq components 2.3.1 Towing components as specified in 2.2 for strength should have aworking strength of at least 1,000 kN for tankers of 20,000 tonnes deadweight and over but less than 50,000 tonnes deadweight, and at least 2,000 kN for tankers of 50,000 tonnes deadweight "and over (working strength is defined as one half ultimate strength). The strength should be sufficient for all relevant angles of towline, i.e. up to 90 0 from the ship'scentreline to port and starboard and 30 0 vertical downwards. 2.3.2 Other components should have aworking strength sufficient to withstand the load to which such components may be subjected during the towing operation. 2.4 Lenqth of towinq pennant The towing pennant should have alength of at least twice the lightest seagoing ballast freeboard at the fairlead plus 50 m. 2.5 Location of stronqpoint and fairlead The bow and stern strongpoint and fair