THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO resolution A.328(IX), by which the Assembly, at its ninth session, adopted the Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk (Gas Carrier Code) and authorized the Committee to amend the Code as may be necessary, NOTING resolution MSC.32(63), by which the Committee adopted amendments to the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk (IGC Code), RECOGNIZING the need to bring the corresponding amendments to the Gas Carrier Code into force on the date on which the amendments to the IGC Code enter into force, - Liquefied Gases in Bulk (IGC Code), RECOGNIZING the need to bring the corresponding amendments to the Gas Carrier Code into force on the date on which the amendments to the IGC Code enter into force, HAVING CONSIDERED at its sixty-third session amendments to the Gas Carrier Code proposed by the Sub-Committee on Bulk Chemicals, 1. ADOPTS amendments to the Gas Carrier Code, the text of which is given in the Annex to the present resolution; 2. DETERMINES that the amendments should become effective on 1 July 1998 upon acceptance and entry into force of the corresponding amendments to the IGC Code adopted by resolution MSC.32(63). W/ 1648n / EWP RESOLUTION MSC.34(63) adopted on 23 May 1994 ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK MSC 63/23/Add.1 ANNEX 5 Page 2 ANNEX AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK 1 Existing chapter XV is replaced by the following: "CHAPTER XV FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks should have ahigher filling limit (FL) than 98% at - SHIPS CARRYING LIQUEFIED GASES IN BULK 1 Existing chapter XV is replaced by the following: "CHAPTER XV FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks should have ahigher filling limit (FL) than 98% at the reference temperature, except as permitted by 15.1.3. 15.1.2 The maximum loading limit (LL) to which acargo tank may be loaded should be determined by the following formula: LL where: LL = FL = = = FL loading limit expressed in percent which means the maximum allowable liquid volume relative to the tank volume to which the tank may be loaded; filling limit as specified in 15.1.1 or 15.1.3; relative density of cargo at the reference temperature; and relative density of cargo at the loading temperature and pressure. 15.1.3 The Administration may allow ahigher filling limit (FL) than the limit of 98% specified in 15.1.1 at the reference temperature, taking into account the shape of the tank, arrangement