THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, NOTING resolution MSC.391(95), by which it adopted the International Code of Safety for Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory under chapter II -1 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), and subsequent amendments adopted to the IGF Code, NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code, --- NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code, HAVING CONSIDERED, at its 109th session, amendments to the IGF Code proposed and circulated in accordance with article VIII(b)(i) of the Convention: 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the IGF Code, the text of which is set out in the annex to the present resolution; 2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the said amendments shall be deemed to have been accepted on 1 July 2027, unless, prior to that date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world'smerchant fleet have notified the Secretary -General of their objections to the amendments; --- tonnage of the world'smerchant fleet have notified the Secretary -General of their objections to the amendments; 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2028 upon their acceptance in accordance with paragraph 2 above; 4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention; 5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention. RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -2- ANNEX --- AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -2- ANNEX AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) PART A 2 General 2.2 Definitions 1 The following new paragraph 2.2.44 is added after paragraph 2.2.43: "2.2.44 Ship constructed on or after 1 January 2028 means: .1 for which the building contract is placed on or after 1 January 2028; or .2 in the absence of abuilding contract, the keels of which are laid or which are at asimilar stage of construction on or after 1 July 2028; or .3 the delivery of which is on or after 1 January 2032." PART A-1 Specific requirements for ships using natural gas as fuel 5 Ship design and arrangement 5.3 Regulations – General 2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before paragraph 5.3.3.6: --- 5.3 Regulations – General 2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before paragraph 5.3.3.6: "5.3.3.5.1 For ships with suction wells installed in fuel tanks, the bottom of the suction well may protrude into the vertical extent of the minimum distance specified in 5.3.3.5, provided that such wells are as small as practicable and the protrusion below the inner bottom plating does not exceed 25% of the depth of the double bottom or 350 mm, whichever is less." 3 In sub-paragraph 5.3.4.2, the definition of "H" is replaced by the following: "His the distance from baseline, in metres, to the lowermost boundary of the fuel tank excluding the suction well, if installed; and" 7 Material and general pipe design 7.3 Regulations for general pipe design 4 The following new paragraph 7.3.1.4 is inserted after paragraph 7.3.1.3 and the subsequent paragraphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6 accordingly: --- subsequent paragraphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6 accordingly: RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -3- "7.3.1.4 For ships constructed on or after 1 January 2028, pressure relief valves discharging liquid or gas from the piping system shall discharge into the fuel tanks whenever the tank MARVS pressure is lower than the setting of the pressure relief valves in accordance with the arrangements in 9.4.2, and shall be designed to ensure that the required discharge capacity is met. Alternatively, they may discharge to the vent mast, if means are provided to detect and dispose of any liquid that may flow into the vent system." 9 Fuel supply to consumers 9.4 Regulations on safety functions of gas supply system 5 The following new paragraph 9.4.2 is inserted after paragraph 9.4.1

and the --- 9.4 Regulations on safety functions of gas supply system 5 The following new paragraph 9.4.2 is inserted after paragraph 9.4.1 and the subsequent paragraphs 9.4.2 to 9.4.10 are renumbered as 9.4.3 to 9.4.11 accordingly: "9.4.2 For ships constructed on or after 1 January 2028, fuel tank inlets from pressure relief valve discharge lines, protecting the piping system according to 7.3.1.4, shall be provided with non-return valves in lieu of valves that are automatically operated when the safety system required in 15.2.2 is activated. Safe means for tank isolation during maintenance shall be available according to 18.3 without affecting the proper operation of pressure relief valves." 11 Fire safety 11.3 Regulations for fire protection 6 Paragraph 11.3.2 is replaced by the following: "11.3.2.1 Any boundary of accommodation spaces, service spaces, control stations, escape routes and machinery spaces, facing fuel tanks on open deck, shall be --- escape routes and machinery spaces, facing fuel tanks on open deck, shall be shielded by A -60 class divisions. The A -60 class divisions shall extend up to the underside of the deck of the navigation bridge. For ships constructed on or after 1 January 2028, any such boundary facing the fuel tank on the open deck which is separated by aminimum distance, as determined to the satisfaction of the Administration through aheat anal ysis to provide protection equivalent to an A -60 class division, shall be considered acceptable, and intermediate structures providing heat protection to the above spaces may also be considered acceptable. Notwithstanding the above-mentioned requirements: .1 for oil tankers and chemical tankers constructed on or after 1 January 2028, A -60 insulation, required by SOLAS regulation II - 2/9.2.4.2.5, shall be considered to meet the above -mentioned requirements provided that the fuel tank is located in the cargo area --- 2/9.2.4.2.5, shall be considered to meet the above -mentioned requirements provided that the fuel tank is located in the cargo area forward of accommodation spaces, service spaces, control stations, escape routes and machinery spaces. Consideration for the protection of accommodation block sides may be necessary; and .2 for ships constructed on or after 1 January 2028, where no source of gas release from the fuel containment system is considered possible, e.g. atype Ctank in which tank connections are in atank connection space, A-60 class shielding is not required. 11.3.2.2 Fuel tanks shall be segregated from cargo in accordance with the requirements of the International Maritime Dangerous Goods (IMDG) Code where fuel tanks are regarded as bulk packaging. For the purposes of stowage and segregation requirements of the IMDG Code, afuel tank on the open deck shall be considered as aclass 2.1 package." RESOLUTION MSC.567(109) (adopted on 6 December 2024) --- aclass 2.1 package." RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -4- 7 Paragraph 11.3.3.1 is replaced by the following: "11.3.3.1 Notwithstanding the last sentence in paragraph 11.3.3, for ships constructed on or after 1 January 202 8, the fuel storage hold space may be considered as acofferdam provided that: .1 the type Ctank is not located directly above machinery spaces of category Aor other rooms with high fire risk; and .2 the minimum distance to the A-60 boundary from the outer surface of the insulation system of atype Ctank or the boundary of the tank connection space, if any, is not less than 900 mm. For the vacuum insulated type Ctank, outer surface of the insulation system means outer surface of the outer shell." 12 Explosion prevention 12.5 Hazardous area zones 12.5.2 Hazardous area zone 1 --- outer surface of the outer shell." 12 Explosion prevention 12.5 Hazardous area zones 12.5.2 Hazardous area zone 1 8 Sub-paragraph 12.5.2.3 is replaced by the following: ".3 For ships constructed on or after 1 January 2028, areas on open deck, or semi-enclosed spaces on deck, within 3 mof any fuel tank outlet, gas or vapour outlet, bunker manifold valve, other fuel valve, fuel pipe flange, ventilation outlets from zone 1 spaces and fuel tank openings for pressure release provided to permit the flow of small volumes of gas or vapour mixtures caused by thermal variation; 9 The following new sub -paragraph 12.5.2.4 is inserted after sub -paragraph 12.5.2.3 and the subsequent sub -paragraphs 12.5.2.4 to 12.5.2.9 are renumbered as 12.5.2.5 to 12.5.2.10 accordingly: ".4 for ships constructed on or after 1 January 2028, areas on open deck, or semi -enclosed spaces on open deck above and in the vicinity of afuel tank vent mast outlet within avertical cylinder of --- deck, or semi -enclosed spaces on open deck above and in the vicinity of afuel tank vent mast outlet within avertical cylinder of unlimited height and 6 mradius centred upon the centre of the outlet, and within ahemisphere of 6 mradius below the outlet. Where it is not possible to maintain the above distances due to the size and layout of the ship, areduced zone can be accepted based on adispersion analysis, using 50% LEL criteria. Th ezone dimensions shall never be less than those given in 12.5.2.3, and shall include asurrounding zone 2 hazardous area meeting the dimensions given in 12.5.3.1." 12.5.3 Hazardous area zone 2 10 The following new paragraph 12.5.3.3 is added after paragraph

12.5.3.2: "12.5.3.3 In lieu of 12.5.3.1, for ships constructed on or after 1 January 2028, this zone includes spaces 4 mbeyond the cylinder and 4 mbeyond the hemisphere defined in 12.5.2.4". RESOLUTION MSC.567(109) (adopted on 6 December 2024) --- defined in 12.5.2.4". RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -5- 13 Ventilation 13.3 Regulations – General 11 Paragraph 13.3.5 is replaced by the following: "13.3.5 For ships constructed on or after 1 January 2028, air inlets for hazardous enclosed spaces shall be taken from areas that, except for the inlets, would be non-hazardous. Air inlets for non-hazardous enclosed spaces shall be taken from non-hazardous areas at least 1.5 maway from the boundaries of any hazardous area." 12 The following new paragraph 13.3.8 is inserted after paragraph 13.3.7 and the subsequent paragraphs 13.3.8 to 13.3.10 are renumbered as 13.3.9 to 13.3.11 accordingly: "13.3.8 For ships constructed on or after 1 January 2028: .1 where the ventilation ducts serving non -hazardous spaces pass through ahazardous space, the ducts shall be gastight and have --- .1 where the ventilation ducts serving non -hazardous spaces pass through ahazardous space, the ducts shall be gastight and have overpressure relative to that hazardous space; and .2 where the ventilation ducts serving hazardous spaces pass through less hazardous or non -hazardous spaces, the ducts shall be gastight and have underpressure relative to the less hazardous or non-hazardous spaces. Ventilation pipes serving hazardous spaces that pass through less hazardous or non -hazardous spaces are acceptable without the need for underpressure, provided that they are fully welded and designed in accordance with chapter 7." _____ RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) --- RESOLUTION MSC.563(108) (adopted on 23 May 2024) AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) MSC 108/20/Add.1 Annex 15, page 1 I:\MSC\108\MSC 108-20-Add.1.docx ANNEX 15 RESOLUTION MSC.563(108) (adopted on 23 May 2024) AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO that the Assembly, when adopting resolution A.689(17) on Testing of life-saving appliances, authorized the Committee to keep the annexed Recommendation on testing of life -saving appliances under review and to adopt, when appropriate, amendments thereto, RECALLING FURTHER that, since