the Maritime Safety Committee by resolution MSC.5(48), he reinafter referred to as “the International Gas Carrier Code”, as may be amended by the Organization; or - Committee by resolution MSC.5(48), he reinafter referred to as “the International Gas Carrier Code”, as may be amended by the Organization; or .2 chapter XIX of the Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Organization by resolution A.328(IX), herein after referred to as “the Gas Carrier Code”, as has been or may be amended by the Organization, whichever is applicable. RESOLUTION MSC.216(82) (adopted on 8 December 2006) AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED- 18 - PART B SUBDIVISION AND STABILITY Regulation 4 General 1 The damage stability requirements in pa rts B-1 through B-4 shall apply to cargo ships of 80 min length (L) and upwards and to all passenge rships regardless of length but shall exclude those cargo ships which are shown to co mply with subdivision and - ships of 80 min length (L) and upwards and to all passenge rships regardless of length but shall exclude those cargo ships which are shown to co mply with subdivision and damage stability regulations in other instruments developed by the Organization. 2 The Administration may, for aparticular ship or group of ships, accept alternative methodologies if it is satisfied that at least the same degree of safety as represented by these regulations is achieved. Any Admi nistration which allows such alternative methodologies shall communicate to the Organization particulars thereof. 3 Ships shall be as efficiently subdivided as is possible having regard to the nature of the service for which they are intended. The degree of subdivision shall vary with the subdivision length (Ls) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with th eships of greatest subdivision length (Ls), - subdivision length (Ls) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with th eships of greatest subdivision length (Ls), primarily engaged in the carriage of passengers. 4 Where it is proposed to fit decks, inner skins or longitudinal bulkheads of sufficient tightness to seriously restrict the flow of water, the Administration shall be satisfied that proper consideration is given to beneficial or adve rse effects of such structures in the calculations. PART B-1 STABILITY Regulation 5 Intact stability information 1 Every passenger ship regardless of si ze and every cargo ship having alength (L) of 24 mand upwards, shall be inclined upon its completion and the elements of its stability determined. 2 The Administration may allow the inclining test of an individual cargo ship to be dispensed with provided basic stability data are available from the inclining