THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO resolution A.886(21), by which the Assembly resolved that the functions of adopting performance standards and technical specifications, as well as amendments thereto, shall be performed by the Maritime Safety Committee on behalf of the Organization, RECALLING FURTHER resolution MSC.74(69), annex 3, by which the Committee adopted the Recommendation on performance standards for auniversal automatic identification system --- the Recommendation on performance standards for auniversal automatic identification system (AIS) to improve the safety of navigation, TAKING INTO ACCOUNT resolution A.1192(33), by which the Assembly urged Member States and all relevant stakeholders to promote actions to prevent illegal operations in the maritime sector by the "dark fleet" or "shadow fleet", RECOGNIZING the need for measures to prevent unauthorized entry or tampering of the ship'sidentity information in shipborne automatic identification systems (AIS), HAVING CONSIDERED, at its 109th session, the recommendation made by the Sub-Committee on Navigation, Communications and Search and Rescue at its eleventh session, 1 ADOPTS revised Performance standards for auniversal shipborne automatic identification system (AIS), set out in the annex to the present resolution; 2 RECOMMENDS that Governments ensure that AIS equipment conforms to performance standards not inferior to those specified in: --- 2 RECOMMENDS that Governments ensure that AIS equipment conforms to performance standards not inferior to those specified in: .1 the present resolution if the equipment is installed on: .1 new ships for which the building contract is placed on or after 1 January 2029, or in the absence of the contract, the keel of which is laid or which are at asimilar stage of construction on or after 1 January 2029; or .2 ships other than those ships prescribed in sub-paragraph .1 above, all installations of the specified type, having acontractual delivery date on or after 1 January 2029, or in the absence of acontractual delivery date to the ship, actually delivered to the ship on or after 1 January 2029; or .2 annex 3 to resolution MSC.74(69) if the equipment is installed on ships other than those prescribed in paragraph 2.1 above. RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) --- RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) MSC 109/22/Add.1 Annex 23, page 2 I:\MSC\109\22\MSC 109-22-Add.1.docx ANNEX PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) 1 Scope 1.1 These performance standards specify the requirements for the universal AIS. 1.2 The AIS should improve the safety of navigation by assisting in the efficient navigation of ships, protection of the environment, and operation of vessel traffic services (VTS), by satisfying the following functional requirements: .1 in aship-to-ship mode for collision avoidance; .2 as ameans for littoral States to obtain information about aship and its cargo; and .3 as a VTS tool, i.e. ship-to-shore (traffic management). 1.3 The AIS should be capable of providing to ships and to competent authorities --- .3 as a VTS tool, i.e. ship-to-shore (traffic management). 1.3 The AIS should be capable of providing to ships and to competent authorities information from the ship, automatically and with the required accuracy and frequency, to facilitate accurate tracking. Transmission of the data should be with the minimum involvement of aship'spersonnel and with ahigh level of availability. 1.4 The installation, in addition to meeting the requirements of the Radio Regulations, applicable ITU -R Recommendations and the general requirements as set out in resolution A.694(17), should comply with the following performance standards. 2 Functionality The system should be capable of operating in anumber of modes: .1 an "autonomous and continuous" mode for operation in all areas. This mode should be capable of being switched to/from one of the following alternate modes by acompetent authority; .2 an "assigned" mode for operation in an area subject to acompetent authority --- modes by acompetent authority; .2 an "assigned" mode for operation in an area subject to acompetent authority responsible for traffic monitoring such that the data transmission interval and/or time slots may be set remotely by that authority; and .3 a "polling" or controlled mode where the data transfer occurs in response to interrogation from aship or competent authority. 3 Capability 3.1 The AIS should comprise: .1 acommunication processor, capable of operating over arange of maritime frequencies, with an appropriate channel selecting and switching method, in support of both short- and long-range applications; RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) MSC 109/22/Add.1 Annex 23, page 3 I:\MSC\109\22\MSC 109-22-Add.1.docx .2 ameans of processing data from an

electronic position -fixing system which --- Annex 23, page 3 I:\MSC\109\22\MSC 109-22-Add.1.docx .2 ameans of processing data from an electronic position -fixing system which provides aresolution of one ten-thousandth of aminute of arc and uses the WGS-84 datum; .3 ameans to automatically input data from other sensors meeting the provisions as specified in paragraph 6.2; .4 ameans to input and retrieve data manually; .5 ameans of error checking the transmitted and received data; and .6 built-in test equipment (BITE). 3.2 The AIS should be capable of: .1 providing information automatically and continuously to acompetent authority and other ships, without involvement of ship'spersonnel; .2 receiving and processing information from other sources, including that from acompetent authority and from other ships; .3 responding to high -priority and safety -related calls with aminimum delay; and .4 providing positional and manoeuvring information at adata rate adequate to --- and .4 providing positional and manoeuvring information at adata rate adequate to facilitate accurate tracking by acompetent authority and other ships. 4 User interface To enable auser to access, select and display the information on aseparate system, the AIS should be provided with an interface conforming to an appropriate international marine interface standard. 5 Identification For the purpose of ship and message identification, the ship's Maritime Mobile Service Identity (MMSI) should be used. 6 Information 6.1 The information provided by the AIS should include: .1 Static: - IMO number1 - Call sign and name - Length and beam - Type of ship - Location of position -fixing antenna on the ship (aft of bow and port or starboard of centreline) 1 In accordance with IMO ship identification number scheme adopted by the Organization (resolution A.1117(30)). If not required to have an IMO number, an official flag State number may be used --- (resolution A.1117(30)). If not required to have an IMO number, an official flag State number may be used (refer to Recommendation ITU-R M.1371 for the entry of an official flag State number). RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) MSC 109/22/Add.1 Annex 23, page 4 I:\MSC\109\22\MSC 109-22-Add.1.docx .2 Dynamic: - Ship'sposition with accuracy indication and integrity status - Time in UTC 2 - Course over ground - Speed over ground - Heading - Navigational status (e.g. NUC, at anchor, etc. - manual input) - Rate of turn (where available) - Optional - Angle of heel (where available)3 - Optional - Pitch and roll (where available)3 .3 Voyage-related: - Ship'sdraught - Hazardous cargo (type)4 - Destination and ETA (at master'sdiscretion) - Optional - Route plan (waypoints)3 .4 Short safety-related messages .5 Equipment Identification message5 --- - Optional - Route plan (waypoints)3 .4 Short safety-related messages .5 Equipment Identification message5 6.2 Information update rates for autonomous mode The different information types are valid for adifferent time period and thus need adifferent update rate: - Static information: Every 6 minutes and on request - Dynamic information: Dependant on speed and course alteration according to table 1 - Voyage-related information: Every 6 minutes, when data has been amended and on request - Safety-related message: As required 2 Date to be established by receiving equipment. 3 Field not provided in basic message. 4 As required by acompetent authority. 5 The AIS equipment should broadcast aunique manufacturer equipment identification number, which should also be physically marked on the equipment. RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) MSC 109/22/Add.1 Annex 23, page 5 --- PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) MSC 109/22/Add.1 Annex 23, page 5 I:\MSC\109\22\MSC 109-22-Add.1.docx TABLE 1 Type of ship Reporting interval Ship at anchor 3 minutes Ship 0-14 knots 12 seconds Ship 0-14 knots and changing course 4 seconds Ship 14-23 knots 6 seconds Ship 14-23 knots and changing course 2 seconds Ship > 23 knots 3 seconds Ship > 23 knots and changing course 2 seconds Ship Reporting Capacity – the system should be able to handle aminimum of 2,000 reports per minute to adequately provide for all operational scenarios envisioned. 6.3 Security Asecurity mechanism should be provided to detect disabling and to prevent unauthorized alteration of input or transmitted data. To protect against unauthorized dissemination of data, the IMO guidelines (Guidelines and Criteria for Ship Reporting Systems6) should be followed. --- the IMO guidelines (Guidelines and Criteria for Ship Reporting Systems6) should be followed. Achange to the IMO ship identification number in the equipment should only be possible by an authorized manufacturer'sagent. 7 Permissible initialization period The installation should be operational within 2 minutes of switching on. 8 Power supply The AIS and associated sensors should be powered from the ship'smain source of electrical energy. In addition, it should be possible to operate the AIS and associated sensors from an alternative source of electrical energy. 9 Technical characteristics The technical characteristics of the AIS such as variable transmitter output power,

operating frequencies (dedicated internationally and selected regionally), modulation and antenna system should comply with the appropriate ITU-R Recommendations.7 *** 6 Resolution MSC.433(98). 7 ITU-R M.1371 series refer. RESOLUTION MSC.570(109) (adopted on 6 December 2024) --- *** 6 Resolution MSC.433(98). 7 ITU-R M.1371 series refer. RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) RESOLUTION MSC.570(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS) --- RESOLUTION MSC.569(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR THE RECEPTION OF MARITIME SAFETY INFORMATION AND SEARCH AND RESCUE RELATED INFORMATION BY MF AND HF DIGITAL NAVIGATIONAL DATA (NAVDAT) SYSTEM MSC 109/22/Add.1 Annex 12, page 1 I:\MSC\109\22\MSC 109-22-Add.1.docx ANNEX 12 RESOLUTION MSC.569(109) (adopted on 6 December 2024) PERFORMANCE STANDARDS FOR THE RECEPTION OF MARITIME SAFETY INFORMATION AND SEARCH AND RESCUE RELATED INFORMATION BY MF AND HF DIGITAL NAVIGATIONAL DATA (NAVDAT) SYSTEM THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee, RECALLING ALSO resolution A.886(21) on Procedure for the adoption of, and amendments to, performance standards and technical specifications, by which the Assem