RECALLING ALSO that the Assembly, at its thirteenth session, when adopting resolution A.535(13) concerning Recommendation on emergency towing requirements for tankers, requested the Committee to keep the Recommendation under review, in particular in respect to new towing concepts which may be introduced and to report as necessary to the Assembly,
NOTING that tankers, including oil tankers, gas carriers and chemical tankers, in emergencies such as complete mechanical breakdowns, may need to be

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
NOTING that tankers, including oil tankers, gas carriers and chemical tankers, in emergencies such as complete mechanical breakdowns, may need to be towed out of danger, and that technologically advanced towing arrangements have been developed since the adoption of resolution A.535(13), whose provisions need revision to incorporate new towing concepts,
NOTING ALSO that the new regulation V/15-1 of the International Convention for the Safety of Life at Sea, 1974, as adopted by the Committee in May 1994, requires that all tankers of not less than 20,000 tonnes deadweight shall be fitted with an emergency towing arrangement, the design and construction of which shall be approved by the Administration based on the Guidelines developed by the Organization,
HAVING CONSIDERED the recommendation made by the Sub-Committee on Ship Design and Equipment at its thirty-seventh session,
1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
Design and Equipment at its thirty-seventh session,
1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the text of which is set out in the Annex to the present resolution and which supersedes resolution A.535(13);
2. RECOMMENDS that all Governments concerned take appropriate steps to implement the Guidelines.
WII648n/EWP
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS MSC 63/23/Add.I
ANNEX 7
Page 2
1 PURPOSE
ANNEX
GUIDELINES FOR EMERGENCY TOWING
ARRANGEMENTS ON TANKERS
1.1 Under regulation V/15-1 of the 1974 SOLAS Convention, as amended by resolution MSC.31(63) in 1994, new and existing tankers of 20,000 tonnes deadweight and above shall be fitted with an emergency towing arrangement, the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization.

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization.
1.2 The present Guidelines are intended to provide standards for the design and construction of emergency towing arrangements which Administrations are recommended to implement.
1.3 For existing tankers fitted with the emergency towing arrangements in accordance with resolution A.535(13), the existing towing arrangements forward of the ship may be retained, but the towing arrangements aft of the ship should be upgraded to comply with the requirements of the present Guidelines.
2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS
2.1 General
The emergency towing arrangements should be so designed as to facilitate salvage and emergency towing operations on tankers primarily to reduce the risk of pollution. The arrangements should at all times be capable of rapid deployment in the absence of main power on the ship to be towed and easy

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
risk of pollution. The arrangements should at all times be capable of rapid deployment in the absence of main power on the ship to be towed and easy connection to the towing vessel. Figure 1 shows arrangements which may be used as reference.
2.2 Towing components
The major components of the towing arrangements should consist of the following:
Forward of ship"' Aft of ship
Pick-up gear
Towing pennant
Chafing gear
Fairlead
Strongpoint
Roller pedestal
optional
optional
Yes
Yes
Yes
Yes
See paragraph 3.1.4.
W/1648n/EWP
Yes
Yes
Depending on design
Yes
Yes
Depending on design
Strength requirements
Yes
Yes
Yes
Yes

(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS M6C 63/23/Add.1
ANNEX 7
Page 3
2.3 Strenqth of the towinq components
2.3.1 Towing components as specified in 2.2 for strength should have a working strength of at least 1,000 kN for tankers of 20,000 tonnes

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
ANNEX 7
Page 3
2.3 Strenqth of the towinq components
2.3.1 Towing components as specified in 2.2 for strength should have a working strength of at least 1,000 kN for tankers of 20,000 tonnes
deadweight and over but less than 50,000 tonnes deadweight, and at least 2,000 kN for tankers of 50,000 tonnes deadweight "and over (working strength is defined as one half ultimate strength). The strength should be sufficient for all relevant angles of towline, i.e. up to 90
0
from the ship's centreline to port and starboard and
30 0 vertical downwards.
2.3.2 Other components should have a working strength sufficient to withstand the load to which such components may be subjected during the towing operation.
2.4 Lenqth of towinq pennant
The towing pennant should have a length of at least twice the lightest seagoing ballast freeboard at the fairlead plus 50 m.
2.5 Location of stronqpoint and fairlead
The bow and stern strongpoint and fairleads should be located so as to

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
seagoing ballast freeboard at the fairlead plus 50 m.
2.5 Location of stronqpoint and fairlead
The bow and stern strongpoint and fairleads should be located so as to
facilitate towing from either side of the bow or stern and minimize the stress on the towing system.
2.6 Stronqpoint
The inboard end fastening should be a stopper or bracket or other fitting of equivalent strength. The strongpoint can be designed integral with the fairlead.
2.7 Fairleads
2.7.1 ~
2.7.2
2.7.3
Fairleads should have an opening large enough to pass the larqest portion of the chafing gear, towing pennant or towing line.
Geometry
The fairlead should give adequate support for the towing pennant

during towing operation which means bending 90
0
to port and to
starboard side and 30
0
vertical downwards. The bending ratio
(towing pennant bearing surface diameter to towing pennant diameter)
should be not less than 7 to 1.
Vertical location

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
starboard side and 30
0
vertical downwards. The bending ratio
(towing pennant bearing surface diameter to towing pennant diameter)
should be not less than 7 to 1.
Vertical location
The fairlead should be located as close as possible to the deck
and, in any case, in such a position that the chafing chain is
approximately parallel to the deck when it is under strain between
the strongpoint and the fairlead.