2.8 Chafing chain
Different solutions on design of chafing gear can be used. If a chafing chain is to be used, it should have the following characteristics:
2.8.1
The chafing chain should be stud link chain.
2.8.2 Length
2.8.3
2.8.4
The chafing chain should be long enough to ensure that the towing pennant remains outside the fairlead during the towing operation.

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
2.8.2 Length
2.8.3
2.8.4
The chafing chain should be long enough to ensure that the towing pennant remains outside the fairlead during the towing operation.
A chain extending from the strongpoint to a point at least 3 m beyond the fairlead should meet this criterion.
Connecting limits
One end of the chafing chain should be suitable for connection to the strongpoint. The other end should be fitted with a standard pear-shaped open link allowing connection to a standard bow shackle.
Stowage
The chafing chain should be stowed in such a way that it can be rapidly connected to the strongpoint.
2.9 Towing connection
The towing pennant should have a hard eye-formed termination allowing connection to a standard bow shackle.
2.10 Prototype test
Designs of emergency towing arrangements in accordance with these Guidelines should be prototype tested to the satisfaction of the Administration.
3 READY AVAILABILITY OF TOWING ARRANGEMENTS

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
Designs of emergency towing arrangements in accordance with these Guidelines should be prototype tested to the satisfaction of the Administration.
3 READY AVAILABILITY OF TOWING ARRANGEMENTS
3.1 To facilitate approval of such equipment and to ensure rapid deployment, emergency towing arrangements should comply with the following criteria:
.1 The aft emergency towing arrangement should be pre-rigged and be

capable of being deployed in a controlled manner in harbour
conditions in not more than 15 min .
. 2 The pick-up gear for the aft towing pennant should be designed at
least for manual operation by one person taking into account the
absence of power and the potential for adverse environmental
conditions that may prevail during such emergency towing
operations. The pick-up gear should be protected against the
weather and other adverse conditions that may prevail .
. 3 The forward emergency towing arrangement should be capable of

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
operations. The pick-up gear should be protected against the
weather and other adverse conditions that may prevail .
. 3 The forward emergency towing arrangement should be capable of
being deployed in harbour conditions in not more than 1 h.
W/1648n/EWP
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS ;
{
MSC 63/23/Add.1
ANNEX 7
Page 5
.4 The forward emergency towing arrangement should be designed at least
with a means of securing a towline to the chafing gear using a
suitably positioned pedestal roller to facilitate connection of the
towing pennant .
5 Forward emergency towing arrangements which comply with the
re'quirements for aft emergency towing arrangements may be accepted .
. 6 All emergency towing arrangements should be clearly marked to
facilitate safe and effective use even in darkness and poor
visibility.
3.2 All emergency towing components should be inspected by ship personnel at

---CHUNK---

SOURCE: MSC.35%2863%29.pdf
facilitate safe and effective use even in darkness and poor
visibility.
3.2 All emergency towing components should be inspected by ship personnel at
regular intervals and "maintained in good working order.
W/1648n/EWP
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS CHAFING GEAR
\
TOWED lJESSEL
TOWING PENNANT
FAIRLEAO TOWING CONNECT tON PICK UP GEAR
BUOY

FIGURE I TYPICAL EMERGENCY TOWING ARRANGEMENTS
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS

---CHUNK---

SOURCE: MEPC.285%2870%29.pdf
RESOLUTION MEPC.285(70)
(Adopted on 28 October 2016)
AMENDMENTS TO THE REVISED GUIDELINES AND SPECIFICATIONS FOR
POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES
OF SHIPS (RESOLUTION MEPC.107(49))MEPC 70/18/Add.1
Annex 21, page 1

https://edocs.imo.org/Final Documents/English/MEPC 70-18-ADD.1 (E).docx
ANNEX 21

RESOLUTION MEPC .285(70)
(Adopted on 28 October 2016)

AMENDMENTS TO THE REVISED GUIDELINES AND SPECIFICATIONS FOR
POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES
OF SHIPS (RESOLUTION MEPC.107(49))

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee (the Committee) conferred upon it by the international conventions for the prevention and control of marine pollution from ships,

NOTING resolution MEPC.107(49) by which it adopted, at its forty-ninth session, the Revised

---CHUNK---

SOURCE: MEPC.285%2870%29.pdf
pollution from ships,

NOTING resolution MEPC.107(49) by which it adopted, at its forty-ninth session, the Revised Guidelines and Specifications for pollution prevention equipment for machinery space bilges of ships,

HAVING CONSIDERED, at its seventieth session, proposed amendments to the above-mentioned Revised Guidelines and Specifications, concerning specifications related to 15 ppm bilge alarms,

1 ADOPTS amendments to the Revised Guidelines and specifications for pollution prevention equipment for machinery space bilges of ships , the text of which is set out in the annex to this resolution;

2 RECOMMENDS Governments to apply the annexed amendments when checking the accuracy of 15 ppm bilge alarms.

RESOLUTION MEPC.285(70)
(Adopted on 28 October 2016)
AMENDMENTS TO THE REVISED GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPS (RESOLUTION MEPC.107(49))MEPC 70/18/Add.1
Annex 21, page 2

---CHUNK---

SOURCE: MEPC.285%2870%29.pdf
AMENDMENTS TO THE REVISED GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPS (RESOLUTION MEPC.107(49))MEPC 70/18/Add.1
Annex 21, page 2