3.5 An inspection regime as defined in paragraphs 8.4 to 8.6 may not be relevant to a ship when idle for a longer period. To maintain the anti-fouling effect of an AFS, inspection and reactive cleaning may be needed before the ship is reactivated to reduce the risk of biofouling.

4 OBJECTIVES

4.1 The objective of these Guidelines is to minimize the transfer of invasive aquatic species through biofouling on ships.

4.2 Procedures, methods and actions taken in line with these Guidelines should

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
species through biofouling on ships.

4.2 Procedures, methods and actions taken in line with these Guidelines should safeguard the obligation under the United Nations Convention on the Law of the Sea (UNCLOS), article 194, to prevent, reduce and control pollution of the marine environment. This includes ensuring not to transfer, directly or indirectly, damage or hazards from one area to another, or transform one type of pollution into another (ref. UNCLOS article 195), as well as preventing the intentional or accidental introduction of species, alien or new, to a particular part of the marine environment (ref. UNCLOS article 196).

4.3 The objective of these Guidelines is pursued by providing a globally consistent approach to stakeholders on the control and management of biofouling, which will contribute to minimizing the risk of transferring invasive aquatic species from biofouling on ships.

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
approach to stakeholders on the control and management of biofouling, which will contribute to minimizing the risk of transferring invasive aquatic species from biofouling on ships.
An additional effect of good biofouling management can be a reduction in emissions to air from ships, due to lower fuel demand in operation as a result of a clean hull.

5 DESIGN AND CONSTRUCTION

5.1 Initial ship design and construction offers the most comprehensive, effective and long-lasting means to minimize ship biofouling risks. In the design and construction of a ship, or when a ship is being significantly modified, the following items, not e xhaustive, should be taken into consideration:

.1 small niches and sheltered areas should be avoided as far as practical, e.g. flush mounting pipes in sea chests (where not practical, these should be designed so that they may be easily accessed for inspection, cleaning and application of AFS like marine growth prevention systems (MGPS));

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
Date: .....

Location/port: .

Inspection organization/responsible officer: .

Inspection conditions: ..

Inspection equipment used: ...

Divers/ROV operators participating: .

Quantitative assessment of biofouling cover is summarized in table 3 (in line with the ratings in table 1)

Table 3: Quantitative assessment of biofouling cover
For each transect and niche area surveyed, the mode of the fouling rating (most frequent rating) and the range (lowest and highest rating) should be recorded. An average should not be used. If more than one of the same type of area is assessed, these should be recorded separately and each be given their own fouling rating.

Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
separately and each be given their own fouling rating.

Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most
frequent
rating
Hull below the waterline
Port vertical side
1 m wide belt
    1 m wide belt of subsection X
    1 m wide belt of subsection X
Starboard vertical side

1 m wide belt
1 m wide belt of subsection X
1 m wide belt of subsection X
Flat bottom front
1 m wide belt
1 m wide belt of subsection X
Flat bottom mid
1 m wide belt
1 m wide belt of subsection X
Flat bottom aft

Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
Annex 17, page 32

I:\MEPC\80\MEPC 80-17-Add.1.docx
Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most
frequent
rating
Hull below the waterline
1 m wide belt
1 m wide belt of subsection X
Niche areas
Bow
subsection X

Bow
subsection X

Bow thruster

Bilge keels
Sea chest gratings
    Location 1
    Location 2
Stern
Propeller and its shaft
Rudder and rudder shaft
Discharge pipes
Rope guards
Sounders/instruments
Sacrificial anodes
Internal seawater systems
..
..

An area should be assigned a fouling rating equal to the highest rated 1 m2 identified along the subdivided areas.

The inspection should be as comprehensive as practicable. The more subdivided areas that

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf