<flat-bottom- front,
flat-bottom- mid,
flat-bottom- aft, bow
dome, boot top,
vertical sides port
side, vertical sides
starboard side, vertical
side aft, transom, or
others>
<EXAMPLE>
<soft brush, blades, metal
brushes or water jet>
<EXAMPLE>
<MGPS (A)>
<EXAMPLE>
<Sea chests, internal
pipework, ballast
uptake system, inlet
gratings>
<EXAMPLE>
<Steaming>
<EXAMPLE>
<Other AFS>

<EXAMPLE>
<No AFS>

INSPECTION SCHEDULE OF HULL AND NICHE AREAS

An inspection will be carried out by organizations or personnel competent to undertake
inspections in line with the fixed intervals described below:

Inspection areas Initial inspection Subsequent inspections
<EXAMPLE>
<Areas installed with

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
inspections in line with the fixed intervals described below:

Inspection areas Initial inspection Subsequent inspections
<EXAMPLE>
<Areas installed with
AFS and operating
within the profile>

<EXAMPLE>
<Inspection within 12
months>
<When utilizing a
performance monitoring
system that indicates
adequate performance of
the AFS, an inspection will
be conducted within 18
months.
If the monitoring indicates
that the AFS is not
performing effectively, an
inspection should be
carried out as soon as
possible.>

<EXAMPLE>
<If rating 0-1 in previous inspection,
then inspection every 12-18 months
If rating 2, 3 or 4 in previous inspection,
then more frequent inspections>
<EXAMPLE>
<Areas with no AFS
and no other
measures>
<EXAMPLE>
<Inspection within 12
months>
<EXAMPLE>
<Inspection more frequent>

CLEANING

Reactive cleaning should be performed as a result of any inspection with a fouling

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
measures>
<EXAMPLE>
<Inspection within 12
months>
<EXAMPLE>
<Inspection more frequent>

CLEANING

Reactive cleaning should be performed as a result of any inspection with a fouling rating 2. It should be performed in line with procedures of the ship cleaning operator or the dry -dock facilities used, and the cleaning practices should be conducted in accordance with the jurisdiction's policies or regulations of the relevant au thority. Preferred cleaning methods and procedures that can be used are described below. The methods and cleaning operator used in each cleaning occasion should be

recorded in the BFRB.

Reactive
cleaning
method(s)
Areas where
cleaning method
will be applied
Operating
condition when

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
Annex 17, page 44

I:\MEPC\80\MEPC 80-17-Add.1.docx
Reactive
cleaning
method(s)
Areas where
cleaning method
will be applied
Operating
condition when
cleaning method
will be applied
Cleaning schedule
<EXAMPLE>
<Water jet and
suction with
capture in line
with <name of
the standard>>
<EXAMPLE>
<flat-bottom-
front, flat-bottom-
mid, flat-bottom-
aft, bow dome,
boot top, vertical
sides port side,
vertical sides
starboard side,
vertical side aft,
transom, or
others>

<EXAMPLE>
<moored in
harbour,
drifting in open
sea, on anchorage
in coastal waters,
on voyage>
<EXAMPLE>
<When recommended based on
monitoring of biofouling parameters
and/or
in case unforeseen biofouling
levels are detected on hull or in
niche areas>
<EXAMPLE>
<Steaming
with capture
performed in
line with
<name of the
standard>>
<EXAMPLE>
<Sea chests,