manual device
with soft brush
or other>
aft, bow dome,
boot top, vertical
sides port side,
vertical sides
starboard side,
vertical side aft,
transom, or
others>
sea, on anchorage
in coastal waters,
on voyage>

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
or other>
aft, bow dome,
boot top, vertical
sides port side,
vertical sides
starboard side,
vertical side aft,
transom, or
others>
sea, on anchorage
in coastal waters,
on voyage>
every <XX> days when operating
in tropical/semi-tropical waters;
when recommended based on
monitoring of biofouling
parameters; and
in case of unforeseen biofouling
levels defined as rating 1 are
detected on hull or in niche areas>
Possible harmful discharge
from cleaning with proactive
cleaning method
<EXAMPLE>
<AFC biocides, biofouling, particles or other>
Manufacturer and model of
ship-specific proactive cleaning
device, if applicable

Proactive cleaning method
suitable for AFC

Required maintenance and
frequency, as applicable

Proactive cleaning suitable for

typical operating profile, i.e. is the ship expected to stay enough time in locations where proactive cleaning can be carried out

Description of how to avoid biofouling cleaning and

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
typical operating profile, i.e. is the ship expected to stay enough time in locations where proactive cleaning can be carried out

Description of how to avoid biofouling cleaning and discharge of macrofouling, if possible

Proactive cleaning device tested in line with <name of the standard> (Y/N), if applicable

MONITORING OF BIOFOULING RISK PARAMETERS AND CONTINGENCY ACTIONS
Relevant digital tools applied for monitoring of biofouling risk parameters and/or digitalized real-data input are <describe the tools and data used for this ship>.
The biofouling risk parameters given below should be monitored when the ship is in operation. When a parameter goes beyond the deviation limit, the risk of biofouling is increased, and the recommended contingency actions should be used as described.
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
recommended contingency actions should be used as described.
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 47

I:\MEPC\80\MEPC 80-17-Add.1.docx
Biofouling risk parameters to monitor
Evaluation of a deviation including deviation limit of the

risk parameter
Contingency
actions
Long-term actions
<EXAMPLE>
<Deviation from speed
specifications
acceptable for the
AFS>
<EXAMPLE>
<Incidental deviations
should be evaluated
for potential biofouling
impact.
Continuous or regular
deviations, or
deviations not
rectified, should lead
to contingency
actions>.
<EXAMPLE>
<Shorter inspection
interval with
inspection every 4
months.
When recommended
by the AFS
manufacturer, more
frequent proactive
cleaning activities
could be
implemented
between
inspections.>
<EXAMPLE>
<Evaluate the need

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
inspection every 4
months.
When recommended
by the AFS
manufacturer, more
frequent proactive
cleaning activities
could be
implemented
between
inspections.>
<EXAMPLE>
<Evaluate the need
for a potential

improvement of the AFS selection prior to the next dry-docking.>
<EXAMPLE>
<Deviation from salinity specifications acceptable for the AFS>
<EXAMPLE>
<Incidental deviations should be evaluated for potential biofouling impact. Continuous or regular deviations, or deviations not rectified, should lead to contingency actions.>
<EXAMPLE>
<Shorter inspection interval with