SOURCE: MSC.216%2882%29.pdf
gangway and cargo ports, valves, pipes, ash-chut es and rubbish-chutes referred to in these regulations shall be to the satisfaction of the Administration;

.2 such valves, doors and mechanisms shall be suitably marked to ensure that they may be properly used to provide maximum safety; and

.3 the frames of vertical watertight doors shall have no groove at the bottom in which dirt might lodge and prevent the door closing properly.

2 In passenger ships and cargo ships wate rtight doors shall be tested by water pressure to a head of water they might sustain in a final or intermediate stage of flooding. Where testing of individual doors is not carried out because of possible damage to insulation or outfitting items, testing of i ndividual doors may be replaced by a prototype pressure test of each type and size of door w ith a test pressure corresponding at least to the head required for the intended location. Th e prototype test shall be carried out before

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
pressure test of each type and size of door w ith a test pressure corresponding at least to the head required for the intended location. Th e prototype test shall be carried out before the door is fitted. The installation met hod and procedure for fitting the door on board shall correspond to that of the prototype te st. When fitted on board, each door shall be checked for proper seating between the bulkhead, the frame and the door.

Regulation 16-1
Construction and initial tests of watertight decks, trunks, etc.

1 Watertight decks, trunks, tunnels, duct keels and ventilators shall be of the same strength as watertight bulkheads at corres ponding levels. The means used for making them watertight, and the arrangements adopted for closing openings in them, shall be to the satisfaction of the Administ ration. Watertight ventilator s and trunks shall be carried at least up to the bulkhead deck in passenge r ships and up to the freeboard deck in cargo ships.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
the satisfaction of the Administ ration. Watertight ventilator s and trunks shall be carried at least up to the bulkhead deck in passenge r ships and up to the freeboard deck in cargo ships.

2 Where a ventilation trunk passing thr ough a structure penetrates the bulkhead deck, the trunk shall be capable of withstandi ng the water pressure that may be present within the trunk, after havi ng taken into account the maximum heel angle allowable during intermediate stages of flooding, in accordance with regulation 7-2.

3 Where all or part of the penetration of the bulkhead deck is on the main ro-ro deck, the trunk shall be capable of withstandi ng impact pressure due to internal water motions (sloshing) of water trapped on the ro-ro deck.

4 After completion, a hose or flooding test sh all be applied to watertight decks and a

hose test to watertight trunks, tunnels and ventilators.

Regulation 17
Internal watertight integrity of passenger ships above the bulkhead deck

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
hose test to watertight trunks, tunnels and ventilators.

Regulation 17
Internal watertight integrity of passenger ships above the bulkhead deck

1 The Administration may require that all reasonable and practicable measures shall be taken to limit the entry and spread of water above the bulkhead deck. Such measures may include partial bulkheads or webs. When partial watertight bulkheads and webs are

fitted on the bulkhead deck, above or in the i mmediate vicinity of watertight bulkheads, they shall have watertight shell and bulkhead de ck connections so as to restrict the flow of water along the deck when the ship is in a heeled damaged condition. Where the partial watertight bulkhead does not line up with the bulkhea d below, the bulkhead deck

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
of water along the deck when the ship is in a heeled damaged condition. Where the partial watertight bulkhead does not line up with the bulkhea d below, the bulkhead deck between shall be made effec tively watertight. Where openi ngs, pipes, scuppers, electric cables etc. are carried through the partial watertight bulkheads or decks within the immersed part of the bulkhead deck, arrangemen ts shall be made to ensure the watertight integrity of the structure above the bulkhead deck.

2 All openings in the exposed weather deck shall have coamings of ample height and strength and shall be provided with effi cient means for expeditiously closing them weathertight. Freeing ports, open rails and sc uppers shall be fitted as necessary for rapidly clearing the weather deck of water under all weather conditions.

3 The open end of air pipes terminating within a superstructure shall be at least 1 m

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
rapidly clearing the weather deck of water under all weather conditions.

3 The open end of air pipes terminating within a superstructure shall be at least 1 m above the waterline when the ship heels to an angle of 15º, or the maximum angle of heel during intermediate stages of flooding, as de termined by direct calculation, whichever is the greater. Alternatively, air pipes from tanks other than oil tanks may discharge through the side of the superstructure . The provisions of this paragraph are without prejudice to the provisions of the International Convention on Load Lines in force.

4 Sidescuttles, gangway, cargo and fuelli ng ports and other means for closing openings in the shell plating above the bulkhead deck shall be of efficient design and construction and of sufficient strength having regard to the spaces in which they are fitted and their positions relative to the deepest subdivision draught.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
construction and of sufficient strength having regard to the spaces in which they are fitted and their positions relative to the deepest subdivision draught.

5 Efficient inside deadlights, so arranged that they can be easily and effectively closed and secured watertight, shall be provided for all side scuttles to spaces below the first deck above the bulkhead deck.

Regulation 17-1
Integrity of the hull and superstructure, damage prevention and control on ro-ro passenger ships

1.1 Subject to the provisions of paragraphs 1.2 and 1.3, all accesses that lead to spaces below the bulkhead deck shall have a lowest point which is not less than 2.5 m above the bulkhead deck.

1.2 Where vehicle ramps are installed to give access to spaces below the bulkhead deck, their openings shall be ab le to be closed weathertight to prevent ingress of water below, alarmed and indicated to the navigation bridge.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
deck, their openings shall be ab le to be closed weathertight to prevent ingress of water below, alarmed and indicated to the navigation bridge.

1.3 The Administration may permit the fitting of particular accesses to spaces below the bulkhead deck provided they are necessary for the essential working of the ship, e.g., the movement of machinery and stor es, subject to such accesses being made watertight, alarmed and indicated on the navigation bridge.

2 Indicators shall be provided on the navi gation bridge for all shell doors, loading doors and other closing appliances which, if left open or not properly secured, could, in the opinion of the Administration, lead to flooding of a special category space or ro-ro space. The indicator system shall be designed on the fail-safe principle and shall show by visual alarms if the door is not fully closed or if any of the securing arrangements are not

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
space. The indicator system shall be designed on the fail-safe principle and shall show by visual alarms if the door is not fully closed or if any of the securing arrangements are not in place and fully locked and by audible alarms if such door or closing appliances become

open or the securing arrangements become un secured. The indicator panel on the navigation bridge shall be equipped with a mode selection function harbour/sea voyage so arranged that an audible alarm is given on the navigation bridge if the ship leaves harbour with the bow doors, inner doors, stern ramp or any other side shell doors not closed or any closing device not in the co rrect position. The power supply for the indicator system shall be independent of the power supply for operating and securing the doors.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
closed or any closing device not in the co rrect position. The power supply for the indicator system shall be independent of the power supply for operating and securing the doors.

3 Television surveillance and a water leakag e detection system shall be arranged to provide an indication to the navigation bridge and to the en gine control station of any leakage through inner and outer bow doors, stern doors or any other shell doors which could lead to flooding of special category spaces or ro-ro spaces.

PART B-3
SUBDIVISION LOAD LINE ASSIGNMENT FOR PASSENGER SHIPS