Regulation 18
Assigning, marking and recording of subdivision load lines for passenger ships

1 In order that the required degree of s ubdivision shall be maintained, a load line corresponding to the approved s ubdivision draught shall be assigned and marked on the ships sides. A ship intended for alternat ing modes of operation may, if the owners

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
corresponding to the approved s ubdivision draught shall be assigned and marked on the ships sides. A ship intended for alternat ing modes of operation may, if the owners desire, have one or more additional load lines assigned and marked to correspond with the subdivision draughts which the Administration may approve fo r the alternative service configurations. Each service configuration so approved shall comply with part B-1 of this chapter independently of the results obtained for other modes of operation.

2 The subdivision load lines assigned and marked shall be recorded in the Passenger Ship Safety Certificate, and shall be dist inguished by the notation P1 for the principal passenger service configuration, and P2, P3, et c., for the alternative configurations. The principal passenger configuration shall be ta ken as the mode of operation in which the required subdivision index R will have the highest value.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
principal passenger configuration shall be ta ken as the mode of operation in which the required subdivision index R will have the highest value.

3 The freeboard corresponding to each of these load lines shall be measured at the same position and from the same deck line as the freeboards determined in accordance with the International Convention on Load Lines in force.

4 The freeboard corresponding to each approved subdivision load line and the service configuration, for which it is approved, shall be clearly indicated on the Passenger Ship Safety Certificate.

5 In no case shall any subdivision load lin e mark be placed a bove the deepest load line in salt water as determined by the strength of the ship or the International Convention on Load Lines in force.

6 Whatever may be the position of the subdivi sion load line marks, a ship shall in no case be loaded so as to submerge the load line mark appropriate to the season and locality

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
6 Whatever may be the position of the subdivi sion load line marks, a ship shall in no case be loaded so as to submerge the load line mark appropriate to the season and locality as determined in accordance with the International Convention on Load Lines in force.

7 A ship shall in no case be so loaded that when it is in salt water the subdivision load line mark appropriate to the partic ular voyage and service configuration is submerged.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-47 -

PART B-4
STABILITY MANAGEMENT

Regulation 19
Damage control information

1 There shall be permanently exhibited, or readily available on the navigation bridge, for the guidance of the officer in ch arge of the ship, plans showing clearly for each deck and hold the boundaries of the wate rtight compartments, the openings therein

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
bridge, for the guidance of the officer in ch arge of the ship, plans showing clearly for each deck and hold the boundaries of the wate rtight compartments, the openings therein with the means of closure and position of any controls thereof, and the arrangements for the correction of any list due to flooding. In addition, booklets containing the aforementioned information shall be made available to the officers of the ship.

2 Watertight doors in passenger ships permitted to remain open during navigation shall be clearly indicated in the ship's stability information.

3 General precautions to be included shal l consist of a listing of equipment, conditions, and operational procedures, considered by the Administration to be necessary to maintain watertight integrity under normal ship operations.

4 Specific precautions to be included shall consist of a listing of elements (i.e. closures, security of cargo, sounding of alarms, etc.) considered by the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
4 Specific precautions to be included shall consist of a listing of elements (i.e. closures, security of cargo, sounding of alarms, etc.) considered by the Administration to be vital to the survival of the ship, passengers and crew.

5 In case of ships to which damage stability requirements of part B-1 apply, damage stability information shall provide the mast er a simple and easily understandable way of assessing the ships survivability in all damage cases involving a compartment or group of compartments.

Regulation 20
Loading of passenger ships

1 On completion of loading of the ship and prior to its departure, the master shall determine the ships trim and stability and also ascertain and record that the ship is in compliance with stability criteria in relevant regulations. The determination of the ships stability shall always be made by calculation. The Administration may accept the use of

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
compliance with stability criteria in relevant regulations. The determination of the ships stability shall always be made by calculation. The Administration may accept the use of an electronic loading and stability computer or equivalent means for this purpose.

2 Water ballast should not in general be car ried in tanks intended for oil fuel. In ships in which it is not practicable to avoid putting water in oil fuel tanks, oily-water separating equipment to the satisfaction of th e Administration shall be fitted, or other alternative means, such as discharge to shor e facilities, acceptable to the Administration shall be provided for disposing of the oily-water ballast.

3 The provisions of this regulation are w ithout prejudice to th e provisions of the International Convention for the Prevention of Pollution from Ships in force.
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
International Convention for the Prevention of Pollution from Ships in force.
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-48 -

Regulation 21
Periodical operation and inspection of watertight doors, etc., in passenger ships

1 Drills for the operating of watertight doors, sidescuttles, valves and closing mechanisms of scuppers, ash-chutes and rubbish-chutes shall take place weekly. In ships in which the voyage exceeds one week in duration a complete drill shall be held before leaving port, and others thereafter at least once a week during the voyage.

2 All watertight doors, both hinged and power-operated, in watertight bulkheads, in use at sea, shall be operated daily.

3 The watertight doors and all mechanisms and indicators conn ected therewith, all valves, the closing of which is necessary to make a compartment watertight, and all

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
3 The watertight doors and all mechanisms and indicators conn ected therewith, all valves, the closing of which is necessary to make a compartment watertight, and all valves the operation of which is necessary fo r damage control cross connections shall be periodically inspected at sea at least once a week.

4 A record of all drills and inspections re quired by this regulation shall be entered in the log-book with an explicit record of any defects which may be disclosed.

Regulation 22
Prevention and control of water ingress, etc.

1 All watertight doors shall be kept closed during navi gation except that they may be opened during navigation as sp ecified in paragraphs 3 and 4. Watertight doors of a width of more than 1.2 m in machinery sp aces as permitted by regulation 13.10 may only be opened in the circumstances detailed in th at regulation. Any door which is opened in accordance with this paragraph shall be ready to be immediately closed.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
be opened in the circumstances detailed in th at regulation. Any door which is opened in accordance with this paragraph shall be ready to be immediately closed.

2 Watertight doors located below the bulkhead deck having a maximum clear opening width of more than 1.2 m shall be kept closed when the ship is at sea, except for limited periods when absolutely necessary as determined by the Administration.

3 A watertight door may be opened duri ng navigation to permit the passage of passengers or crew, or when work in the im mediate vicinity of the door necessitates it being opened. The door must be immediately closed when transit through the door is complete or when the task which necessitated it being open is finished.

4 Certain watertight doors may be permitted to remain open during navigation only