if considered absolutely necessary; that is, be ing open is determined essential to the safe

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
4 Certain watertight doors may be permitted to remain open during navigation only if considered absolutely necessary; that is, be ing open is determined essential to the safe and effective operation of the ships m achinery or to permit passengers normally unrestricted access throughout the passenger area. Such determination shall be made by the Administration only after careful consideration of the impact on ship operations and survivability. A watertight door permitted to re main thus open shall be clearly indicated in the ships stability information and shall always be ready to be immediately closed.

5 Portable plates on bulkheads shall always be in place before the ship leaves port, and shall not be removed during navigation except in case of urgent necessity at the discretion of the master. The necessary precautions shall be taken in replacing them to ensure that the joints are watertight. Power-operated sliding watertight doors permitted in

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
discretion of the master. The necessary precautions shall be taken in replacing them to ensure that the joints are watertight. Power-operated sliding watertight doors permitted in machinery spaces in accordance with regulati on 13.10 shall be closed before the ship leaves port and shall remain closed during navigation except in case of urgent necessity at the discretion of the master.
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-49 -

6 Watertight doors fitted in watertight bulkheads divi ding cargo between deck spaces in accordance with regulation 13.9.1 shall be closed before the voyage commences and shall be kept closed during navigation; the time of opening such doors in port and of closing them before the ship leaves port shall be entered in the logbook.

7 Gangway, cargo and fuelling ports fitted below the bulkhead deck shall be

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
closing them before the ship leaves port shall be entered in the logbook.

7 Gangway, cargo and fuelling ports fitted below the bulkhead deck shall be effectively closed and secured watertight befo re the ship leaves por t, and shall be kept closed during navigation.

8 The following doors, located above the bulkhead deck, sh all be closed and locked before the ship proceeds on any voyage and shal l remain closed and locked until the ship is at its next berth:

.1 cargo loading doors in the shel l or the boundaries of enclosed superstructures;

.2 bow visors fitted in positions as indicated in paragraph 8.1;

.3 cargo loading doors in th e collision bulkhead; and

.4 ramps forming an alternative closure to those defined in paragraphs 8.1 to 8.3 inclusive.

9 Provided that where a door cannot be opened or closed while the ship is at the berth such a door may be opened or left open while the ship appro aches or draws away

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
to 8.3 inclusive.

9 Provided that where a door cannot be opened or closed while the ship is at the berth such a door may be opened or left open while the ship appro aches or draws away
from the berth, but only so far as may be n ecessary to enable the door to be immediately operated. In any case, the inner bow door must be kept closed.

10 Notwithstanding the requirements of para graphs 8.1 and 8.4, the Administration may authorize that particular doors can be op ened at the discretion of the master, if necessary for the operation of the ship or the embarking and disembarking of passengers when the ship is at safe anchorage and provided that the safety of the ship is not impaired.

11 The master shall ensure that an effec tive system of supervision and reporting of the closing and opening of the doors referred to in paragraph 8 is implemented.

12 The master shall ensure, before the ship proceeds on any voyage, that an entry in

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
the closing and opening of the doors referred to in paragraph 8 is implemented.

12 The master shall ensure, before the ship proceeds on any voyage, that an entry in the log-book is made of the time of the last closing of the doors specified in paragraph 13 and the time of any opening of particular doors in accordance with paragraph 14.

13 Hinged doors, portable plates, sidescut tles, gangway, cargo and bunkering ports and other openings, which are required by these regulations to be kept closed during navigation, shall be closed before the ship leaves port. The time of closing and the time of opening (if permissible under these regulation s) shall be recorded in such log-book as may be prescribed by the Administration.

14 Where in a between-decks, the sills of a ny of the sidescuttles referred to in regulation 15.3.2 are below a line drawn parallel to the bulkhead deck at side and having

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
14 Where in a between-decks, the sills of a ny of the sidescuttles referred to in regulation 15.3.2 are below a line drawn parallel to the bulkhead deck at side and having

its lowest point 1.4 m plus 2.5% of the breadth of the ship above the water when the ship departs from any port, all the sidescuttles in that between-decks shall be closed watertight and locked before the ship leaves port, a nd they shall not be ope ned before the ship
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-


arrives at the next port. In the application of this paragraph the appropriate allowance for fresh water may be made when applicable.

.1 The time of opening such sidescuttles in port and of cl osing and locking them before the ship leaves port shall be entered in such log-book as may be prescribed by the Administration.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
.1 The time of opening such sidescuttles in port and of cl osing and locking them before the ship leaves port shall be entered in such log-book as may be prescribed by the Administration.

.2 For any ship that has one or more sidescuttles so placed that the requirements of paragraph 14 would apply when it was floating at its deepest subdivision draught, the Admi nistration may indicate the limiting mean draught at which these sidescuttles will have their sills above the line drawn parallel to the bul khead deck at side, and having its lowest point 1.4 m plus 2.5% of the breadth of the ship above the waterline corresponding to the limiting mean dr aught, and at which it will therefore be permissible to depart from port w ithout previously closing and locking them and to open them at sea on the re sponsibility of the master during the voyage to the next port. In tropical zones as defined in the International

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
them and to open them at sea on the re sponsibility of the master during the voyage to the next port. In tropical zones as defined in the International
Convention on Load Lines in force, this limiting draught may be increased by 0.3 m.

15 Sidescuttles and their deadlights which will not be accessible during navigation shall be closed and secured before the ship leaves port.

16 If cargo is carried in spaces referred to in regulation 15.5.2, the sidescuttles and their deadlights shall be closed watertight and locked before the cargo is shipped and such closing and locking shall be recorded in such log-book as may be prescribed by the Administration.

17 When a rubbish-chute, etc., is not in us e, both the cover and the valve required by regulation 15.10.2 shall be kept closed and secured.

Regulation 22-1
Flooding detection systems for passenger ships carrying 36 or more persons

constructed on or after 1 July 2010

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
regulation 15.10.2 shall be kept closed and secured.

Regulation 22-1
Flooding detection systems for passenger ships carrying 36 or more persons constructed on or after 1 July 2010

A flooding detection system for watertight spaces below the bulkhead deck shall be provided based on the guidelines developed by the Organization.

Regulation 23
Special requirements for ro-ro passenger ships

1 Special category spaces and ro-ro spaces shall be continuously patrolled or monitored by effective means, such as televi sion surveillance, so that any movement of vehicles in adverse weather conditions and unauthorized access by passengers thereto can be detected whilst the ship is underway.

2 Documented operating procedures for clos ing and securing all shell doors, loading doors and other closing appliances which, if left open or not properly secured, could, in the opinion of the Administration, lead to flooding of a special category space or ro-ro