the requirements set out in parts C, D and E, provided that the al ternative design and arrangements meet the intent of the requirements concerned and provide an equivalent level of safety to this chapter.

2.2 When alternative design or arrangements deviate from the prescriptive requirements of parts C, D and E, an engine ering analysis, evaluation and approval of the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
2.2 When alternative design or arrangements deviate from the prescriptive requirements of parts C, D and E, an engine ering analysis, evaluation and approval of the design and arrangements shall be carried out in accordance with this regulation.

3 Engineering analysis

The engineering analysis shall be prepared and submitted to the Administration, based on the guidelines developed by the Organizati on and shall include, as a minimum, the following elements:

.1 determination of the ship type, machinery, electrical installations and space(s) concerned;
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-54 -

.2 identification of the prescriptive re quirement(s) with which the machinery and electrical installations will not comply;

.3 identification of the reason th e proposed design will not meet the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
and electrical installations will not comply;

.3 identification of the reason th e proposed design will not meet the prescriptive requirements supported by compliance with other recognized engineering or industry standards;

.4 determination of the performance criteria for the ship, machinery, electrical installation or the space(s) concerned a ddressed by the relevant prescriptive requirement(s):

.1 performance criteria shall provide a level of safety not inferior to the relevant prescriptive require ments contained in parts C, D and E; and

.2 performance criteria shall be quantifiable and measurable;

.5 detailed description of the alternat ive design and arrangements, including a list of the assumptions used in the design and any proposed operational

restrictions or conditions;

.6 technical justification demonstrat ing that the alternative design and arrangements meet the safety performance criteria; and

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
restrictions or conditions;

.6 technical justification demonstrat ing that the alternative design and arrangements meet the safety performance criteria; and

.7 risk assessment based on identifica tion of the potential faults and hazards associated with the proposal.

4 Evaluation of the alternative design and arrangements

4.1 The engineering analysis required in paragraph 3 shal l be evaluated and approved by the Administration, taking into account the guidelines developed by the Organization.

4.2 A copy of the documentation, as approve d by the Administration, indicating that the alternative design and arrangements comply with this regulation, shall be carried on board the ship.

5 Exchange of information

The Administration shall communicate to the Organization pertinent information concerning alternative design and arrangements approved by them for circulation to all Contracting Governments.

6 Re-evaluation due to change of conditions

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
concerning alternative design and arrangements approved by them for circulation to all Contracting Governments.

6 Re-evaluation due to change of conditions

If the assumptions and operation al restrictions that were s tipulated in th e alternative design and arrangements are changed, the engi neering analysis shall be carried out under the changed condition and shall be approved by the Administration.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

CHAPTER II-2
CONSTRUCTION FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION

Regulation 3 Definitions

3 The following new paragraphs 51 and 52 ar e added after the existing paragraph 50:

51 Safe area in the context of a casualty is, from the perspective of habitability, any area(s) which is not flooded or which is outside the main vertical zone(s) in which a fire

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
51 Safe area in the context of a casualty is, from the perspective of habitability, any area(s) which is not flooded or which is outside the main vertical zone(s) in which a fire has occurred such that it can safely accomm odate all persons onboard to protect them from hazards to life or health and provide them with basic services.

52 Safety centre is a control station dedicated to the management of emergency situations. Safety systems operation, control and/or monitoring are an integral part of the safety centre.

Regulation 7 Detection and alarm

4 The following new paragraph 2.4 is a dded after the existing paragraph 2.3:

2.4 A fixed fire detection an d fire alarm system for passenger ships shall be capable of remotely and individually identifying each detector and manually operated call point.

5 In paragraphs 5.2 and 5.3.1, the following new text is added at the end of the paragraphs:

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
remotely and individually identifying each detector and manually operated call point.

5 In paragraphs 5.2 and 5.3.1, the following new text is added at the end of the paragraphs:

Detectors fitted in cabins, when activated, shall also be capable of emitting, or cause to be emitted, an audible alarm within the space where they are located.

Regulation 8 Control of smoke spread

6 In paragraph 2, the following new sentence is added at the end of the paragraph:

The ventilation system servi ng safety centres may be derived from the ventilation system serving the navigation bridge, unless located in an adjacent main vertical zone.

Regulation 9 Containment of fire

7 In paragraph 2.2.3.2.2 (7), the words Sale shops are deleted.

8 In paragraph 2.2.3.2.2 (8), the words Sale shops are added.

9 In the notes for tables 9.3 and 9.4, th e following sentence is added at the end of subscript c:

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
8 In paragraph 2.2.3.2.2 (8), the words Sale shops are added.

9 In the notes for tables 9.3 and 9.4, th e following sentence is added at the end of subscript c:

No fire rating is required for those partiti ons separating the navigation bridge and the safety centre when the latter is within the navigation bridge.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-56 -

10 The following new paragraph 2.2.7 is added after paragraph 2.2.6:

2.2.7 Protection of atriums

2.2.7.1 Atriums shall be within enclosures formed of A class divisions having a fire rating determined in accordance with tables 9.2 and 9.4, as applicable.

2.2.7.2 Decks separating spaces within atrium s shall have a fire rating determined in accordance with tables 9.2 and 9.4, as applicable.