11 The existing paragraph 7.5.1 is renumbered as paragraph 7.5.1.1 and the following new

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
accordance with tables 9.2 and 9.4, as applicable.

11 The existing paragraph 7.5.1 is renumbered as paragraph 7.5.1.1 and the following new paragraph 7.5.1.2 is added thereafter:

7.5.1.2 Exhaust ducts from ranges for cooking equipment installed on open decks shall conform to paragraph 7.5.1.1, as a pplicable, when passing through accommodation spaces or spaces containing combustible materials.

12 The following new paragraph 7.6 is adde d after the existing paragraph 7.5.2.1:

7.6 Ventilation systems for main laundries in ships carrying more than 36 passengers

Exhaust ducts from main laundries shall be fitted with:

.1 filters readily removable for cleaning purposes;

.2 a fire damper located in the lower end of the duct which is automatically and remotely operated;

.3 remote-control arrangements for shutting off the exhaust fans and supply fans from within the space and for op erating the fire damper mentioned in paragraph 7.6.2; and

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
.3 remote-control arrangements for shutting off the exhaust fans and supply fans from within the space and for op erating the fire damper mentioned in paragraph 7.6.2; and

.4 suitably located hatches for inspection and cleaning.

Regulation 10 Fire fighting

13 In the first sentence of paragraph 6.4, be tween the words equipment and shall, the words installed in enclosed spaces or on open decks are added.

Regulation 13 Means of escape

14 In paragraph 3.2.3, the words public spaces in the third sentence are deleted and the following new sentence is added before the fourth sentence:

Public spaces may also have direct access to stairway enclosures except for the backstage of a theatre.

15 The following new paragraph 3.2.5.3 is added after the existing paragraph 3.2.5.2:

3.2.5.3 In lieu of the escape route ligh ting system required by paragraph 3.2.5.1,

alternative evacuation guidance system s may be accepted if approved by the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
3.2.5.3 In lieu of the escape route ligh ting system required by paragraph 3.2.5.1, alternative evacuation guidance system s may be accepted if approved by the Administration based on the guidelines developed by the Organization.

16 The following new regulations 21, 22 and 23 are added after the existing regulation 20:
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

Regulation 21
Casualty threshold, safe return to port and safe areas

1 Application

Passenger ships constructed on or after 1 July 2010 having a length, as defined in regulation II-1/2.5, of 120 m or more or having three or more main vertical zones shall comply with the provisions of this regulation.

2 Purpose

The purpose of this regulation is to establish design criteria for a ships safe return to port

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
comply with the provisions of this regulation.

2 Purpose

The purpose of this regulation is to establish design criteria for a ships safe return to port under its own propulsion after a casualty that does not exceed the casualty threshold stipulated in paragraph 3 and also provi des functional requireme nts and performance standards for safe areas.

3 Casualty threshold

The casualty threshold, in the context of a fire, includes:

.1 loss of space of origin up to th e nearest A class boundaries, which may be a part of the space of origin, if the space of origin is protected by a fixed fire-extinguishing system; or

.2 loss of the space of origin and adja cent spaces up to the nearest A class boundaries, which are not part of the space of origin.

4 Safe return to port

When fire damage does not exceed the casualty threshold indicated in paragraph 3, the ship shall be capable of returning to port while providing a safe area as defined in

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
4 Safe return to port

When fire damage does not exceed the casualty threshold indicated in paragraph 3, the ship shall be capable of returning to port while providing a safe area as defined in regulation 3.51. To be deemed capable of returning to port, the following systems shall remain operational in the remaining part of the ship not affected by fire:

.1 propulsion;

.2 steering systems and steering-control systems;

.3 navigational systems;

.4 systems for fill, transfer and service of fuel oil;

.5 internal communication between the bridge, engineering spaces, safety centre, fire-fighting and damage cont rol teams, and as required for passenger and crew notification and mustering;

.6 external communication;

.7 fire main system;

.8 fixed fire-extinguishing systems;

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-58 -

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
.8 fixed fire-extinguishing systems;

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-58 -

.9 fire and smoke detection system;

.10 bilge and ballast system;

.11 power-operated watertight and semi-watertight doors;

.12 systems intended to support safe areas as indicated in paragraph 5.1.2;

.13 flooding detection systems; and

.14 other systems determined by the Ad ministration to be vital to damage control efforts.

5 Safe area(s)

5.1 Functional requirements:

.1 the safe area(s) shall generally be an internal space(s); however, the use of an external space as a safe area may be allowed by the Administration taking into account any restriction due to the area of operation and relevant expected environmental conditions;

.2 the safe area(s) shall provide a ll occupants with the following basic

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
taking into account any restriction due to the area of operation and relevant expected environmental conditions;

.2 the safe area(s) shall provide a ll occupants with the following basic services to ensure that the health of passengers and crew is maintained:

.1 sanitation;