.2 water;

.3 food;

.4 alternate space for medical care;

.5 shelter from the weather;

.6 means of preventing heat stress and hypothermia;

.7 light; and

.8 ventilation;

.3 ventilation design shall reduce the ri sk of smoke and hot gases that could affect the use of the safe area(s); and

.4 means of access to life-saving applia nces shall be provided from each area identified or used as a safe area, ta king into account that a main vertical zone may not be available for internal transit.

5.2 Alternate space for medical care

Alternate space for medical care shall co nform to a standard acceptable to the Administration.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
5.2 Alternate space for medical care

Alternate space for medical care shall co nform to a standard acceptable to the Administration.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-59 -

Regulation 22
Design criteria for systems to remain operational after a fire casualty

1 Application

Passenger ships constructed on or after 1 July 2010 having a length, as defined in regulation II-1/2.2, of 120 m or more or having three or more main vertical zones shall comply with the provisions of this regulation.

2 Purpose

The purpose of this regulation is to provide desi gn criteria for systems required to remain operational for supporting the orderly evacua tion and abandonment of a ship, if the casualty threshold, as defined in regulation 21.3, is exceeded.

3 Systems

3.1 In case any one main vertical zone is unserviceable due to fire, the following

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
casualty threshold, as defined in regulation 21.3, is exceeded.

3 Systems

3.1 In case any one main vertical zone is unserviceable due to fire, the following systems shall be so arranged and segregated as to remain operational:

.1 fire main;

.2 internal communications (in support of fire-f ighting as required for passenger and crew notification and evacuation);

.3 means of external communications;

.4 bilge systems for removal of fire-fighting water;

.5 lighting along escape routes, at as sembly stations and at embarkation stations of life-saving appliances; and

.6 guidance systems for evacuation shall be available.

3.2 The above systems shall be capable of operation for at least 3 h based on the assumption of no damage outside the unservic eable main vertical zone. These systems are not required to remain operational within the unserviceable main vertical zones.

3.3 Cabling and piping within a trunk constr ucted to an A-60 standard shall be

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
are not required to remain operational within the unserviceable main vertical zones.

3.3 Cabling and piping within a trunk constr ucted to an A-60 standard shall be deemed to remain intact and serviceable while passing through the unserviceable main vertical zone for the purposes of paragraph 3. 1. An equivalent de gree of protection for cabling and piping may be approved by the Administration.

Regulation 23
Safety centre on passenger ships

1 Application

Passenger ships constructed on or after 1 July 2010 shall have on board a safety centre complying with the requirements of this regulation.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-60 -

2 Purpose

The purpose of this regulation is to provide a space to assist with the management of emergency situations.

3 Location and arrangement

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
2 Purpose

The purpose of this regulation is to provide a space to assist with the management of emergency situations.

3 Location and arrangement

The safety centre shall either be a part of the navigation bridge or be located in a separate space adjacent, but having direct access, to the navigation bridge, so that the management of emergencies can be performed without distracting watch officers from their navigational duties.

4 Layout and ergonomic design

The layout and ergonomic design of the sa fety centre shall take into account the guidelines developed by the Organization, as appropriate.

5 Communications

Means of communication between the safety centre, the central control station, the navigation bridge, the engine control room, the storage room(s) for fire-extinguishing system(s) and fire equipment lockers shall be provided.

6 Control and monitoring of safety systems

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
navigation bridge, the engine control room, the storage room(s) for fire-extinguishing system(s) and fire equipment lockers shall be provided.

6 Control and monitoring of safety systems

Notwithstanding the requirements set out elsewhere in the Convention, the full functionality (operation, contro l, monitoring or any combinati on thereof, as required) of the safety systems listed below shall be available from the safety centre:

.1 all powered ventilation systems;

.2 fire doors;

.3 general emergency alarm system;

.4 public address system;

.5 electrically powered ev acuation guidance systems;

.6 watertight and semi-watertight doors;

.7 indicators for shell doors, loadi ng doors and other closing appliances;

.8 water leakage of inner/outer bow doors, stern doors and any other shell door;

.9 television surveillance system;

.10 fire detection and alarm system;

.11 fixed fire-fighting local application system(s);

---CHUNK---