2.2 Nitrogen oxides (NOx) (regulation 13)

2.2.1 The following marine diesel engines installed on this ship are in accordance with the requirements of regulation 13, as indicated:

Applicable regulation of MARPOL Annex VI
(NTC = NOx Technical Code 2008)
(AM = approved method)
Engin
e #1
Engin
e #2
Engin
e #3
Engin
e #4
Engin
e #5
1 Manufacturer and model
2 Serial number
3 Use (applicable application cycle(s) NTC
3.2)

4 Rated power (kW) (NTC 1.3.11)
5 Rated speed (rpm) (NTC 1.3.12)
6 Identical engine installed 1/1/2000
exempted by 13.1.1.2

7 Identical engine installation date (dd/mm/yyyy)
as per 13.1.1.2

8a
Major conversion
(dd/mm/yyyy)
13.2.1.1 & 13.2.2
8b 13.2.1.2 & 13.2.3
8c 13.2.1.3 & 13.2.3
9a

Tier I
13.3

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
as per 13.1.1.2

8a
Major conversion
(dd/mm/yyyy)
13.2.1.1 & 13.2.2
8b 13.2.1.2 & 13.2.3

8c 13.2.1.3 & 13.2.3
9a

Tier I
13.3
9b 13.2.2
9c 13.2.3.1
9d 13.2.3.2
9e 13.7.1.2
10a

Tier II
13.4
10b 13.2.2
10c 13.2.2 (Tier III not
possible)

10d 13.2.3.2
10e 13.5.2 (Exemptions)
10f 13.7.1.2
11a
NOx Tier III Emission
Control Areas
13.5.1.1
11b 13.2.2
11c 13.2.3.2
11d 13.7.1.2
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 54 -

Applicable regulation of MARPOL Annex VI
(NTC = NOx Technical Code 2008)
(AM = approved method)
Engin
e #1
Engin
e #2
Engin
e #3
Engin
e #4
Engin
e #5
12

AM

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
Applicable regulation of MARPOL Annex VI
(NTC = NOx Technical Code 2008)
(AM = approved method)
Engin
e #1
Engin
e #2
Engin
e #3
Engin
e #4
Engin
e #5
12

AM
installed
13 not commercially available
at this survey

14 not applicable

2.3 Sulphur oxides (SOx) and particulate matter (regulation 14)

2.3.1 When the ship operates outside of an emission control area specified in regulation 14.3, the ship uses:

.1 fuel oil with a sulphur content as documented by bunker delivery notes that does not exceed the limit value of 0.50% m/m, and/or .....

.2 an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6 that is at least as effective in terms of SOx emission reductions as compared to using a fuel oil with a sulphur content limit value of 0.50% m/m .....

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
reductions as compared to using a fuel oil with a sulphur content limit value
of 0.50% m/m .....

2.3.2 When the ship operates inside an emission control area specified in regulation 14.3, the ship uses:

.1 fuel oil with a sulphur content as documented by bunker delivery notes that does not exceed the limit value of 0.10% m/m,
and/or .

.2 an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6 that is at least as effective in terms of SOx emission reductions as compared to using a fuel oil with a sulphur content limit value of 0.10% m/m ...

2.3.3 For a ship wit hout an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6, the sulphur content of fuel oil carried for use on board the ship shall not exceed 0.50% m/m as documented by bunker delivery

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
regulation 4.1 as listed in paragraph 2.6, the sulphur content of fuel oil carried for use on board the ship shall not exceed 0.50% m/m as documented by bunker delivery notes ....

2.3.4 The ship is fitted with designated sampling point(s) in accordance with regulation 14.10 or 14.11.....

2.3.5 In accordance with regulation 14.12, t he requirement for fitting or designating sampling point(s) in accordance with regulation 14.10 or 14.11 is not applicable for a fuel oil service system for a low-flashpoint fuel for combustion purposes for propulsion or operation on board the ship .....

2.4 Volatile organic compounds (VOCs) (regulation 15)

2.4.1 The tanker has a vapour collection system installed and approved in accordance with MSC/Circ.585.....