SOURCE: MEPC.328%2876%29.pdf
" 20% plastic.

The mixture will have up to 50% moisture and
7% incombustible solids.

2 Incinerators described in regulation 16.6.1 shall operate within the following limits:

O2 in combustion chamber:

6 -12%
CO in flue gas maximum average:

200 mg/MJ
Soot number maximum average: Bacharach 3 or Ringelmann 1
(20% opacity) (a higher soot number is
acceptable only during very short periods
such as starting up)

Unburned components in ash residues:

Maximum 10% by weight
Combustion chamber flue gas outlet
temperature range:
850 -1200°C

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 61 -

Appendix V

Information to be included in the bunker delivery note (regulation 18.5)

1 Name and IMO number of receiving ship

2 Port

3 Date of commencement of delivery

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
Appendix V

Information to be included in the bunker delivery note (regulation 18.5)

1 Name and IMO number of receiving ship

2 Port

3 Date of commencement of delivery

4 Name, address and telephone number of marine fuel oil supplier

5 Product name(s)

6 Quantity in metric tonnes

7 Density at 15°C (kg/m3)

8 Sulphur content (% m/m)

9 A declaration signed and certified by the fuel oil supplier's representative that the fuel oil supplied is in conformity with regulation 18.3 of this Annex and that the sulphur content of the fuel oil supplied does not exceed:

the limit value given by regulation 14.1 of this Annex;

the limit value given by regulation 14.4 of this Annex; or

the purchaser's specified limit value of _____ (% m/m), as completed by the fuel oil supplier 's representative and on the basis of the purchaser 's notification that the fuel oil:

.1 is intended to be used in combinat ion with an equivalent means of

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
fuel oil supplier 's representative and on the basis of the purchaser 's notification that the fuel oil:

.1 is intended to be used in combinat ion with an equivalent means of compliance in accordance with regulation 4 of this Annex; or

.2 is subject to a relevant exemption for a ship to conduct trials for sulphur oxides emission reduction and control technology research in accordance with regulation 3.2 of this Annex.

The declaration shall be completed by the fuel oil supplier's representative by marking the applicable box(es) with a cross (x).
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 62 -

Appendix VI

Verification procedures for a MARPOL Annex VI fuel oil sa mple (regulation 18.8.2 or regulation 14.8)

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 62 -

Appendix VI

Verification procedures for a MARPOL Annex VI fuel oil sa mple (regulation 18.8.2 or regulation 14.8)

The following relevant verification procedure shall be used to determine whether the fuel oil delivered to, in use or carried for use on board a ship has met the applicable sulphur limit of regulation 14 of this Annex.

This appendix refers to the following representative MARPOL Annex VI fuel oil samples:

Part 1 sample of fuel oil delivered in accordance with regulation 18.8.1, hereafter referred to as the "MARPOL delivered sample" as defined in regulation 2.1.22.

Part 2 sample of fuel oil in use, intended to be used or carried for use on board in accordance with regulation 14.8, hereafter referred to as the "in-use sample " as defined in regulation 2.1.16 and "onboard sample" as defined in regulation 2.1.24.

Part 1 MARPOL delivered sample

1 General Requirements

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
defined in regulation 2.1.16 and "onboard sample" as defined in regulation 2.1.24.

Part 1 MARPOL delivered sample

1 General Requirements

1.1 The representative sample of the fuel oil, which is required by regulation 18.8.1 (the MARPOL delivered sample), shall be used to verify the sulphur content of the fuel oil delivered to a ship.

1.2 A Party, through its competent authority, shall manage the verification procedure.

1.3 A laboratory undertaking the sulphur testing procedure given in this appendix shall have valid accreditation in respect of the test method to be used.

2 Verification Procedure Part 1

2.1 The MARPOL delivered sample shall be conveyed by the competent authority to the laboratory.

2.2 The laboratory shall:

.1 record the details of the seal number and the sample label on the test record;

.2 record the condition of the seal of the sample as received on the test record; and

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
.1 record the details of the seal number and the sample label on the test record;

.2 record the condition of the seal of the sample as received on the test record; and

.3 reject any sample where the seal has been broken prior to receipt and record that rejection on the test record.

2.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

.1 unseal the sample;

.2 ensure that the sample is thoroughly homogenized;

.3 draw two subsamples from the sample; and

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 63 -