6.1.3 A fixed pressure water-spraying fire-e xtinguishing system complying with the provisions of the Fire Safety Systems Code sh all be installed on cabin balconies of ships to which regulation 5.3.4 applies, where furnitu re and furnishings on such balconies are not as defined in regulations 3.40.1, 3.40.2, 3.40.3, 3.40.6 and 3.40.7.

CHAPTER III
LIFE-SAVING APPLIANCES AND ARRANGEMENTS

Regulation 6 Communications

21 Paragraph 4.3 is replaced by the following:

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
CHAPTER III
LIFE-SAVING APPLIANCES AND ARRANGEMENTS

Regulation 6 Communications

21 Paragraph 4.3 is replaced by the following:

4.3 The general emergency alarm system shall be audible throughout all the accommodation and normal crew working spaces. On passenger ships, the system shall also be audible on all open decks.

Regulation 11 Survival craft muster and embarkation arrangements

22 In the first sentence of paragraph 7, the word unfavourable is replaced by the word all and the unit ° is inserted after the terms 10 and 20.

Regulation 14 Stowage of rescue boats

23 The words , and if the inflated type, in a fully inflated condition at all times are added at the end of subparagraph .1.

Regulation 19 Emergency training and drills

24 Paragraph 3.3.4 is replaced by the following:

3.3.4 In the case of a lifeboat arranged for free-fall launching, at least once every three

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Regulation 19 Emergency training and drills

24 Paragraph 3.3.4 is replaced by the following:

3.3.4 In the case of a lifeboat arranged for free-fall launching, at least once every three months during an abandon ship drill, the crew shall board the lifeboat, properly secure themselves in their seats and commence launch procedures up to, but not including, the actual release of the lifeboat (i .e., the release hook shall not be releas ed). The lifeboat shall then either be free-fall launched with only the required opera ting crew on board, or

lowered into the water by means of the seconda ry means of launching with or without the
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-
7 -

operating crew on board. In both cases, the lif eboat shall thereafter be manoeuvred in the water by the operating crew. At intervals of not more than six months, the lifeboat shall

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
operating crew on board. In both cases, the lif eboat shall thereafter be manoeuvred in the water by the operating crew. At intervals of not more than six months, the lifeboat shall either be launched by free-fall with only the operating crew on board, or simulated launching shall be carried out in accordance with the guidelines developed by the Organization.

Regulation 20 Operational readiness, maintenance and inspections

25 Paragraphs 4.1 and 4.2 are replaced by the following:

Falls used in launching shall be inspected periodically with special regard for areas passing through sheaves, and renewed when necessa ry due to deteriora tion of the falls or at intervals of not more than 5 years, whichever is the earlier.

26 In the third sentence of paragraph 6.2, the wo rds it should be run for such period as prescribed in the manufacturers handbook are repl aced by the words a suitable water supply may be provided.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
prescribed in the manufacturers handbook are repl aced by the words a suitable water supply may be provided.

27 The heading of paragraph 8 is replaced by the following:

8 Servicing of inflatable liferafts, inflat able lifejackets, marine evacuation systems and maintenance and repair of inflated rescue boats

28 The second sentence of paragraph 11.1.3 is replaced by the following:

The load to be applied shall be the mass of the survival craft or rescue boat without persons on board, except that, at intervals not exceeding five years, the test shall be carried out with a proof load equal to 1.1 times the weight of the surv ival craft or rescue boat and its full complement of persons and equipment.

29 The chapeau of paragraph 11.2 is replaced by the following:

11.2 Lifeboat or rescue boat on-load releas e gear, including free- fall lifeboat release systems, shall be:

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
29 The chapeau of paragraph 11.2 is replaced by the following:

11.2 Lifeboat or rescue boat on-load releas e gear, including free- fall lifeboat release systems, shall be:

30 In the first sentence of paragraph 11.2.3, th e word lifeboat is replaced by the word boat.

31 The following new paragraph 11.3 is added to the regulation:

11.3 Davit-launched liferaft auto matic release hooks shall be:

.1 maintained in accordance with instru ctions for on-board maintenance as required by regulation 36;

.2 subject to a thorough examination and operational test during the annual surveys required by regulations I/7 and I/8 by properly trained personnel familiar with the system; and

.3 operationally tested under a load of 1.1 times the total mass of the liferaft when loaded with its full complement of persons and equipment whenever the automatic release hook is overhauled. Such over-hauling and test shall be carried out at least once every five years.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
the automatic release hook is overhauled. Such over-hauling and test shall be carried out at least once every five years.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-8 -

Regulation 21 Survival craft and rescue boats

32 The chapeau of paragraph 1.2 is replaced by the following:

1.2 Passenger ships engaged on short in ternational voyages shall carry:

33 Paragraph 1.3 is deleted and the remaini ng paragraphs are renumbered accordingly.

34 In paragraph 1.4, the words after all person s have been assembled, with lifejackets donned are added at the end of the paragraph.

35 Paragraph 2.3 is replaced by the following:

2.3 A lifeboat may be accepted as a rescue boat provided that it and its launching and recovery arrangements also comply with the requirements for a rescue boat.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
2.3 A lifeboat may be accepted as a rescue boat provided that it and its launching and recovery arrangements also comply with the requirements for a rescue boat.

36 In paragraph 3.2, the words and complying with the special standards of subdivision prescribed by regulation II-1/6.5 are deleted.

Regulation 26 Additional requirements for ro-ro passenger ships

37 In paragraph 3.1, the words approved by th e Administration having regard for the recommendations approved by the Organization are replaced by the words complying with section 5.1.4 of the Code.

38 In paragraph 3.2, all the words after the wo rd appliance are replaced by the words complying with section 6.1.7 of the Code.

Regulation 31 Survival craft and rescue boats

39 Subparagraph .2 of paragraph 1.1 is replaced by the following:

.2 in addition, one or more inflatable or rigid liferafts, complying with the

---CHUNK---