electrical power supply system is directly s upplied by the emergency source of electrical

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
11 Emergency switchboard is a switchboard which in the event of failure of the main electrical power supply system is directly s upplied by the emergency source of electrical power or the transitional source of emerge ncy power and is intended to distribute electrical energy to the emergency services.

12 Emergency source of electrical power is a source of electr ical power, intended to supply the emergency switchboard in the event of a failure of the supply from the main source of electrical power.

13 Power actuating system is the hydraulic equipment provided for supplying power to turn the rudder stock, comp rising a steering gear power unit or units, together with the associated pipes and fittings, and a rudder actuator. The power actuating systems may share common mechanical components (i.e. tiller, quadrant and rudder stock) or components serving the same purpose.

14 Maximum ahead service speed is the greatest speed which the ship is designed to

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
components serving the same purpose.

14 Maximum ahead service speed is the greatest speed which the ship is designed to maintain in service at sea at the deepest seagoing draught.

15 Maximum astern speed is the speed which it is estimated the ship can attain at the designed maximum astern power at the deepest seagoing draught.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-
17 -

16 Machinery spaces are all machinery spaces of category A and all other spaces containing propelling machinery, boilers, oil fuel units, steam and internal combustion engines, generators and major electrical machinery, oil filling stations, refrigerating, stabilizing, ventilation and ai r conditioning machinery, and sim ilar spaces, and trunks to such spaces.

17 Machinery spaces of category A are those spaces and trunks to such spaces which contain:

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
such spaces.

17 Machinery spaces of category A are those spaces and trunks to such spaces which contain:

.1 internal combustion machinery used for main propulsion;

.2 internal combustion machinery us ed for purposes other than main propulsion where such machinery has in the aggregate a total power output of not less than 375 kW; or

.3 any oil-fired boiler or oil fuel unit.

18 Control stations are those spaces in which the ship's radio or main navigating equipment or the emergency source of power is located or where the fire recording or fire control equipment is centralized.

19 Chemical tanker is a cargo ship constructed or adapted and used for the carriage in bulk of any liquid product listed in either:

.1 chapter 17 of the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemical s in Bulk adopted by the Maritime Safety Committee by resolution MSC.4(48), hereinafter referred to as

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
of Ships Carrying Dangerous Chemical s in Bulk adopted by the Maritime Safety Committee by resolution MSC.4(48), hereinafter referred to as the International Bulk Chemical Code, as may be amended by the Organization; or

.2 chapter VI of the Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk adopted by the Assembly of the Organization by resolution A.212(VII), hereinafter referred to as the Bulk Chemical Code, as has been or may be amended by the Organization,

whichever is applicable.

20 Gas carrier is a cargo ship constructed or ad apted and used for the carriage in bulk of any liquefied gas or other products listed in either:

.1 chapter 19 of the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Maritime Safety Committee by resolution MSC.5(48), he reinafter referred to as the International Gas Carrier Code, as may be amended by the Organization; or

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Committee by resolution MSC.5(48), he reinafter referred to as the International Gas Carrier Code, as may be amended by the Organization; or

.2 chapter XIX of the Code for the C onstruction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Organization by resolution A.328(IX), herein after referred to as the Gas Carrier Code,

as has been or may be amended by the Organization,

whichever is applicable.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-18 -

PART B
SUBDIVISION AND STABILITY

Regulation 4
General

1 The damage stability requirements in pa rts B-1 through B-4 shall apply to cargo ships of 80 m in length (L) and upwards and to all passenge r ships regardless of length but shall exclude those cargo ships which are shown to co mply with subdivision and

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
ships of 80 m in length (L) and upwards and to all passenge r ships regardless of length but shall exclude those cargo ships which are shown to co mply with subdivision and damage stability regulations in other instruments developed by the Organization.

2 The Administration may, for a particular ship or group of ships, accept alternative methodologies if it is satisfied that at least the same degree of safety as represented by these regulations is achieved. Any Admi nistration which allows such alternative methodologies shall communicate to the Organization particulars thereof.

3 Ships shall be as efficiently subdivided as is possible having regard to the nature of the service for which they are intended. The degree of subdivision shall vary with the subdivision length (Ls) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with th e ships of greatest subdivision length (Ls),

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
subdivision length (Ls) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with th e ships of greatest subdivision length (Ls), primarily engaged in the carriage of passengers.

4 Where it is proposed to fit decks, inner skins or longitudinal bulkheads of sufficient tightness to seriously restrict the flow of water, the Administration shall be satisfied that proper consideration is given to beneficial or adve rse effects of such structures in the calculations.

PART B-1
STABILITY

Regulation 5
Intact stability information

1 Every passenger ship regardless of si ze and every cargo ship having a length (L) of 24 m and upwards, shall be inclined upon its completion and the elements of its stability determined.

2 The Administration may allow the inclining test of an individual cargo ship to be dispensed with provided basic stability data are available from the inclining test of a sister

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
2 The Administration may allow the inclining test of an individual cargo ship to be dispensed with provided basic stability data are available from the inclining test of a sister ship and it is shown to the satisfaction of the Administration that reliable stability information for the exempted ship can be obtai ned from such basic data, as required by regulation 5-1. A weight survey shall be carried out upon completion and the ship shall be inclined whenever in comparison with the data derived from the sister ship, a deviation from the lightship displacement exceeding 1% for ships of 160 m or more in length and 2% for ships of 50 m or less in length a nd as determined by linear interpolation for intermediate lengths or a deviation from th e lightship longitudinal centre of gravity exceeding 0.5% of Ls is found.

3 The Administration may also allow the inclin ing test of an individual ship or class

---CHUNK---