SOURCE: MSC.216%2882%29.pdf
exceeding 0.5% of Ls is found.

3 The Administration may also allow the inclin ing test of an individual ship or class of ships especially designed for the carriage of liquids or ore in bulk to be dispensed with when reference to existing data for similar sh ips clearly indicates th at due to the ships proportions and arrangements more than sufficient metacentric height will be available in all probable loading conditions.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-19 -

4 Where any alterations are made to a ship so as to materially affect the stability information supplied to the master, amended stability information shall be provided. If necessary the ship shall be re-inclined. The ship shall be re-inclined if anticipated deviations exceed one of the values specified in paragraph 5.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
necessary the ship shall be re-inclined. The ship shall be re-inclined if anticipated deviations exceed one of the values specified in paragraph 5.

5 At periodical intervals not exceeding five years, a lightweight survey shall be carried out on all passenger ships to verify any changes in lightship displacement and longitudinal centre of gravity. The ship shall be re-inclined whenever, in comparison with the approved stability information, a de viation from the lightship displacement exceeding 2% or a deviation of the longitu dinal centre of gravity exceeding 1% of Ls is found or anticipated.

6 Every ship shall have scales of draughts marked clearly at the bow and stern. In the case where the draught mark s are not located where they are easily readable, or operational constraints for a particular trade make it difficult to read the draught marks, then the ship shall also be fitted with a re liable draught indicatin g system by which the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
operational constraints for a particular trade make it difficult to read the draught marks, then the ship shall also be fitted with a re liable draught indicatin g system by which the bow and stern draughts can be determined.

Regulation 5-1
Stability information to be supplied to the master

1 The master shall be supplied with such information satisfactory to the Administration as is necessary to enable hi m by rapid and simple processes to obtain accurate guidance as to the st ability of the ship under vary ing conditions of service. A copy of the stability information shall be furnished to the Administration.

2 The information should include:

.1 curves or tables of minimum operational metacentric height (GM) versus draught which assures compliance with the relevant intact and damage stability requirements, alternatively co rresponding curves or tables of the maximum allowable vertical centre of gravity (KG) versus draught, or with

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
stability requirements, alternatively co rresponding curves or tables of the maximum allowable vertical centre of gravity (KG) versus draught, or with the equivalents of either of these curves;

.2 instructions concerning the operation of cross-flooding arrangements; and

.3 all other data and aids which might be necessary to maintain the required intact stability and stability after damage.

3 The stability information shall show the influence of various trims in cases where the operational trim range exceeds +/- 0.5% of Ls.

4 For ships which have to fulfil the stabil ity requirements of part B-1, information referred to in paragraph 2 are determined fr om considerations related to the subdivision index, in the following manner: Minimum required GM (or maximum permissible vertical position of centre of gravity KG) for the three draughts ds, dp and dl are equal to the GM (or KG values) of corresponding loading cases used for the calculation of survival

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
vertical position of centre of gravity KG) for the three draughts ds, dp and dl are equal to the GM (or KG values) of corresponding loading cases used for the calculation of survival factor si. For intermediate draughts, values to be used shall be obtained by linear interpolation applied to the GM value only between the deep est subdivision draught and the partial subdivision draught and between the pa rtial load line and the light service draught respectively. Int act stability criteria will also be taken in to account by retaining for each draft the maximum among minimum required GM values or the minimum of maximum permissible KG values for both criteria. If th e subdivision index is calculated for different trims, several required GM curves will be established in the same way.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-20 -

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-20 -

5 When curves or tables of mini mum operational metacentric height (GM) versus

draught are not appropriate, the master should ensure that the operating condition does not deviate from a studied loading condition, or verify by calculation that the stability criteria are satisfied for this loading condition.

Regulation 6
Required subdivision index R

1 The subdivision of a ship is considered sufficient if the attained subdivision index A, determined in accordance with regula tion 7, is not less than the required subdivision index R calculated in accordance with this regulation and if, in addition, the partial indices As, Ap and Al are not less than 0.9 R for passenger ships and 0.5 R for cargo ships.

2 For all ships to which the damage stabil ity requirements of this chapter apply, the

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
partial indices As, Ap and Al are not less than 0.9 R for passenger ships and 0.5 R for cargo ships.

2 For all ships to which the damage stabil ity requirements of this chapter apply, the
degree of subdivision to be provided shall be determined by the required subdivision index R, as follows:

.1 In the case of cargo ships greater than 100 m in length (Ls):

R = 1521281 s + L

.2 In the case of cargo ships not less than 80 m in length (Ls) and not greater than 100 m in length (Ls):

R =)]1 100 [1/(1 1 oo sRR L× +

where Ro is the value R as calculated in accordance with the formula in subparagraph .1.

.3 In the case of passenger ships:

R = 15,2252.55,0001 s + + N L

where:

N = N1 + 2N2
N1 = number of persons for wh om lifeboats are provided
N2 = number of persons (including officers and crew) the ship is permitted to carry in excess of N1.

.4 Where the conditions of service are such that compliance with

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
N2 = number of persons (including officers and crew) the ship is

permitted to carry in excess of N1.

.4 Where the conditions of service are such that compliance with paragraph 2.3 of this regulation on the basis of N = N1 + 2N2 is impracticable and where the Administration considers that a suitably reduced degree of hazard exists, a lesser value of N may be taken but in no case less than N = N1 + N2.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-21 -

Regulation 7
Attained subdivision index A

1 The attained subdivision index A is obtained by the summation of the partial indices As, Ap and Al, (weighted as shown) calculated for the draughts ds, dp and dl defined in regulation 2 in accordance with the following formula:

A = 0.4 As + 0.4Ap + 0.2Al

Each partial index is a summation of contri butions from all damage cases taken in

---CHUNK---

SOURCE: MSC.216%2882%29.pdf