with no subse uent
cleaning
Inspection in line with
schedule in P
Deviation from A
specifications e g speed
salinity temperature
A damage
uitable A
installed in area
E ceeding e pected
lifetime of A
YE
Performance loss as per
P
peration in line with
P including
proactive cleaning
if relevant
monitoring of risk
parameters and no
indication of reduced
A efficacy
Deviation from A
maintenance/service
regime
HIGH
Area has high
risk of
biofouling
N
NTINGEN Y
A TI N P AN
Details
in appendi
Downtime/malfunction
of GP or clean hull
measures
YE
N
Deviation from regular
proactive cleaning or

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
Area has high
risk of
biofouling
N
NTINGEN Y
A TI N P AN
Details
in appendi

Downtime/malfunction
of GP or clean hull
measures
YE
N
Deviation from regular
proactive cleaning or
necessary reactive
cleaning
Biofouling risk parameters
Design and construction
reinstallation of A
In operation
P

Area has low
risk of
biofouling
onitoring
biofouling risk
parameters
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 30

I:\MEPC\80\MEPC 80-17-Add.1.docx
APPENDIX 2 INSPECTION AND CLEANING REPORTS

1 Introduction

The Guidelines recommend that a report should be prepared after an inspection and/or cleaning operation. The report should record the details of the biofouling management actions undertaken on the ship. The inspection report should be prepared by the inspection provider.

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
cleaning operation. The report should record the details of the biofouling management actions undertaken on the ship. The inspection report should be prepared by the inspection provider. It may also be relevant to prepare a report after an inspection carried out by ship's crew as part of contingency actions.

The cleaning report should be prepared by either the cleaning operators or the inspection provider as part of a combined cleaning and inspection report.

Digital tools may be applied for the reporting and/or assessment of results. The conclusions from the reports should be recorded in the BFRB including reference to the detailed report/assessment.

2 Entries in the report after a biofouling inspection

The following information should be recorded in the inspection report:

Ship particulars:
- Ship name
- IMO number
Date and place of inspection
Name of inspection/cleaning company
List of all inspected hull and niche areas

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
Ship particulars:
- Ship name
- IMO number
Date and place of inspection
Name of inspection/cleaning company
List of all inspected hull and niche areas
Inspection equipment used (including list of divers/ROV operators participating in the operation)
Inspection conditions (i.e. duration, estimated visibility underwater)
Signature of authorized person of the inspection/cleaning company
Inspection start and end times
Results:
- Type of biofouling as per the rating in table 1
- Quantitative assessments of biofouling cover of area inspected (i.e. estimates of per cent cover) as per table 1
AFC condition
- The condition of the AFC should be observed during the inspection and reported. The condition is recommended to be categorized in line with table 4
MGPS condition
- The condition of the MGPS should be observed during the inspection and reported. The condition is recommended to be categorized in line with table 5
Photos/videos

---CHUNK---

SOURCE: MEPC.378%2880%29.pdf
table 4
MGPS condition
- The condition of the MGPS should be observed during the inspection and reported. The condition is recommended to be categorized in line with table 5
Photos/videos
- Photos and videos submitted or used in a digital assessment tool as evidence of hull fouling

I:\MEPC\80\MEPC 80-17-Add.1.docx
SAMPLE OF INSPECTION REPORT

Name of ship: .....

IMO number: .....

Date: .....

Location/port: .

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
a ship fitted with a d ual fuel engine, the ship directly exits the NO x Tier III emission control area(s) or proceeds directly to the nearest gas fuel bunkering facility appropriate to the ship located in the NOx Tier III emission control area(s);

.2 for a ship with a Tier II engine undergoing conversion, maintenance or repair, the period beginning at the time the ship enters the NO x Tier III emission control area(s) and proceeds directly to the shipyard or other repair facility, and ending at the time the ship is released from the shipyard or other repair