DWT
n/a 0-10*

0-20* 0-30*
LNG
carrier***
10,000 DWT
and above n/a 10** 20 30
Ro-ro cargo
ship (vehicle
carrier)***
10,000 DWT
and above n/a 5** 15 30
Ro-ro cargo
ship***
2,000 DWT
and above n/a 5** 20 30
1,000 and
above but less
than 2,000
DWT
n/a 0-5*,** 0-20* 0-30*
Ro-ro
passenger
ship***
1,000 DWT
and above n/a 5** 20 30
250 and above
but less than
1,000 DWT
n/a 0-5*,** 0-20* 0-30*
Cruise
passenger
ship***
having
non-
conventional
propulsion
85,000 GT
and above n/a 5** 20 30
25,000 and
above but less
than 85,000
GT
n/a 0-5*,** 0-20* 0-30*
* Reduction factor to be linearly interpolated between the two values dependent upon ship size. The lower value of the reduction factor is to be applied to the smaller ship size.
** Phase 1 commences for those ships on 1 September 2015.

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
upon ship size. The lower value of the reduction factor is to be applied to the

smaller ship size.
** Phase 1 commences for those ships on 1 September 2015.
*** Reduction factor applies to those ships delivered on or after 1 September 2019,
as defined in paragraph 2.1 of regulation 2.
Note: n/a means that no required EEDI applies.

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 39 -

3 The reference line values shall be calculated as follows:

Reference line value = a · bc

where a, b and c are the parameters given in table 2.

Table 2 - Parameters for the determination of reference values for the different ship types

Ship type defined in regulation 2 a b c
2.2.5 Bulk carrier 961.79 DWT of the ship
where
DWT279,000

279,000 where
DWT > 279,000
0.477

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
Ship type defined in regulation 2 a b c
2.2.5 Bulk carrier 961.79 DWT of the ship
where
DWT279,000

279,000 where
DWT > 279,000
0.477
2.2.7 Combination carrier 1,219.00 DWT of the ship 0.488
2.2.9 Containership 174.22 DWT of the ship 0.201
2.2.11 Cruise passenger ship
having non-conventional
propulsion
170.84 GT of the ship 0.214
2.2.14 Gas carrier 1,120.00 DWT of the ship 0.456
2.2.15 General cargo ship 107.48 DWT of the ship 0.216
2.2.16 LNG carrier 2,253.7 DWT of the ship 0.474
2.2.22 Refrigerated cargo carrier 227.01 DWT of the ship 0.244
2.2.26 Ro-ro cargo ship 1405.15 DWT of the ship

0.498

1686.17* DWT of the ship
where
DWT17,000*

17,000 where
DWT > 17,000*
2.2.27 Ro -ro cargo ship (vehicle
carrier)
(DWT/GT)-
0.7 · 780.36
where DWT/GT < 0.3
1,812.63
where DWT/GT 0.3
DWT of the ship

0.471
2.2.28 Ro-ro passenger ship 752.16 DWT of the ship

0.381
902.59* DWT of the ship
where
DWT10,000*

10,000 where
DWT > 10,000*

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
1,812.63
where DWT/GT 0.3
DWT of the ship

0.471
2.2.28 Ro-ro passenger ship 752.16 DWT of the ship

0.381
902.59* DWT of the ship
where
DWT10,000*

10,000 where
DWT > 10,000*
2.2.29 Tanker 1,218.80 DWT of the ship 0.488
* to be used from phase 2 and thereafter.

4 If the design of a ship allows it to fall into more than one of the ship type definitions specified in table 2, the required EEDI for the ship shall be the most stringent (the lowest) required EEDI.

5 For each ship to which this regulation applies, the installed propulsion power shall not be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines to be developed by the Organization.

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines to be developed by the Organization.

6 At the beginning of phase 1 and at the midpoint of phase 2, the Organization shall review the status of technological developments and, if proven necessary, amend the time periods, the EEDI reference line parameters for relevant ship types and reduction rates set out in this regulation.

Regulation 25
Required EEXI

1 For: