.1 each ship; and

.2 each ship which has undergone a major conversion

which falls into one of the categories in regulations 2.2.5, 2.2.7, 2.2.9, 2.2.11, 2.2.14 to 2.2.16, 2.2.22, and 2.2.26 to 2.2.29 and to which this chapter is applicable, the attained EEXI shall be as follows:

Attained EEXI Required EEXI = (1
Y
100) EEDI reference line value

where Y is the reduction factor specified in Table 3 for the required EEXI compared to the EEDI

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
as follows:

Attained EEXI Required EEXI = (1
Y
100) EEDI reference line value

where Y is the reduction factor specified in Table 3 for the required EEXI compared to the EEDI
reference line.

Table 3 - Reduction factors (in percentage) for the EEXI relative to the EEDI reference line

Ship type	Size	Reduction factor
Bulk carrier	200,000 DWT and above	15
	20,000 and above but less than 200,000 DWT	20
	10,000 and above but less than 20,000 DWT	0-20*
Gas carrier	15,000 DWT and above	30
	10,000 and above but less than 15,000 DWT	20
	2,000 and above but less than 10,000 DWT	0-20*
Tanker	200,000 DWT and above	15
	20,000 and above but less than 200,000 DWT	20
	4,000 and above but less than 20,000 DWT	0-20*

Containership 200,000 DWT and above 50
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS,

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
Containership 200,000 DWT and above 50
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS,
1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 41 -

Ship type Size Reduction factor
120,000 and above but
less than 200,000 DWT 45
80,000 and above but less
than 120,000 DWT 35
40,000 and above but less
than 80,000 DWT 30
15,000 and above but less
than 40,000 DWT 20
10,000 and above but less
than 15,000 DWT 0-20*
General cargo ship
15,000 DWT and
above 30
3,000 and above but less
than 15,000 DWT 0-30*
Refrigerated cargo carrier
5,000 DWT and
above 15
3,000 and above but less
than 5,000 DWT 0-15*
Combination carrier
20,000 DWT and
above 20
4,000 and above but less
than 20,000 DWT 0-20*
LNG carrier 10,000 DWT and above 30
Ro-ro cargo ship (vehicle
carrier)
10,000 DWT and
above 15
Ro-ro cargo ship
2,000 DWT and
above 5

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf

4,000 and above but less
than 20,000 DWT 0-20*
LNG carrier 10,000 DWT and above 30
Ro-ro cargo ship (vehicle
carrier)
10,000 DWT and
above 15
Ro-ro cargo ship
2,000 DWT and
above 5
1,000 and above but less
than 2,000 DWT 0-5*
Ro-ro passenger ship
1,000 DWT and
above 5
250 and above but less
than 1,000 DWT 0-5*
Cruise passenger ship
having non-conventional
propulsion
85,000 GT
and above 30
25,000 and above but less
than 85,000 GT 0-30*

* Reduction factor to be linearly interpolated between the two values dependent upon ship size.

The lower value of the reduction factor is to be applied to the smaller ship size.

2 The EEDI reference line values shall be calculated in accordance with regulations 24.3 and 24.4 of this Annex. For ro-ro cargo ships and ro-ro passenger ships, the reference line value to be used from phase 2 and thereafter under regulation 24.3 of this Annex shall be referred to.

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
reference line value to be used from phase 2 and thereafter under regulation 24.3 of this Annex shall be referred to.

3 A review shall be completed by 1 January 2026 by the Organization to assess the effectiveness of this regulation taking into account any guidelines developed by the Organization. If, based on the review, the Parties decide to adopt amendments to this

regulation, such amendments shall be adopted and brought into force in accordance with the provisions of article 16 of the present Convention.

Regulation 26
Ship Energy Efficiency Management Plan (SEEMP)

1 Each ship shall keep on board a ship specific Ship Energy Efficiency Management Plan (SEEMP). This may form part of the ship 's Safety Management System (SMS).

---CHUNK---

SOURCE: MEPC.328%2876%29.pdf
1 Each ship shall keep on board a ship specific Ship Energy Efficiency Management Plan (SEEMP). This may form part of the ship 's Safety Management System (SMS). The SEEMP shall be developed and reviewed, taking into account the guidelines adopted by the Organization.

2 In the case of a ship of 5,000 gross tonnage and above, the SEEMP shall include a description of the methodology that will be used to collect the data required by regulation 27.1 of this Annex and the processes that will be used to report the data to the ship's Administration.

3 In the case of a ship of 5,000 gross tonnage and above, which falls into one or more of the categories in regulations 2.2.5, 2.2.7, 2.2.9, 2.2.11, 2.2.14 to 2.2.16, 2.2.22, and 2.2.26 to 2.2.29 of this Annex:

.1 On or before 1 January 2023 the SEEMP shall include:

.1 a description of the methodology that will be used to calculate the