---CHUNK---

SOURCE: MEPC.403(83).pdf
.4 for ships on international voyages, be written in the working language of the master and officers and, if the working language of the master and officers is not English, French or Spanish, include a translation into one of these languages.

7 This regulation shall also apply to gas carriers only if the types of loading and containment systems allow safe retention of non-methane VOCs on board or their safe return ashore.37

Regulation 16
Shipboard incineration

1 Except as provided in paragraph 4 of this regulation, shipboard incineration shall be allowed only in a shipboard incinerator.

2 Shipboard incineration of the following substances shall be prohibited:

.1 residues of cargoes subject to Annex I, II or III or related contaminated packing materials;

.2 polychlorinated biphenyls (PCBs);

35 Refer to Standards for vapour emission control systems (MSC/Circ.585).

36 Refer to the Guidelines for the development of a VOC management plan (resolution MEPC.185(59)). Refer also to Technical information on systems and operation to assist development of VOC management plans

---CHUNK---

SOURCE: MEPC.403(83).pdf
36 Refer to the Guidelines for the development of a VOC management plan (resolution MEPC.185(59)). Refer also to Technical information on systems and operation to assist development of VOC management plans (MEPC.1/Circ.680), and Technical information on a vapour pressure control system in order to facilitate the development and the update of VOC management plans (MEPC.1/Circ.719).

37 Refer to the International Code for the construction and equipment of ships carrying liquefied gases in bulk (IGC Code) (resolution MSC.5(48), as amended).

.3 garbage, as defined by Annex V, containing more than traces of heavy metals;

.4 refined petroleum products containing halogen compounds;

.5 sewage sludge and sludge oil neither of which is generated on board the

ship; and

.6 exhaust gas cleaning system residues.

3 Shipboard incineration of polyvinyl chlorides (PVCs) shall be prohibited, except in

---CHUNK---

SOURCE: MEPC.403(83).pdf
.5 sewage sludge and sludge oil neither of which is generated on board the ship; and

.6 exhaust gas cleaning system residues.

3 Shipboard incineration of polyvinyl chlorides (PVCs) shall be prohibited, except in shipboard incinerators for which IMO Type Approval Certificates38 have been issued.

4 Shipboard incineration of sewage sludge and sludge oil generated during normal operation of a ship may also take place in the main or auxiliary power plant or boilers, but in those cases, shall not take place inside ports, harbours or estuaries.

5 Nothing in this regulation either:

.1 affects the incineration at sea prohibitions of the Convention on the Prevention of Marine Pollution by Dumping of Wastes and Other Matter, 1972, as amended, and the 1996 Protocol thereto, or other requirements thereof,
or

.2 precludes the development, installation and operation of alternative design shipboard thermal waste treatment devices that meet or exceed the requirements of this regulation.

6.1 Except as provided in paragraph 6.2 of this regulation, each incinerator on a ship

---CHUNK---

SOURCE: MEPC.403(83).pdf
shipboard thermal waste treatment devices that meet or exceed the requirements of this regulation.

6.1 Except as provided in paragraph 6.2 of this regulation, each incinerator on a ship constructed on or after 1 January 2000 or incinerator that is installed on board a ship on or after 1 January 2000 shall meet the requirements contained in appendix IV. Eac h incinerator subject to this paragraph shall be approved by the Administration taking into account the standard specification for shipboard incinerators developed by the Organization;39

6.2 The Administration may allow exclusion from the application of paragraph 6.1 of this regulation to any incinerator installed on board a ship before 19 May 2005, provided that the ship is solely engaged in voyages within waters subject to the sovereignty or jurisdiction of the State the flag of which the ship is entitled to fly.

7 Incinerators installed in accordance with the requirements of paragraph 6.1 of this regulation shall be provided with a manufacturer's operating manual, which is to be retained

with the unit and which shall specify how to operate the incinerator within the limits described

---CHUNK---

SOURCE: MEPC.403(83).pdf
regulation shall be provided with a manufacturer's operating manual, which is to be retained
with the unit and which shall specify how to operate the incinerator within the limits described
in paragraph 2 of appendix IV of this Annex.

38 Type Approval Certificates issued taking into account the Revised guidelines for the implementation of Annex V of MARPOL (resolution MEPC.59(33), as amended by resolution MEPC.92(45)), or Standard specification for shipboard incinerators (resolution MEPC.76(40), as amended by resolution MEPC.93(45)), or the 2014 Standard specification for shipboard incinerators (resolution MEPC.244(66)), as amended by resolution MEPC.368(79).

39 Refer to the 2014 Standard specification for shipboard incinerators (resolution MEPC.244(66), as amended by resolution MEPC.368(79)), or Standard specification for shipboard incinerators (resolution MEPC.76(40), as amended by resolution MEPC.93(45)), and Type approval of shipboard incinerators (MEPC.1/Circ.793).
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1

---CHUNK---

SOURCE: MEPC.403(83).pdf
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1
Annex 11, page 34

I:\MEPC\MEPC 83-17-Add.1.docx
8 Personnel responsible for the operation of an incinerator installed in accordance with the requirements of paragraph 6.1 of this regulation shall be trained to implement the guidance provided in the manufacturer's operating manual as required by paragraph 7 of this regulation.

9 For incinerators installed in accordance with the requirements of paragraph 6.1 of this regulation the combustion chamber gas outlet temperature shall be monitored at all times the unit is in operation. Where that incinerator is of the continuous -feed type, waste shall not be fed into the unit when the combustion chamber gas outlet temperature is below 850°C. Where that incinerator is of the batch-loaded type, the unit shall be designed so that the combustion chamber gas outlet temperature shall reach 600 °C within five minutes after start -up and will thereafter stabilize at a temperature not less than 850°C.

Regulation 17
Reception facilities

---CHUNK---

SOURCE: MEPC.403(83).pdf
chamber gas outlet temperature shall reach 600 °C within five minutes after start -up and will
thereafter stabilize at a temperature not less than 850°C.

Regulation 17
Reception facilities

1 Each Party undertakes to ensure the provision of facilities adequate to meet the:

.1 needs of ships using its repair ports for the reception of ozone -depleting substances and equipment containing such substances when removed from ships;

.2 needs of ships using its ports, terminals or repair ports for the reception of exhaust gas cleaning residues from an exhaust gas cleaning system;

without causing undue delay to ships, and

.3 needs in ship -breaking facilities for the reception of ozone -depleting substances and equipment containing such substances when removed from ships.

2 The following States may satisfy the requirements in paragraph 1 of this regulation through regional arrangements when, because of those States ' unique circumstances, such arrangements are the only practical means to satisfy these requirements:

.1 small island developing States; and