3 The reference line values shall be calculated as follows:

Reference line value = a · bc

where a, b and c are the parameters given in table 2.

Table 2 - Parameters for the determination of reference values for the different ship types

Ship type defined in regulation 2	a	b	c
2.2.5 Bulk carrier	961.79	DWT of the ship where DWT279,000	
		279,000 where DWT > 279,000	0.477
2.2.6 Combination carrier	1,219.00	DWT of the ship	0.488
2.2.7 Containership	174.22	DWT of the ship	0.201
2.2.9 Cruise passenger ship having non-conventional propulsion	170.84	GT of the ship	0.214
2.2.12 Gas carrier	1,120.00	DWT of the ship	0.456
2.2.13 General cargo ship	107.48	DWT of the ship	0.216
2.2.14 LNG carrier	2,253.7	DWT of the ship	0.474
2.2.20 Refrigerated cargo carrier	227.01	DWT of the ship	0.244
2.2.24 Ro-ro cargo ship	1405.15	DWT of the ship	
			0.498
	1686.17*	DWT of the ship where DWT17,000*	
		17,000 where DWT > 17,000*	
2.2.25 Ro-ro cargo ship (vehicle carrier)	(DWT/GT)-0.7 ·		
	780.36	where DWT/GT < 0.3	
	1,812.63	where DWT/GT 0.3 DWT of the ship	
			0.471

---CHUNK---

SOURCE: MEPC.403(83).pdf

0.498
1686.17* DWT of the ship
where
DWT17,000*

17,000 where DWT
> 17,000*
2.2.25 Ro-ro cargo ship (vehicle
carrier)
(DWT/GT)-0.7 ·
780.36
where DWT/GT < 0.3
1,812.63
where DWT/GT 0.3
DWT of the ship

0.471
2.2.26 Ro-ro passenger ship 752.16 DWT of the ship

0.381
902.59* DWT of the ship
where
DWT10,000*

10,000 where DWT
> 10,000*
2.2.27 Tanker 1,218.80 DWT of the ship 0.488
 * to be used from phase 2 and thereafter.

4 If the design of a ship allows it to fall into more than one of the ship type definitions specified in table 2, the required EEDI for the ship shall be the most stringent (the lowest) required EEDI.

5 For each ship to which this regulation applies, the installed propulsion power shall not be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines developed by the Organization.52

---CHUNK---

SOURCE: MEPC.403(83).pdf
be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines developed by the Organization.52

6 At the beginning of phase 1 and at the midpoint of phase 2, the Organization shall review the status of technological developments and, if proven necessary, amend the time periods, the EEDI reference line parameters for relevant ship types and reduction rates set out

in this regulation.

Regulation 25
Required EEXI

1 For:

.1 each ship; and

.2 each ship which has undergone a major conversion

which falls into one of the categories in regulations 2.2.5 to 2.2.7, 2.2.9, 2.2.1 2 to 2.2.14, 2.2.20, and 2.2.24 to 2.2.27 and to which this chapter is applicable, the attained EEXI shall be as follows:

Attained EEXI Required EEXI = (1
Y
100) EEDI reference line value

where Y is the reduction factor specified in Table 3 for the required EEXI compared to the EEDI reference line.

Table 3 - Reduction factors (in percentage) for the EEXI relative to the EEDI reference line

Ship type Size Reduction factor
Bulk carrier
200,000 DWT and
above 15
20,000 and above but less

---CHUNK---

SOURCE: MEPC.403(83).pdf
to the EEDI reference line.

Table 3 - Reduction factors (in percentage) for the EEXI relative to the EEDI reference line

Ship type Size Reduction factor
Bulk carrier
200,000 DWT and
above 15
20,000 and above but less
than 200,000 DWT 20
10,000 and above but less
than 20,000 DWT 0-20*
Gas carrier
15,000 DWT and
above 30
10,000 and above but less
than 15,000 DWT 20
2,000 and above but less
than 10,000 DWT 0-20*

Tanker
200,000 DWT and
above 15
20,000 and above but less
than 200,000 DWT 20
4,000 and above but less
than 20,000 DWT
0-20*

52 Refer to the Guidelines for determining minimum propulsion power to maintain the manoeuvrability of ships in adverse conditions (MEPC.1/Circ.850/Rev.3).

Ship type Size Reduction factor
Containership
200,000 DWT
and above 50