120,000 and above but
less than 200,000 DWT 45
80,000 and above but less
than 120,000 DWT 35
40,000 and above but less
than 80,000 DWT 30

---CHUNK---

SOURCE: MEPC.403(83).pdf
Ship type Size Reduction factor
Containership
200,000 DWT
and above 50
120,000 and above but
less than 200,000 DWT 45
80,000 and above but less
than 120,000 DWT 35
40,000 and above but less
than 80,000 DWT 30
15,000 and above but less
than 40,000 DWT 20
10,000 and above but less
than 15,000 DWT 0-20*
General cargo ship
15,000 DWT and
above 30
3,000 and above but less
than 15,000 DWT 0-30*
Refrigerated cargo carrier
5,000 DWT and
above 15
3,000 and above but less
than 5,000 DWT 0-15*
Combination carrier
20,000 DWT and
above 20
4,000 and above but less
than 20,000 DWT 0-20*
LNG carrier 10,000 DWT and above 30
Ro-ro cargo ship (vehicle
carrier)
10,000 DWT and
above 15
Ro-ro cargo ship
2,000 DWT and
above 5
1,000 and above but less
than 2,000 DWT 0-5*
Ro-ro passenger ship
1,000 DWT and
above 5
250 and above but less
than 1,000 DWT 0-5*

Cruise passenger ship
having non-conventional
propulsion
85,000 GT
and above 30
25,000 and above but less
than 85,000 GT 0-30*

* Reduction factor to be linearly interpolated between the two values dependent upon ship

---CHUNK---

SOURCE: MEPC.403(83).pdf
than 1,000 DWT 0-5*
Cruise passenger ship
having non-conventional
propulsion
85,000 GT
and above 30
25,000 and above but less
than 85,000 GT 0-30*

* Reduction factor to be linearly interpolated between the two values dependent upon ship
size. The lower value of the reduction factor is to be applied to the smaller ship size.

2 The EEDI reference line values shall be calculated in accordance with regulations 24.3 and 24.4 of this Annex. For ro-ro cargo ships and ro-ro passenger ships, the reference line value to be used from phase 2 and thereafter under regulation 24.3 of this Annex shall be referred to.

3 This regulation shall be kept under review in light of its implementation, taking into account the IMO Strategy on Reduction of GHG Emissions from Ships.

1 Each ship shall keep on board a ship -specific Ship Energy Efficiency Management

---CHUNK---

SOURCE: MEPC.403(83).pdf
Annex 11, page 47

I:\MEPC\MEPC 83-17-Add.1.docx
Regulation 26
Ship Energy Efficiency Management Plan (SEEMP)

1 Each ship shall keep on board a ship -specific Ship Energy Efficiency Management Plan (SEEMP). This may form part of the ship's Safety Management System (SMS). The SEEMP shall be developed and reviewed, taking into account the guidelines adopted by the Organization.53

2 In the case of a ship of 5,000 gross tonnage and above, the SEEMP shall include a description of the methodology that will be used to collect the data required by regulation 27.1 of this Annex and the processes that will be used to report the data to the ship's Administration.

3 In the case of a ship of 5,000 gross tonnage and above, which falls into one or more of the categories in regulations 2.2.5 to 2.2.7, 2.2.9, 2.2.1 2 to 2.2.1 4, 2.2.2 0, and 2.2.2 4 to 2.2.27 of this Annex:

.1 On or before 1 January 2023 the SEEMP shall include:

.1 a description of the methodology that will be used to calculate the ship's attained annual operational CII required by regulation 28 of this Annex and the processes that will be used to report this value to the ship's Administration;

---CHUNK---

SOURCE: MEPC.403(83).pdf
.1 a description of the methodology that will be used to calculate the ship's attained annual operational CII required by regulation 28 of this Annex and the processes that will be used to report this value to the ship's Administration;

.2 the required annual operational CII, as specified in regulation 28 of this Annex, for the next three years;

.3 an implementation plan documenting how the required annual operational CII will be achieved during the next three years; and

.4 a procedure for self-evaluation and improvement.

.2 For a ship rated as D for three consecutive years or rated as E in accordance with regulation 28 of this Annex, the SEEMP shall be reviewed in accordance with regulation 28.8 of this Annex to include a plan of corrective actions to achieve the required annual operational CII.

4 In the case of a ship to which chapter 5 applies:

.1 On or before 1 January 2028, the SEEMP shall include:

.1 a description of the methodology that will be used to collect the data required by regulation 33 of this Annex to calculate the ship 's attained annual GFI, target annual GFI and GFI compliance balance; and

---CHUNK---

SOURCE: MEPC.403(83).pdf

.1 a description of the methodology that will be used to collect the data required by regulation 33 of this Annex to calculate the ship 's attained annual GFI, target annual GFI and GFI compliance balance; and

.2 the processes that will be used to report the data required by regulations 33 and 37 of this Annex to the ship's Administration.

53 Refer to the 2024 Guidelines for the development of a Ship Energy Efficiency Management Plan (SEEMP) (resolution MEPC.395(82), as amended by resolution MEPC.401(83)).

5 For ships to which paragraphs 3 and 4 of this regulation apply, the SEEMP shall be subject to verification and company audits taking into account guidelines developed by the Organization.54

Regulation 27
Collection and reporting of ship fuel oil consumption data