Applicable regulation of MARPOL Annex VI
(NTC = NOx Technical Code 2008)
(AM = approved method)
Engine
#1
Engine
#2
Engine
#3
Engine
#4
Engine
#5
1 Manufacturer and model
2 Serial number
3 Use (applicable application cycle(s)
NTC 3.2)

4 Rated power (kW) (NTC 1.3.11)
5 Rated speed (rpm) (NTC 1.3.12)
6 Identical engine installed 1/1/2000
exempted by 13.1.1.2

7 Identical engine installation date
(dd/mm/yyyy) as per 13.1.1.2

8a
Major conversion
(dd/mm/yyyy)
13.2.1.1 & 13.2.2
8b 13.2.1.2 & 13.2.3
8c 13.2.1.3 & 13.2.3
9a

Tier I
13.3
9b 13.2.2
9c 13.2.3.1
9d 13.2.3.2
9e 13.7.1.2
9f Tier I NTC 8 (Multiple Engine
Operational Profiles)

10a

Tier II
13.4
10b 13.2.2
10c 13.2.2 (Tier III not
possible)

10d 13.2.3.2
10e 13.5.2 (Exemptions)
10f 13.7.1.2
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)

---CHUNK---

SOURCE: MEPC.403(83).pdf
10d 13.2.3.2
10e 13.5.2 (Exemptions)
10f 13.7.1.2
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)
-
-
-
-
-MEPC 83/17/Add.1
Annex 11, page 71

I:\MEPC\MEPC 83-17-Add.1.docx
Applicable regulation of MARPOL Annex VI
(NTC = NOx Technical Code 2008)
(AM = approved method)
Engine
#1
Engine
#2
Engine
#3
Engine
#4
Engine
#5
10g Tier II NTC 8 (Multiple Engine
Operational Profiles)

11a
NOx Tier III
Emission Control
Areas
13.5.1.1
11b 13.2.2
11c 13.2.3.2
11d 13.7.1.2
11e Tier III NTC 8 (Multiple Engine
Operational Profiles)

12

AM6
installed
13 not commercially available
at this survey

14 not applicable

2.3 Sulphur oxides (SOx) and particulate matter (regulation 14)

2.3.1 When the ship operates outside of an emission control area specified in regulation 14.3, the ship uses:

.1 fuel oil with a sulphur content as documented by bunker delivery notes that does not exceed the limit value of 0.50% m/m, and/or

---CHUNK---

SOURCE: MEPC.403(83).pdf
2.3.1 When the ship operates outside of an emission control area specified in regulation 14.3, the ship uses:

.1 fuel oil with a sulphur content as documented by bunker delivery notes that does not exceed the limit value of 0.50% m/m, and/or
.....

.2 an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6 that is at least as effective in terms of SOx emission reductions as compared to using a fuel oil with a sulphur content limit value of 0.50% m/m .....

2.3.2 When the ship operates inside an emission control area specified in regulation 14.3, the ship uses:

.1 fuel oil with a sulphur content as documented by bunker delivery notes that does not exceed the limit value of 0.10% m/m, and/or
.

.2 an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6 that is at least as effective in terms of SOx emission reductions as compared to using a fuel oil with a sulphur content limit value of 0.10% m/m ...

---CHUNK---

SOURCE: MEPC.403(83).pdf
listed in paragraph 2.6 that is at least as effective in terms of SOx emission reductions as compared to using a fuel oil with a sulphur content limit value of 0.10% m/m ...

2.3.3 For a ship without an equivalent arrangement approved in accordance with regulation 4.1 as listed in paragraph 2.6, the sulphur content of fuel oil carried for use on board the ship shall not exceed 0.50% m/m as documented by bunker delivery notes ....

2.3.4 The ship is fitted with designated sampling point(s) in accordance with regulation 14.10 or 14.11.....

6 Refer to the 2014 Guidelines on the approved method process (resolution MEPC.243(66)).
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)
-
-
-
-
-MEPC 83/17/Add.1
Annex 11, page 72

I:\MEPC\MEPC 83-17-Add.1.docx
2.3.5 In accordance with regulation 14.12, the requirement for fitting or designating

---CHUNK---

SOURCE: MEPC.403(83).pdf
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)
-