-
-
-
-MEPC 83/17/Add.1
Annex 11, page 72

I:\MEPC\MEPC 83-17-Add.1.docx
2.3.5 In accordance with regulation 14.12, the requirement for fitting or designating sampling point(s) in accordance with regulation 14.10 or 14.11 is not applicable for a fuel oil service system used for a low-flashpoint fuel or a gas fuel.....

2.4 Volatile organic compounds (VOCs) (regulation 15)

2.4.1 The tanker has a vapour collection system installed and approved in accordance with MSC/Circ.585.....

2.4.2.1 For a tanker carrying crude oil, there is an approved VOC management plan .....
2.4.2.2 VOC management plan approval reference .....

2.5 Shipboard incineration (regulation 16)

The ship has an incinerator:

.1 installed on or after 1 January 2000 that complies with:

.1 resolution MEPC.76(40), as amended7 .....

.2 resolution MEPC.244(66) as amended8

---CHUNK---

SOURCE: MEPC.403(83).pdf
The ship has an incinerator:

.1 installed on or after 1 January 2000 that complies with:

.1 resolution MEPC.76(40), as amended7 .....

.2 resolution MEPC.244(66) as amended8
.....

.2 installed before 1 January 2000 that complies with:

.1 resolution MEPC.59(33), as amended9
.....

.2 resolution MEPC.76(40), as amended7
.....

2.6 Equivalents (regulation 4)

The ship has been allowed to use the following fitting, material, appliance or apparatus to be

fitted in a ship or other procedures, alternative fuel oils, or compliance methods used as an alternative to that required by this Annex:

System or equipment Equivalent used Approval reference

THIS IS TO CERTIFY that this Record is correct in all respects.

Issued at . . . .
(place of issue of the Record)

Date (dd/mm/yyyy) . . . .

---CHUNK---

SOURCE: MEPC.403(83).pdf
(place of issue of the Record)

Date (dd/mm/yyyy) . . . .
(date of issue) (signature of duly authorized
official issuing the Record)

(seal or stamp of the authority, as appropriate)

7 As amended by resolution MEPC.93(45).

8 As amended by resolution MEPC.368(79).

9 As amended by resolution MEPC.92(45).

Appendix II

Test cycles and weighting factors (regulation 13)

The following test cycles and weighting factors shall be applied for verification of compliance of marine diesel engines with the applicable NO x limit in accordance with regulation 13 of MARPOL Annex VI using the test procedure and calculation method as specified in the NOx Technical Code.

.1 For a fixed pitch propeller propulsion engine or a propeller -law operated non-propulsion engine, test cycle E3 shall be applied in accordance with table 1;

---CHUNK---

SOURCE: MEPC.403(83).pdf
NOx Technical Code.

.1 For a fixed pitch propeller propulsion engine or a propeller -law operated non-propulsion engine, test cycle E3 shall be applied in accordance with table 1;

.2 For a propulsion engine that does not operate with a fixed pitch propeller, including an engine fitted as part of a diesel-electric installation or an engine operated with a controllable-pitch propeller, test cycle E2 shall be applied in accordance with table 2;

.3 For a non-propulsion engine that is a constant -speed engine, test cycle D2 shall be applied in accordance with table 3;

.4 For a non-propulsion engine that operates as a variable -speed engine, not included above, test cycle C1 shall be applied in accordance with table 4.

Table 1 Test cycle for a marine diesel engine as given by .1 above

Test cycle
E3
Speed 100% 91% 80% 63%
Power 100% 75% 50% 25%
Weighting factor 0.2 0.5 0.15 0.15

Table 2 Test cycle for a marine diesel engine as given by .2 above

Test cycle
E2
Speed 100% 100% 100% 100%
Power 100% 75% 50% 25%
Weighting factor 0.2 0.5 0.15 0.15

Table 3 Test cycle for a marine diesel engine as given by .3 above

Test cycle
D2

---CHUNK---

SOURCE: MEPC.403(83).pdf
Test cycle
E2
Speed 100% 100% 100% 100%
Power 100% 75% 50% 25%
Weighting factor 0.2 0.5 0.15 0.15

Table 3 Test cycle for a marine diesel engine as given by .3 above

Test cycle
D2
Speed 100% 100% 100% 100% 100%
Power 100% 75% 50% 25% 10%
Weighting factor 0.05 0.25 0.3 0.3 0.1

Table 4 Test cycle for a marine diesel engine as given by .4 above

Test
cycle
C1
Speed Rated Intermediate Idle
Torque 100% 75% 50% 10% 100% 75% 50% 0%
Weighting
factor
0.15 0.15 0.15 0.1 0.1 0.1 0.1 0.15

In the case of marine diesel engine to be certified in accordance with paragraph 5.1.1 of regulation 13, the specific emission at each individual mode point shall not exceed the applicable NOx emission limit value by more than 50% except as follows:

.1 The 10% mode point in the D2 test cycle.

.2 The 10% mode point in the C1 test cycle.

.3 The idle mode point in the C1 test cycle.