facility, and under the responsibility of the Administration, using the following standard fuel/waste specification for the type approval te st for determining whether the incinerator operates within the limits specified in paragraph 2 of this appendix:

Sludge oil consisting of: 75% sludge oil from heavy fuel oil (HFO);
5% waste lubricating oil; and
20% `emulsified water.

Solid waste consisting of: 50% food waste;
50% rubbish containing:
approx. 30% paper,
" 40% cardboard,
" 10% rags,
" 20% plastic.

The mixture will have up to 50% moisture and
7% incombustible solids.

2 Incinerators described in regulation 16.6.1 shall operate within the following limits:

O2 in combustion chamber:

6 -12%
CO in flue gas maximum average:

200 mg/MJ
Soot number maximum average: Bacharach 3 or Ringelmann 1
(20% opacity) (a higher soot number is

---CHUNK---

SOURCE: MEPC.403(83).pdf
O2 in combustion chamber:

6 -12%
CO in flue gas maximum average:

200 mg/MJ
Soot number maximum average: Bacharach 3 or Ringelmann 1
(20% opacity) (a higher soot number is
acceptable only during very short periods
such as starting up)

Unburned components in ash residues:

Maximum 10% by weight
Combustion chamber flue gas outlet
temperature range:
850 - 1,200°C

RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1

Appendix V

Information to be included in the bunker delivery note (regulation 18.5)

1 Name and IMO number of receiving ship

2 Port

3 Date of commencement of delivery

4 Name, address and telephone number of marine fuel oil supplier

5 Product name(s)

6 Quantity in metric tonnes

7 Density at 15°C (kg/m3)1

8 Sulphur content (% m/m)2

9 The flashpoint (°C) specified in accordance with standards acceptable to the Organization3, or a statement that the flashpoint has been measured at or above 70°C;

---CHUNK---

SOURCE: MEPC.403(83).pdf
7 Density at 15°C (kg/m3)1

8 Sulphur content (% m/m)2

9 The flashpoint (°C) specified in accordance with standards acceptable to the Organization3, or a statement that the flashpoint has been measured at or above 70°C;

10 A declaration signed and certified by the fuel oil supplier's representative that the fuel oil supplied is in conformity with regulation 18.3 of MARPOL Annex VI and that the sulphur content of the fuel oil supplied does not exceed:

the limit value given by regulation 14.1 of MARPOL Annex VI;

the limit value given by regulation 14.4 of MARPOL Annex VI; or

the purchaser's specified limit value of _____ (% m/m), as completed by the fuel oil supplier's representative and on the basis of the purchaser's notification that the fuel oil:

.1 is intended to be used in combination with an equivalent means of compliance in accordance with regulation 4 of MARPOL Annex VI;

or

.2 is subject to a relevant exemption for a ship to conduct trials for
sulphur oxides emission reduction and control technology research
in accordance with regulation 3.2 of MARPOL Annex VI.

---CHUNK---

SOURCE: MEPC.403(83).pdf
or

.2 is subject to a relevant exemption for a ship to conduct trials for
sulphur oxides emission reduction and control technology research
in accordance with regulation 3.2 of MARPOL Annex VI.

The declaration shall be completed by the fuel oil supplier's representative by marking
the applicable box(es) with a cross (x).

1 Fuel oil shall be tested in accordance with ISO 3675:1998 or ISO 12185:1996.

2 Fuel oil shall be tested in accordance with ISO 8754:2003.

3 ISO 2719:2016, Determination of flash point Pensky-Martens closed cup method, Procedure A
(for Distillate Fuels) or Procedure B (for Residual Fuels).

Appendix VI

Verification procedures for a MARPOL Annex VI fuel oil sample
(regulation 18.8.2 or regulation 14.8)

The following relevant verification procedure shall be used to determine whether the fuel oil
delivered to, in use or carried for use on board a ship has met the applicable sulphur limit of

---CHUNK---

SOURCE: MEPC.403(83).pdf
(regulation 18.8.2 or regulation 14.8)

The following relevant verification procedure shall be used to determine whether the fuel oil
delivered to, in use or carried for use on board a ship has met the applicable sulphur limit of
regulation 14 of MARPOL Annex VI.

This appendix refers to the following representative MARPOL Annex VI fuel oil samples:

Part 1 sample of fuel oil delivered 1 in accordance with regulation 18.8.1, hereafter
referred to as the "MARPOL delivered sample" as defined in regulation 2.1.22.

Part 2 sample of fuel oil in use,2 intended to be used or carried for use on board in accordance with regulation 14.8, hereafter referred to as the "in -use sample" as defined in regulation 2.1.16 and "onboard sample"3 as defined in regulation 2.1.24.

Part 1 MARPOL delivered sample

1 General requirements

1.1 The representative sample of the fuel oil, which is required by regulation 18.8.1 (the MARPOL delivered sample), shall be used to verify the sulphur content of the fuel oil delivered to a ship.

1.2 A Party, through its competent authority, shall manage the verification procedure.

---CHUNK---

SOURCE: MEPC.403(83).pdf
MARPOL delivered sample), shall be used to verify the sulphur content of the fuel oil delivered to a ship.

1.2 A Party, through its competent authority, shall manage the verification procedure.

1.3 A laboratory undertaking the sulphur testing procedure given in this appendix shall