have valid accreditation4 in respect of the test method to be used.

2 Verification procedure Part 1

2.1 The MARPOL delivered sample shall be conveyed by the competent authority to the laboratory.

2.2 The laboratory shall:

.1 record the details of the seal number and the sample label on the test record;

.2 record the condition of the seal of the sample as received on the test record; and

.3 reject any sample where the seal has been broken prior to receipt and record that rejection on the test record.

1 Samples taken in accordance with the Guidelines for the sampling of fuel oil for determination of compliance with MARPOL Annex VI and SOLAS chapter II-2 (circular MSC-MEPC.2/Circ.18).

2 Samples taken in accordance with the 2019 Guidelines for on board sampling for the verification of the

---CHUNK---

SOURCE: MEPC.403(83).pdf
with MARPOL Annex VI and SOLAS chapter II-2 (circular MSC-MEPC.2/Circ.18).

2 Samples taken in accordance with the 2019 Guidelines for on board sampling for the verification of the
sulphur content of the fuel oil used on board ships (MEPC.1/Circ.864/Rev.1).

3 Refer to the 2020 Guidelines for on board sampling of fuel oil intended to be used or carried for use on board a ship (MEPC.1/Circ.889).

4 The laboratory is to be accredited to ISO/IEC 17025:2017 or an equivalent standard for the performance of the given sulphur content test ISO 8754:2003.

2.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

.1 unseal the sample;

.2 ensure that the sample is thoroughly homogenized;

.3 draw two subsamples from the sample; and

.4 reseal the sample and record the new reseal details on the test record.

---CHUNK---

SOURCE: MEPC.403(83).pdf
.1 unseal the sample;

.2 ensure that the sample is thoroughly homogenized;

.3 draw two subsamples from the sample; and

.4 reseal the sample and record the new reseal details on the test record.

2.4 The two subsamples shall be tested in succession, in accordance with the specified test method referred to in regulation 2.1.30. For the purposes of this Part 1 verification procedure, the results of the test analysis shall be referred to as '1A' and '1B':

.1 results 1A and 1B shall be recorded on the test record in accordance with the requirements of the test method; and

.2 if the results of 1A and 1B are within the repeatability (r)5 of the test method, the results shall be considered valid; or

.3 if the results 1A and 1B are not within the repeatability (r) of the test method, both results shall be rejected and two new subsamples shall be taken by the laboratory and tested. The sample bottle shall be resealed in accordance with paragraph 2.3.4 after the new subsamples have been taken;

.4 in the case of two failures to achieve repeatability between 1A and 1B, the cause of that failure shall be investigated by the laboratory and resolved

---CHUNK---

SOURCE: MEPC.403(83).pdf
accordance with paragraph 2.3.4 after the new subsamples have been taken;

.4 in the case of two failures to achieve repeatability between 1A and 1B, the cause of that failure shall be investigated by the laboratory and resolved before further testing of the sample is undertaken. On resolution of that repeatability issue, two new subsamples shall be taken in accordance with paragraph 2.3. The sample shall be resealed in accordance with paragraph 2.3.4 after the new subsamples have been taken.

2.5 If the test results of 1A and 1B are valid, an average of these two results shall be calculated. The average value shall be referred to as 'X' and shall be recorded on the test record:

.1 if the result X is equal to or less than the applicable limit required by regulation 14, the fuel oil shall be considered to have met the requirement; or

.2 if the result X is greater than the applicable limit required by regulation 14, the fuel oil shall be considered to have not met the requirement.

5 Repeatability (r) calculation taking into account ISO 4259-2:2017-2 and as defined in the test method used.
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)

---CHUNK---

SOURCE: MEPC.403(83).pdf
the fuel oil shall be considered to have not met the requirement.

5 Repeatability (r) calculation taking into account ISO 4259-2:2017-2 and as defined in the test method used.
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)

Table 1: Summary of Part 1 MARPOL delivered sample procedure

On the basis of the test method referred to in regulation 2.1.30
Applicable limit % m/m: V Result 2.5.1: X V

Result 2.5.2: X > V
0.10 Met the requirement Not met the requirement
0.50
Result X reported to 2 decimal places

2.6 The final results obtained from this verification procedure shall be evaluated by the competent authority.

2.7 The laboratory shall provide a copy of the test record to the competent authority managing the verification procedure.

Part 2 In-use and onboard samples

3 General requirements

3.1 The in-use or onboard sample, as appropriate, shall be used to verify the sulphur

---CHUNK---

SOURCE: MEPC.403(83).pdf
managing the verification procedure.

Part 2 In-use and onboard samples

3 General requirements

3.1 The in-use or onboard sample, as appropriate, shall be used to verify the sulphur content of the fuel oil as represented by that sample of fuel oil at the point of sampling.

3.2 A Party, through its competent authority, shall manage the verification procedure.

3.3 A laboratory undertaking the sulphur testing procedure given in this appendix shall have valid accreditation6 in respect of the test method to be used.

4 Verification procedure Part 2

4.1 The in-use or onboard sample shall be conveyed by the competent authority to the laboratory.

4.2 The laboratory shall:

.1 record the details of the seal number and the sample label on the test record;

.2 record the condition of the seal of the sample as received on the test record; and

.3 reject any sample where the seal has been broken prior to receipt and record that rejection on the test record.

4.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

.1 unseal the sample;