---CHUNK---

SOURCE: MEPC.403(83).pdf
that rejection on the test record.

4.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

.1 unseal the sample;

.2 ensure that the sample is thoroughly homogenized;

6 The laboratory is to be accredited to ISO/IEC 17025:2017 or an equivalent standard for the performance of the given sulphur content test ISO 8754:2003.
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1
Annex 11, page 81

I:\MEPC\MEPC 83-17-Add.1.docx
.3 draw two subsamples from the sample; and

.4 reseal the sample and record the new reseal details on the test record.

4.4 The two subsamples shall be tested in succession, in accordance with the specified test method referred to in regulation 2.1.30. For the purposes of this Part 2 verification procedure, the results obtained shall be referred to as '2A' and '2B':

.1 results 2A and 2B shall be recorded on the test record in accordance with the requirements of the test method; and

---CHUNK---

SOURCE: MEPC.403(83).pdf
procedure, the results obtained shall be referred to as '2A' and '2B':

.1 results 2A and 2B shall be recorded on the test record in accordance with the requirements of the test method; and

.2 if the results of 2A and 2B are within the repeatability (r)7 of the test method, the results shall be considered valid; or

.3 if the results of 2A and 2B are not within the repeatability (r) of the test method, both results shall be rejected and two new subsamples shall be taken by the laboratory and tested. The sample bottle shall be resealed in accordance with paragraph 4.3.4 after the new subsamples have been taken; and

.4 in the case of two failures to achieve repeatability between 2A and 2B, the cause of that failure shall be investigated by the laboratory and resolved before further testing of the sample is undertaken. On resolution of that

repeatability issue, two new subsamples shall be taken in accordance with paragraph 4.3. The sample shall be resealed in accordance with paragraph 4.3.4 after the new subsamples have been taken.

4.5 If the test results of 2A and 2B are valid, an average of these two results shall be

---CHUNK---

SOURCE: MEPC.403(83).pdf
paragraph 4.3. The sample shall be resealed in accordance with paragraph 4.3.4 after the new subsamples have been taken.

4.5 If the test results of 2A and 2B are valid, an average of these two results shall be calculated. That average value shall be referred to as 'Z' and shall be recorded on the test record:

.1 if Z is equal to or less than the applicable limit required by regulation 14, the sulphur content of the fuel oil as represented by the tested sample shall be considered to have met the requirement;

.2 if Z is greater than the applicable limit required by regulation 14 but less than or equal to that applicable limit + 0.59R (where R is the reproducibility of the test method),8 the sulphur content of the fuel oil as represented by the tested sample shall be considered to have met the requirement; or

.3 if Z is greater than the applicable limit required by regulation 14 + 0.59R, the sulphur content of the fuel oil as represented by the tested sample shall be considered to have not met the requirement.

7 Repeatability (r) calculation taking into account ISO 4259-2:2017-2 and as defined in the test method used.

---CHUNK---

SOURCE: MEPC.403(83).pdf
sulphur content of the fuel oil as represented by the tested sample shall be considered to have not met the requirement.

7 Repeatability (r) calculation taking into account ISO 4259-2:2017-2 and as defined in the test method used.

8 Reproducibility (R) calculation taking into account ISO 4259-2:2017-2 and as defined in the test method used.

Table 2: Summary of in-use or onboard sample procedure9

On the basis of the test method referred to in regulation 2.1.30

Applicable limit %m/m:
V
Test margin
value:
W
Result 4.5.1:
Z V
Result
4.5.2:
V < Z W

Result 4.5.3:
Z > W
0.10 0.11 Met the
requirement
Met the
requirement
Not met the
requirement 0.50 0.53

Result Z reported to 2 decimal places

4.6 The final results obtained from this verification procedure shall be evaluated by the competent authority.

4.7 The laboratory shall provide a copy of the test record to the competent authority

---CHUNK---

SOURCE: MEPC.403(83).pdf
Result Z reported to 2 decimal places

4.6 The final results obtained from this verification procedure shall be evaluated by the competent authority.

4.7 The laboratory shall provide a copy of the test record to the competent authority managing the verification procedure.

9 Results of testing undertaken by the company or other entities are outside the MARPOL process and hence should be considered within the approach given by ISO 4259:2017-2 regarding recipient drawn samples.
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1
Annex 11, page 83

I:\MEPC\MEPC 83-17-Add.1.docx
Appendix VII

Emission control areas (regulations 13.6 and 14.3)

1 The boundaries of emission control areas designated under regulations 13.6 and

14.3, other than the Baltic Sea, the North Sea, and the Norwegian Sea areas, are set forth in this appendix.

2 The North American area comprises:

.1 the sea area located off the Pacific coasts of the United States and Canada, enclosed by geodesic lines connecting the following coordinates:

---CHUNK---

SOURCE: MEPC.403(83).pdf
this appendix.

2 The North American area comprises:

.1 the sea area located off the Pacific coasts of the United States and Canada, enclosed by geodesic lines connecting the following coordinates:

Point	Latitude	Longitude
1	32°32.10 N	117°06.11 W
2	32°32.04 N	117°07.29 W
3	32°31.39 N	117°14.20 W
4	32°33.13 N	117°15.50 W