ANNEX
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
PART A
2 General
2.2 Definitions
1 The following new paragraph 2.2.44 is added after paragraph 2.2.43:
"2.2.44 Ship constructed on or after 1 January 2028 means:
.1 for which the building contract is placed on or after 1 January 2028;
or
.2 in the absence of a building contract, the keels of which are laid or
which are at a similar stage of construction on or after 1 July 2028;
or
.3 the delivery of which is on or after 1 January 2032."
PART A-1
Specific requirements for ships using natural gas as fuel
5 Ship design and arrangement
5.3 Regulations General
2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before
paragraph 5.3.3.6:

SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
5.3 Regulations General
2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before
paragraph 5.3.3.6:
"5.3.3.5.1 For ships with suction wells installed in fuel tanks, the bottom of the suction
well may protrude into the vertical extent of the minimum distance specified in 5.3.3.5,
provided that such wells are as small as practicable and the protrusion below the inner
bottom plating does not exceed 25% of the depth of the double bottom or 350 mm,
whichever is less."
3 In sub-paragraph 5.3.4.2, the definition of "H" is replaced by the following:
"H is the distance from baseline, in metres, to the lowermost boundary of the fuel tank
excluding the suction well, if installed; and"
7 Material and general pipe design
7.3 Regulations for general pipe design
4 The following new paragraph 7.3.1.4 is inserted after paragraph 7.3.1.3 and the
subsequent paragraphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6
accordingly:

SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
subsequent paragraphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6
accordingly:
RESOLUTION MSC.567(109) (adopted on 6 December 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

"7.3.1.4 For ships constructed on or after 1 January 2028, pressure relief valves
discharging liquid or gas from the piping system shall discharge into the fuel tanks

whenever the tank MARVS pressure is lower than the setting of the pressure relief valves in accordance with the arrangements in 9.4.2, and shall be designed to ensure that the required discharge capacity is met. Alternatively, they may discharge to the vent mast, if means are provided to detect and dispose of any liquid that may flow into the vent system."
9 Fuel supply to consumers
9.4 Regulations on safety functions of gas supply system
5 The following new paragraph 9.4.2 is inserted after paragraph 9.4.1 and the
---
SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
9.4 Regulations on safety functions of gas supply system
5 The following new paragraph 9.4.2 is inserted after paragraph 9.4.1 and the
subsequent paragraphs 9.4.2 to 9.4.10 are renumbered as 9.4.3 to 9.4.11 accordingly:
"9.4.2 For ships constructed on or after 1 January 2028, fuel tank inlets from pressure relief valve discharge lines, protecting the piping system according to 7.3.1.4, shall be provided with non-return valves in lieu of valves that are automatically operated when the safety system required in 15.2.2 is activated. Safe means for tank isolation during maintenance shall be available according to 18.3 without affecting the proper operation of pressure relief valves."
11 Fire safety
11.3 Regulations for fire protection
6 Paragraph 11.3.2 is replaced by the following:
"11.3.2.1 Any boundary of accommodation spaces, service spaces, control stations, escape routes and machinery spaces, facing fuel tanks on open deck, shall be
---
SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
escape routes and machinery spaces, facing fuel tanks on open deck, shall be
shielded by A -60 class divisions. The A -60 class divisions shall extend up to the underside of the deck of the navigation bridge. For ships constructed on or after 1 January 2028, any such boundary facing the fuel tank on the open deck which is separated by a minimum distance, as determined to the satisfaction of the Administration through a heat anal ysis to provide protection equivalent to an A -60 class division, shall be considered acceptable, and intermediate structures providing heat protection to the above spaces may also be considered acceptable.
Notwithstanding the above-mentioned requirements:
.1 for oil tankers and chemical tankers constructed on or after 1 January 2028, A -60 insulation, required by SOLAS regulation II -2/9.2.4.2.5, shall be considered to meet the above -mentioned requirements provided that the fuel tank is located in the cargo area
---
SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
2/9.2.4.2.5, shall be considered to meet the above -mentioned requirements provided that the fuel tank is located in the cargo area
forward of accommodation spaces, service spaces, control stations, escape routes and machinery spaces. Consideration for the

protection of accommodation block sides may be necessary; and
.2 for ships constructed on or after 1 January 2028, where no source of gas release from the fuel containment system is considered possible, e.g. a type C tank in which tank connections are in a tank connection space, A-60 class shielding is not required.
11.3.2.2 Fuel tanks shall be segregated from cargo in accordance with the requirements of the International Maritime Dangerous Goods (IMDG) Code where fuel tanks are regarded as bulk packaging. For the purposes of stowage and segregation requirements of the IMDG Code, a fuel tank on the open deck shall be considered as a class 2.1 package."
RESOLUTION MSC.567(109) (adopted on 6 December 2024)

SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
a class 2.1 package."
RESOLUTION MSC.567(109) (adopted on 6 December 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

7 Paragraph 11.3.3.1 is replaced by the following:
"11.3.3.1 Notwithstanding the last sentence in paragraph 11.3.3, for ships constructed on or after 1 January 202 8, the fuel storage hold space may be considered as a cofferdam provided that:
.1 the type C tank is not located directly above machinery spaces of category A or other rooms with high fire risk; and
.2 the minimum distance to the A-60 boundary from the outer surface of the insulation system of a type C tank or the boundary of the tank connection space, if any, is not less than 900 mm. For the vacuum insulated type C tank, outer surface of the insulation system means outer surface of the outer shell."
12 Explosion prevention
12.5 Hazardous area zones
12.5.2 Hazardous area zone 1

SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
outer surface of the outer shell."
12 Explosion prevention
12.5 Hazardous area zones
12.5.2 Hazardous area zone 1
8 Sub-paragraph 12.5.2.3 is replaced by the following:
".3 For ships constructed on or after 1 January 2028, areas on open deck, or semi-enclosed spaces on deck, within 3 m of any fuel tank outlet, gas or vapour outlet, bunker manifold valve, other fuel valve, fuel pipe flange, ventilation outlets from zone 1 spaces and fuel tank openings for pressure release provided to permit the flow of small volumes of gas or vapour mixtures caused by thermal variation;
9 The following new sub -paragraph 12.5.2.4 is inserted after sub -paragraph 12.5.2.3 and the subsequent sub -paragraphs 12.5.2.4 to 12.5.2.9 are renumbered as 12.5.2.5 to 12.5.2.10 accordingly:

".4 for ships constructed on or after 1 January 2028, areas on open deck, or semi -enclosed spaces on open deck above and in the vicinity of a fuel tank vent mast outlet within a vertical cylinder of
---
SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
deck, or semi -enclosed spaces on open deck above and in the vicinity of a fuel tank vent mast outlet within a vertical cylinder of unlimited height and 6 m radius centred upon the centre of t he outlet, and within a hemisphere of 6 m radius below the outlet. Where it is not possible to maintain the above distances due to the size and layout of the ship, a reduced zone can be accepted based on a dispersion analysis, using 50% LEL criteria. Th e zone dimensions shall never be less than those given in 12.5.2.3, and shall include a surrounding zone 2 hazardous area meeting the dimensions given in 12.5.3.1."
12.5.3 Hazardous area zone 2
10 The following new paragraph 12.5.3.3 is added after paragraph 12.5.3.2:
"12.5.3.3 In lieu of 12.5.3.1, for ships constructed on or after 1 January 2028, this zone includes spaces 4 m beyond the cylinder and 4 m beyond the hemisphere defined in 12.5.2.4".
RESOLUTION MSC.567(109) (adopted on 6 December 2024)

SOURCE: MSC.567(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf
defined in 12.5.2.4".
RESOLUTION MSC.567(109) (adopted on 6 December 2024)

13 Ventilation
13.3 Regulations General
11 Paragraph 13.3.5 is replaced by the following:
"13.3.5 For ships constructed on or after 1 January 2028, air inlets for hazardous enclosed spaces shall be taken from areas that, except for the inlets, would be non-hazardous. Air inlets for non-hazardous enclosed spaces shall be taken from non-hazardous areas at least 1.5 m away from the boundaries of any hazardous