communication with helicopters in its area of operation.

_____

8 Refer to Volume 3, Part II of annex 10, and Part III, section II of annex 6 to the ICAO Convention.

11.8 Internal communications

All types of MODUs should be fitted with efficient means of communication between the control

---

SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

11.8 Internal communications

All types of MODUs should be fitted with efficient means of communication between the control
room, the bridge (if provided) and position or positions fitted with facilities for operation of radio equipment.

11.9 Performance standards

All radio equipment should be of a type approved by the Administration issuing the licence. Such equipment should conform to appropriate performance standards not inferior to those adopted by the Organization.9

_____

9 Refer to the following performance standards adopted by the Organization:
General requirements
.1 General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids (resolution A.694(17));
.2 Performance standards for the presentation of navigation-related information on shipborne navigational displays (resolution MSC.191(79), as amended);

SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

navigational displays (resolution MSC.191(79), as amended);
.3 Performance standards for bridge alert management (resolution MSC.302(87));

VHF equipment
.4 Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling (resolution MSC.511(105));
.5 Performance standards for survival craft portable two-way VHF radiotelephone apparatus (resolution MSC.515(105));
.6 Recommendation on Performance standards for on -scene (aeronautical) portable two-way VHF radiotelephone apparatus (annex 1 to resolution MSC.80(70), as amended);

MF and HF equipment
.7 System performance standard for the pro mulgation and coordination of maritime safety
---
SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf
MF and HF equipment
.7 System performance standard for the pro mulgation and coordination of maritime safety
information using high-frequency narrow-band direct-printing (resolution MSC.507(105));
.8 Performance standards for shipborne MF and MF/HF radio installations capable of voice
communication, digital selective calling and reception of maritime safety information and
search and rescue related information (resolution MSC.512(105));
.9 Performance standards for the reception of maritime safety information and search and
rescue related information by MF (NAVTEX) and HF (resolution MSC.508(105));

Ship earth stations and enhanced group call (EGC) equipment
.10 Performance standards for Inmarsat -C ship earth stations capable of transmitting and
receiving direct-printing communications (resolution MSC.513(105));
.11 Revised performance standards for enhanced group call (EGC) equipment
(resolution MSC.306(87), as amended);

SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf
.11 Revised performance standards for enhanced group call (EGC) equipment
(resolution MSC.306(87), as amended);
.12 Performance standards for a ship earth station for use in the GMDSS
(resolution MSC.434(98));

Integrated radiocommunication systems
.13 Performance standards for a shipborne integrated communication system (ICS) when
used in the Global Maritime Distress and Safety System (GMDSS)
(resolution MSC.517(105));

Emergency position-indicating radio beacons
.14 Performance standards for float-free release and activation arrangements for emergency
radio equipment (resolution A.662(16));
.15 Performance standards for float -free emergency position -indicating radio beacons
(EPIRBs) operating on 406 MHz (resolution MSC.471(101));

Search and rescue transmitters and transponders
.16 Performance standards for search and rescue radar transponders
(resolution MSC.510(105)); and

SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf
Search and rescue transmitters and transponders
.16 Performance standards for search and rescue radar transponders
(resolution MSC.510(105)); and

.17 Performance standards for survival craft AIS search and rescue transmitters (AIS -SART) for use in search and rescue operations (resolution MSC.246(83)).

11.10 Survey of the radio station

11.10.1 The radio station of a unit should be subject to survey as specified below:

.1 by the Administration which issues the licence or its authorized representative before the radio station is put into service;

.2 when the unit is moved and comes under the administrative control of another coastal State a survey may be carried out by that State or its authorized representative; and
---
SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf
another coastal State a survey may be carried out by that State or its authorized representative; and

.3 within three months before or after the anniversary date of the MODU Code certificate, a periodical survey carried out by an officer of the Administration and/or the coastal State or their respective authorized representative.

11.10.2 EPIRBs should be serviced at intervals not exceeding five years, to be performed by an approved shore-based maintenance facility.

11.10.3 The Administration may recognize the coastal State as its authorized representative.

11.10.4 In every case when an authorized representative of the coastal State carries out an inspection, a report should be issued and kept with the radio documents, and a copy, if requested, should be forwarded to the Administration.

11.11 Navigation equipment

11.11.1 All units should comply with SOLAS chapter V.

11.11.2 Administrations may exempt units from navigation equipment carriage requirements,
---
SOURCE: MSC.506(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf
11.11.1 All units should comply with SOLAS chapter V.

11.11.2 Administrations may exempt units from navigation equipment carriage requirements,

in accordance with SOLAS regulation V/3.

***

RESOLUTION MSC.506(105) (adopted on 28 April 2022)
AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 2009 (2009 MODU CODE)
RESOLUTION MSC.506(105) (adopted on 28 April 2022)
AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 2009 (2009 MODU CODE)

SOURCE: MSC.524(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.524(106).pdf
RESOLUTION MSC.524(106) (adopted on 10 November 2022)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING
GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

RESOLUTION MSC.524(106)
(adopted on 10 November 2022)

AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

NOTING resolution MSC.391(95), by which it adopted the International Code of Safety for Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory under chapters II-1 and II-2 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"),