In the individual schedule for "SYNTHETIC CALCIUM FLUORIDE", under the section for "Description", replace "70%-80%" with the words "70% to 80%", replace "5% -10%" with the words "5% to 10%" and replace "10%-20%" with the words "10% to 20%".

New individual schedules

Insert the following new individual schedules in alphabetical order:

"AMMONIUM NITRATE BASED FERTILIZER

This schedule shall only apply to ammonium nitrate based fertilizers which do not meet any of the criteria on dangerous goods or materials hazardous only in bulk specified in 9.2.2 or 9.2.3 of this Code, respectively.

Ammonium nitrate based fertilizers transported in conditions mentioned in this schedule are straight nitrogen fertilizers or compound fertilizers within the following composition limits:

SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
straight nitrogen fertilizers or compound fertilizers within the following composition limits:

Straight nitrogen fertilizers containing less than 2% chloride, and

.1 not more than 70% ammonium nitrate with other inorganic materials; or

.2 not more than 80% ammonium nitrate mixed with calcium carbonate and/or dolomite and/or mineral calcium sulphate and not more than 0.4% total combustible organic material calculated as carbon; or

.3 mixtures of ammonium nitrate and ammonium sulphate with not more than 45% ammonium nitrate and not more than 0. 4% total combustible organic material calculated as carbon.

Compound NPK/NK/NP fertilizers

.1 mixtures of nitrogen with phosphate and/or potash containing not more than 70% ammonium nitrate and not more than 0.4% total combustible
---
SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
.1 mixtures of nitrogen with phosphate and/or potash containing not more than 70% ammonium nitrate and not more than 0.4% total combustible organic material calculated as carbon or not more than 45% ammonium nitrate and unrestricted combustible material; and

.2 either less than 20% of ammonium nitrate content or less than 2% of chloride (as indicated in the grey area of the figure for NPK/NP/NK fertilizers below).

The shipper shall declare the ammonium nitrate content and the chloride content in accordance with 4.2 of this Code.

Notwithstanding the above, fertilizers within these composition limits are not subject to the provisions of this schedule, if they are assigned class 9 due to the hazard of self -sustaining decomposition based on the results of the trough test (referred to in the UN Manual of Tests and Criteria, part III, section 39).

Description
Crystals, granules or prills. Non-cohesive when dry. Wholly or partly soluble in water. Common
---
SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
and Criteria, part III, section 39).

Description
Crystals, granules or prills. Non-cohesive when dry. Wholly or partly soluble in water. Common products, listed (non-exhaustive) under this schedule are:

.1 calcium ammonium nitrate;

.2 ammonium sulphate nitrate;

.3 ammonium nitrate with other sulphates (e.g. calcium or magnesium sulphate); and

.4 compound NPK/NP/NK fertilizer.
% Ammonium
nitrate
% Chloride
70 %
20 %
2 %
....
RESOLUTION MSC.500(105) (adopted on 28 April 2022)
AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE
- 9 -

Characteristics
Physical properties
Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t)
1 to 5 mm 27° to 42° 1,000 to 1,200 0.83 to 1.00
Hazard classification
Class Subsidiary hazard(s) MHB Group
Not applicable Not applicable Not applicable C

Hazard
When this cargo is heated strongly, it will decompose and give off toxic gases with the risk of
---
SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
Hazard
When this cargo is heated strongly, it will decompose and give off toxic gases with the risk of
toxic fumes in the cargo hold, adjacent spaces and on deck. If decomposition is initiated in a localized area, it is highly unlikely to spread throughout the mass of the fertilizer.

Fertilizer dust might be irritating to skin and mucous membranes. It is a hygroscopic cargo and will cake if wet.

Stowage and segregation
"Separated from" sources of heat.

Hold cleanliness
Clean and dry as relevant to the hazards of the cargo.

Weather precautions
This cargo shall be kept as dry as practicable. This cargo shall not be handled during precipitation. During handling of this cargo, all non -working hatches of the cargo spaces into which this cargo is loaded, or to be loaded, shall be closed.

Loading
Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code.

Precautions

SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
Loading
Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code.

Precautions
"NO SMOKING" signs shall be displayed on deck whenever this cargo is on board.
Smoking shall not be allowed on deck and in the cargo spaces.

No welding, burning, cutting or other operations involving the use of fire, open flame, spark or arc-producing equipment shall be carried out on equipment or structures in direct contact with the fertilizer.

In order to avoid heating the cargo, all electrical equipment or other equipmen t capable of developing heat, other than that of approved safe type, in the cargo spaces to be used for this cargo shall be electrically disconnected from the power source, by appropriate means other than a fuse, at a point external to the space. This situation shall be maintained while the cargo is on board.

Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo.

SOURCE: MSC.500(105).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.500(105).pdf
is on board.

Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo.

Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Due consideration shall be given to protect equipment from the dust of the cargo. Persons who may be exposed to the dust of the cargo shall wear goggles or other equivalent dust eye -protection and dust filter masks. Those persons shall wear protective clothing, as necessary.

Ventilation
The cargo spaces carrying this cargo shall not be ventilated during voyage, except in an emergency.

Carriage
No special requirements.

Discharge
This cargo is hygroscopic and may cake in overhangs, impairing safety during discharge.

If this cargo has hardened, it shall be trimmed to avoid the formation of overhangs, as necessary.

Clean-up

SOURCE: MSC.500(105).pdf