SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
"north-up" orientation. Other orientations are permitted. When such orientations are displayed, the orientation should be altered in steps large enough to avoid unstable display of the chart information.

8.2 ECDIS should provide for true motion mode. Other modes are permitted.

8.3 When true motion mode is in use, reset and generation of the chart display of the neighbouring area should take place automatically at own ship's distance from the edge of the display as determined by the mariner.

8.4 It should be possible to manually change the displayed chart area and the position of own ship relative to the edge of the display.

8.5 If the area covered by the ECDIS display includes waters for which no ENC at a scale appropriate for navigation is available, the areas representing those waters should carry an indication (see appendix 5) to the mariner to refer to the paper chart or to the RCDS mode of operation (see appendix 7).

9 COLOURS AND SYMBOLS

SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
operation (see appendix 7).

9 COLOURS AND SYMBOLS

9.1 IHO-recommended colours and symbols should be used to represent system database information.5

5 IHO Publication S-52 - Specifications for Chart Content and Display Aspects of ECDIS and S-101 Portrayal Catalogue (see appendix 1) and S-98.

9.2 The colours and symbols other than those mentioned in 9.1 should comply with the applicable requirements contained in the IMO standards for navigational symbols.6

9.3 ECDIS should allow the mariner to select whether own ship is displayed in true scale or as a symbol.

10 DISPLAY REQUIREMENTS

10.1 ECDIS should be capable of displaying information for:

.1 route planning and supplementary navigation tasks; and

.2 route monitoring.

SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
10.1 ECDIS should be capable of displaying information for:

.1 route planning and supplementary navigation tasks; and

.2 route monitoring.

10.2 The effective size of the chart presentation for route monitoring should be at least 270 mm x 270 mm.

10.3 The display should be capable of meeting the colour and resolution recommendations of IHO.5

10.4 The method of presentation should ensure that the displayed information is clearly visible to more than one observer in the conditions of light normally experienced on the bridge of the ship by day and by night.

10.5 If information categories included in the standard display (see appendix 2) are removed to customize the display, this should be permanently indicated. Identification of categories which are removed from the standard display should be shown on demand.

11 ROUTE PLANNING, MONITORING AND VOYAGE RECORDING

11.1 It should be possible to carry out route planning, route monitoring in a simple and
---
SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
11 ROUTE PLANNING, MONITORING AND VOYAGE RECORDING

11.1 It should be possible to carry out route planning, route monitoring in a simple and reliable manner.

11.2 The largest scale data available in the system database for the area given should always be used by the ECDIS for all alerts or indications of crossing the ship's safety contour and of entering a prohibited area, and for alerts and indications according to appendix 5.

11.3 Route planning

11.3.1 It should be possible to carry out route planning including both straight and curved segments.

11.3.2 It should be possible to adjust a planned route alphanumerically and graphically including:

.1 adding waypoints to a route;

.2 deleting waypoints from a route; and

.3 changing the position of a waypoint.

6 SN.1/Circ.243/Rev.2.

5 IHO Publication S-52 - Specifications for Chart Content and Display Aspects of ECDIS and S-101 Portrayal Catalogue (see appendix 1) and S-98.

SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
Catalogue (see appendix 1) and S-98.

11.3.3 It should be possible to plan one or more alternative routes in addition to the selected route. The selected route should be clearly distinguishable from the other routes.

11.3.4 A graphical indication is required if the mariner plans a route closer than a user-specified distance from own ship's safety contour.

11.3.5 A graphical indication should be given if the mariner plans a route closer than a user-specified distance from the boundary of a user-selectable category of prohibited area or geographic area for which special conditions exist (see appendix 4). A graphic al indication should also be given if the mariner plans a route closer than a user -specified distance from a
---
SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
should also be given if the mariner plans a route closer than a user -specified distance from a user-selectable category of point objects, such as a fixed or floating aid to navigation or isolated danger. The user -selectable categories should be the same as the user selections for the display of objects and be based on IHO standards. There should be a permanent indication when any user -selectable categories are deselected. Details of the deselection should be available on demand.

11.3.6 It should be possible for the mariner to select that the indications of 11.3.4 and 11.3.5 take into account accuracy information of relevant hydrographic information, as defined by IHO standards.

11.3.7 It should also be possible to perform a complete route check to support the appraisal and planning process according to the applicable parts of resolution A.893(21). Detected objects should be available for review in graphical form and, on demand, in textual form.

SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
objects should be available for review in graphical form and, on demand, in textual form.

11.3.8 It should be possible for the mariner to specify a cross track limit of deviation from the planned route at which an automatic off-track alarm should be activated.

11.4 Route monitoring

11.4.1 For route monitoring the selected route and own ship's position should appear whenever the display covers that area.

11.4.2 It should be possible to display a sea area that does not have the ship on the display (e.g. for look ahead, route planning), while route monitoring. If this is done on the display used for route monitoring, the automatic route monit oring functions (e.g. updating ship's position, and providing alerts and indications) should be continuous. It should be possible to return to the route monitoring display covering own ship's position immediately by single operator action.

11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical
---
SOURCE: MSC.530(106).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical indication if, within a specified time or distance set by the mariner, own ship will pass closer than a user-selected distance from the safety contour. There should be a permanent indication when the safety contour alarm is deselected.

11.4.4 ECDIS should give a warning or caution, or indication, as selected by the mariner, and related graphical indication if, within a specified time or distance set by the mariner, own ship will pass closer than a user -selected distance from the boundary of a user -selectable category of prohibited area or of a geographical area for which special conditions exist (see appendix 4). The user -selectable categories should be the same as user selec tions for the display of objects and be based on IHO standards. There should be a permanent indication when any user -selectable categories are deselected. Details of the deselection should be