ship; or

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
construction on or after 1 January 2026, any installation date on the
ship; or
.2 for ships other than those specified in .1, including those
constructed before 1 January 2009, a contractual delivery date for
lifting appliance or anchor handling winches, or in the absence of
a contractual delivery date, the actual delivery date of the
lifting appliance or anchor handling winches to the ship on or
after 1 January 2026."
RESOLUTION MSC.532(107) (adopted on 8 June 2023)
2023 AMENDMENTS TO THE INTERNATIONAL CONVENTION
FOR THE SAFETY OF LIFE AT SEA, 1974
- 3 -
Part A-1
Structure of ships
2 The following new regulation is added after existing regulation II-1/3-12:
"Regulation 3-13
Lifting appliances and anchor handling winches
1 Application
1.1 Unless expressly provided otherwise, this regulation shall apply to lifting
appliances and anchor handling winches, and loose gear utilized with the lifting
appliances and the anchor handling winches.

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
appliances and anchor handling winches, and loose gear utilized with the lifting
appliances and the anchor handling winches.
1.2 Notwithstanding the above, this regulation does not apply to:
.1 lifting appliances on ships certified as MODUs;
.2 lifting appliances used on offshore construction ships, such as
pipe/cable laying/repair or offshore installation vessels, including
ships for decommissioning work, which comply with standards
acceptable to the Administration;
.3 integrated mechanical equipment for opening and closing hold
hatch covers; and
.4 life-saving launching appliances complying with the International
Life-Saving Appliance (LSA) Code.
1.3 The Administration shall determine to what extent the provisions of
paragraphs 2.1 and 2.4 do not apply to lifting appliances which have a safe working
load below 1,000 kg.
2 Design, construction and installation
2.1 Lifting appliances installed on or after 1 January 2026 shall be:

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf

load below 1,000 kg.
2 Design, construction and installation
2.1 Lifting appliances installed on or after 1 January 2026 shall be:
.1 designed, constructed and installed in accordance with the requirements of a classification society which is recognized by the Administration in accordance with the provisions of regulation XI-1/1 or standards acceptable to the Administration which provide an equivalent level of safety; and
.2 load tested and thoroughly examined after installation and before being taken into use for the first time and after repairs, modifications or alterations of major character.
2.2 Anchor handling winches installed on or after 1 January 2026 shall be designed, constructed, installed and tested to the satisfaction of the Administration, based on the Guidelines developed by the Organization.
2.3 Lifting appliances installed on or after 1 January 2026 shall be permanently marked and provided with documentary evidence for the safe working load (SWL).

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
marked and provided with documentary evidence for the safe working load (SWL).

2.4 Lifting appliances installed before 1 January 2026 shall be tested and thoroughly examined, based on the Guidelines developed by the Organization and comply with paragraph 2.3 no later than the date of the first renewal survey on or after 1 January 2026.
2.5 Anchor handling winches installed before 1 January 2026 shall be tested and thoroughly examined, based on the Guidelines developed by the Organization no later than the date of the first renewal survey on or after 1 January 2026.
3 Maintenance, operation, inspection and testing
All lifting appliances and anchor handling winches, regardless of installation date, and all loose gear utilized with any lifting appliances and anchor handling winches, shall
---
SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
all loose gear utilized with any lifting appliances and anchor handling winches, shall
be operationally tested, thoroughly examined, inspected, operated and maintained, based on the Guidelines developed by the Organization.
4 Inoperative lifting appliances and anchor handling winches
Except as provided in regulation I/11(c), while all reasonable steps shall be taken to maintain lifting appliances, anchor handling winches and loose gear to which this regulation applies in working order, malfunctions of that equipment shall not be assumed as making the ship unseaworthy or as a reason for delaying the ship in ports, provided that action has been taken by the master to take the inoperative lifting appliance or anchor handling winch into account in planning and executing a safe voyage."
CHAPTER II-2
CONSTRUCTION FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION

Part A
General
Regulation 1
Application
2 Applicable requirements to existing ships

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
Part A
General
Regulation 1
Application
2 Applicable requirements to existing ships
3 The following new paragraph 2.10 is added after existing paragraph 2.9:
"2.10 All ships constructed before 1 January 2026 shall comply with regulation 10.11.2, as adopted by resolution MSC.532(107), not later than the date of the first survey on or after 1 January 2026."
RESOLUTION MSC.532(107) (adopted on 8 June 2023)
2023 AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

Part C
Suppression of fire
Regulation 10
Fire fighting
4 The following new paragraph 11 is added after existing section 10:
"11 Fire-extinguishing media restrictions
The purpose of this paragraph is to protect persons on board against exposure to dangerous substances used in fire fighting, as well as to minimize the impact of fire-extinguishing media that are deemed detrimental to the environment.
11.1 Application

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
fire-extinguishing media that are deemed detrimental to the environment.
11.1 Application
This paragraph applies to ships constructed on or after 1 January 2026.
11.2 General
11.2.1 The prohibited substances in this paragraph shall be delivered to appropriate shore-based reception facilities when removed from the ship.
11.2.2 Use or storage of extinguishing media containing perfluorooctane sulfonic acid (PFOS) shall be prohibited."
CHAPTER V
SAFETY OF NAVIGATION
Regulation 2
Definitions
5 The following new paragraphs are added after existing paragraph 7:
"8 Bulk carrier means a bulk carrier as defined in regulation XII/1.1.
9 Containership means a ship which is intended primarily to carry containers."
Regulation 19

Carriage requirements for shipborne navigational systems and equipment
6 The following new paragraph 2.12 is added after existing paragraph 2.11:
"2.12 Containerships and bulk carriers of 3,000 gross tonnage and upwards
---
SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
"2.12 Containerships and bulk carriers of 3,000 gross tonnage and upwards
constructed on or after 1 January 2026 shall be fitted with an electronic inclinometer,
or other means, to determine, display and record the ship's roll motion."
RESOLUTION MSC.532(107) (adopted on 8 June 2023)
2023 AMENDMENTS TO THE INTERNATIONAL CONVENTION
FOR THE SAFETY OF LIFE AT SEA, 1974
- 6 -
CHAPTER XIV
SAFETY MEASURES FOR SHIPS OPERATING IN POLAR WATERS
Regulation 2
Application
7 Regulation 2 is replaced by the following:
"Regulation 2
Application
1 Unless expressly provided otherwise, this chapter applies to the following
ships operating in polar waters:
.1 ships certified in accordance with chapter I;
.2 fishing vessels of 24 metres in length overall and above;
.3 pleasure yachts of 300 gross tonnage and upwards not engaged in
trade; and
.4 cargo ships of 300 gross tonnage and upwards but
below 500 gross tonnage.

SOURCE: MSC.532(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.532(107).pdf
trade; and
.4 cargo ships of 300 gross tonnage and upwards but
below 500 gross tonnage.
2 Ships subject to paragraph 1.1 constructed before 1 January 2017 shall
meet the relevant requirements of the Polar Code by the first intermediate or renewal
survey, whichever occurs first, after 1 January 2018.