boats, the self-righting test should only be done in the light condition, and 6.14.1.1, 6.14.3, 6.14.4, 6.14.5 and 6.14.9 are not applicable. With regard to 6.14.2, a bo at fitted with a helmsman 's emergency release switch should be considered to be arranged to stop automatically when inverted."

RESOLUTION MSC.544(107) (adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
MSC 107/20/Add.1
Annex 14, page 4

I:\MSC\107\MSC 107/20/Add.1.docx
7.5 Inflated fast rescue boats

8 Paragraph 7.5 is replaced by the following:

"Inflated fast rescue boats should be subjected to the tests prescribed in 6.4.1, 6.6.1, 6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1), 6.11, 6.12, 6.14.1 to 6.14.8 (if inflated fast
---
SOURCE: MSC.545(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.545(107).pdf
6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1), 6.11, 6.12, 6.14.1 to 6.14.8 (if inflated fast rescue boat is self-righting), 7.1.2, 7.1.3, 7.1.6 (if inflated fast rescue boat is equipped with outboard motor), 7.1.7 (if inflated fast rescue boat is not self-righting), 7.1.8, 7.2.2 to 7.2.16 and 7.4.2."

7.6 Rigid/inflated fast rescue boats

9 Paragraph 7.6 is replaced by the following:

"Rigid/inflated fast rescue boats should be subjected to the tests prescribed in 6.2 (for hull), 7.2.14 (for inflated part), 6.4.1, 6.6.1, 6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1) to 6.12, 6.14.1 to 6.14.8 (if rigid/inflated fast rescue boat it self-righting), 7.1.2 to 7.1.4, 7.1.6 (if rigid/inflated rescue boat is equipped with outboard motor), 7.1.7 (if rigid/inflated fast rescue boat is not self -righting), 7.1.8, 7.2.2 to 7.2.11, 7.2.15, 7.2.16, 7.3.2 and 7.4.2."

APPENDIX 1

ADULT REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION

SOURCE: MSC.545(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.545(107).pdf
7.2.16, 7.3.2 and 7.4.2."

APPENDIX 1

ADULT REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION

10 Paragraph 2 is replaced by the following:

"2 MATERIALS

All materials used should comply with ISO 12402-7:2020."

APPENDIX 2

CHILD REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION

11 Paragraph 2 is replaced by the following:

"2 MATERIALS

All materials used should comply with ISO 12402-7:2020."

APPENDIX 3

INFANT REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION

12 Paragraph 2 is replaced by the following:

"2 MATERIALS

All materials used should comply with ISO 12402-7:2020."

***

RESOLUTION MSC.544(107) (adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
RESOLUTION MSC.544(107) (adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

SOURCE: MSC.544(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf
RESOLUTION MSC.544(107) (adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

ANNEX 14
RESOLUTION MSC.544(107)
(adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
THE MARITIME SAFETY COMMITTEE,
RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO that the Assembly, when adopting resolution A.689(17) on Testing of life-saving appliances, authorized the Committee to keep the annexed Recommendation on testing of life -saving appliances under review and to adopt, when appropriate, amendments thereto,
RECALLING FURTHER that, since the adoption of resolution A.689(17), the Committee has amended the Recommendation annexed thereto by resolutions MSC.54(66) and MSC.81(70),
---
SOURCE: MSC.544(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf
amended the Recommendation annexed thereto by resolutions MSC.54(66) and MSC.81(70),
and by circulars MSC/Circ.596, MSC/Circ.615 and MSC/Circ.809,
RECOGNIZING the need to ensure that the references in the Revised recommendation on testing of life-saving appliances (resolution MSC.81(70)) are kept up to date,
1 ADOPTS the Amendments to the Revised recommendation on testing of life -saving appliances (resolution MSC.81(70)), set out in the annex to the present resolution;
2 RECOMMENDS Governments to ensure that life -saving appliances installed on or after 1 January 2029 conform to the amended prototype tests in sections 6 (Lifeboats) and 7 (Rescue boats and fast rescue boats), as set out in the annex to the present resolution;
3 INVITES Contracting Governments to the SOLAS Convention to bring the above amendments to the attention of all parties concerned.
RESOLUTION MSC.544(107) (adopted on 8 June 2023)

SOURCE: MSC.544(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf
amendments to the attention of all parties concerned.
RESOLUTION MSC.544(107) (adopted on 8 June 2023)
AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

ANNEX

AMENDMENTS TO THE REVISED RECOMMENDATION ON
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

PART 1 PROTOTYPE TESTS FOR LIFE-SAVING APPLIANCES

2 LIFEJACKETS

2.4 Tests of components other than buoyancy materials

1 The footnote to paragraph 2.4 is replaced by the following:

"* Refer to the recommendations of the International Organization for Standardization, in particular publication ISO 12402 -7:2020 Personal flotation devices. Part 7: Materials and components. Safety requirements and test methods."

2.6 Tests for lifejacket buoyancy material

Tensile strength test

2 The footnote to paragraph 2.6.8 is replaced by the following:

SOURCE: MSC.544(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf
2.6 Tests for lifejacket buoyancy material

Tensile strength test

2 The footnote to paragraph 2.6.8 is replaced by the following:

" * Refer to the recommendations of the International Organization for Standardization, in particular publication ISO 12402-7:2020, Personal flotation devices. Part 7: Materials and components. Safety requirements and test methods."

3 IMMERSION SUITS

3.2 Thermal protective tests

General

3 Paragraph 3.2.3 is replaced by the following:

"3.2.3 Where human subjects are used, the tests should always be conducted under the supervision of a physician. Emergency resuscitation equipment should be available during all tests. For safety reasons, ECG should be monitored during every test. Testing should be stopped at the wish of the test subjects, if the falling rate of the core temperature is more than 1.5ºC per hour after the first half hour, if the skin
---
SOURCE: MSC.544(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf
the core temperature is more than 1.5ºC per hour after the first half hour, if the skin
temperature of the hand, foot or lumbar region should fall below 10 ºC for more than 15 minutes, or if the attending physician considers it advisable."