depletion in the cargo space, an appropriate instrument for measuring the concentration of gas or oxygen in the air shall be provided together with detailed instructions for its use. Such an instrument shall be to the satisfaction of the Administration.

2 The A

dministration shall take steps to ensure that crews of ships are trained in the use of such instruments.

Regu

lation 4

SOURCE: MSC.539(107).pdf

URL:

https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf

the Administration.

2 The A

dministration shall take steps to ensure that crews of ships are trained in the use of such instruments.

Regu

lation 4

The use of pesticides in ships

App

ropriate precautions shall be taken in the use of pesticides in ships, in particular for the purposes of fumigation.

Regu

lation 5

Stowage and securing

1 Car

go, cargo units and cargo transport units carried on or under deck shall be so loaded, stowed and secured as to prevent as far as is practicable, throughout the voyage, damage or hazard to the ship and the persons on board, and loss of cargo overboard.

2 Car

go, cargo units and cargo transport units shall be so packed and secured within the unit as to prevent, throughout the voyage, damage or hazard to the ship and the persons on board.

3 App

ropriate precautions shall be taken during loading and transport of heavy cargoes or cargoes with

---

SOURCE: MSC.539(107).pdf

URL:

https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf

3 App

ropriate precautions shall be taken during loading and transport of heavy cargoes or cargoes with abnormal physical dimensions to ensure that no structural damage to the ship occurs and to maintain adequate stability throughout the voyage.

4 App

ropriate precautions shall be taken during loading and transport of cargo units and cargo transport units on board ro-ro ships, especially with regard to the securing arrangements on board such ships and on the cargo units and cargo transport units and with regard to the strength of the securing points and lashings.

5 Fre

ight containers shall not be loaded to more than the maximum gross weight indicated on the Safety Approval Plate under the International Convention for Safe Containers (CSC), as amended.

6 All c

argoes, other than solid and liquid bulk cargoes, cargo units and cargo transport units, shall be loaded, stowed and secured throughout the voyage in accordance with the Cargo Securing Manual approved by the

---

SOURCE: MSC.539(107).pdf

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
stowed and secured throughout the voyage in accordance with the Cargo Securing Manual approved by the
10
RESOLUTION MSC.539(107) (adopted on 8 June 2023)
2023 AMENDMENTS TO THE
INTERNATIONAL MARITIME SOLID BULK CARGOES (IMSBC) CODE
Non-c
ommercial use only
Adm
inistration. In ships with ro-ro spaces, as defined in regulation II-2/3.41, all securing of such cargoes, cargo units, and cargo transport units, in accordance with the Cargo Securing Manual, shall be completed before the ship leaves the berth. The Cargo Securing Manual shall be drawn up to a standard at least equivalent to relevant guidelines developed by the Organization.
Part
B
Spec
ial provisions for solid bulk cargoes
Regu
lation 6
Acceptability for shipment
1 Pri
or to loading a solid bulk cargo, the master shall be in possession of comprehensive information on the ships stability and on the distribution of cargo for the standard loading conditions. The method of providing such
---
SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
ships stability and on the distribution of cargo for the standard loading conditions. The method of providing such information shall be to the satisfaction of the Administration.
Regu
lation 7
Loading, unloading and stowage of solid bulk cargoes
1 For t
he purpose of this regulation, terminal representative means a person appointed by the terminal or other facility, where the ship is loading or unloading, who has responsibility for operations conducted by that terminal or facility with regard to the particular ship.
To enable the master to prevent excessive stresses in the ships structure, the ship shall be provided with a booklet, which shall be written in a language with which the ships officers responsible for cargo operations are familiar. If this language is not English, the ship shall be provided with a booklet written also in the English language. The booklet shall, as a minimum, include:
.1 sta
bility data, as required by regulation II-1/5-1;
.2 bal

SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
booklet shall, as a minimum, include:
.1 sta
bility data, as required by regulation II-1/5-1;

.2 bal
lasting and deballasting rates and capacities;
.3 max
imum allowable load per unit surface area of the tank top plating;
.4 max
imum allowable load per hold;
.5 gen
eral loading and unloading instructions with regard to the strength of the ships structure including any limitations on the most adverse operating conditions during loading, unloading, ballasting opera - tions and the voyage;
.6 any s
pecial restrictions such as limitations on the most adverse operating conditions imposed by the Administration or organization recognized by it, if applicable; and
.7 whe
re strength calculations are required, maximum permissible forces and moments on the ships hull during loading, unloading and the voyage.
3 Bef
ore a solid bulk cargo is loaded or unloaded, the master and the terminal representative shall agree on a
---
SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
3 Bef
ore a solid bulk cargo is loaded or unloaded, the master and the terminal representative shall agree on a
plan which shall ensure that the permissible forces and moments on the ship are not exceeded during loading or unloading, and shall include the sequence, quantity and rate of loading or unloading, taking into consideration the speed of loading or unloading, the number of pours and the deballasting or ballasting capability of the ship. The plan and any subsequent amendments thereto shall be lodged with the appropriate authority of the port State.

Non-commercial use only
4 The m
aster and terminal representative shall ensure that loading and unloading operations are conducted in accordance with the agreed plan.
5 If du
ring loading or unloading any of the limits of the ship referred to in paragraph 2 are exceeded or are
---
SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
accordance with the agreed plan.
5 If du
ring loading or unloading any of the limits of the ship referred to in paragraph 2 are exceeded or are
likely to become so if the loading or unloading continues, the master has the right to suspend operation and the obligation to notify accordingly the appropriate authority of the port State with which the plan has been lodged. The master and the terminal representative shall ensure that corrective action is taken. When unloading cargo, the master and terminal representative shall ensure that the unloading method does not damage the ships structure.
6 The m
aster shall ensure that ships personnel continuously monitor cargo operations. Where possible, the ships draught shall be checked regularly during loading or unloading to confirm the tonnage figures supplied.

Each draught and tonnage observation shall be recorded in a cargo logbook. If significant deviations from the
---
SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
Each draught and tonnage observation shall be recorded in a cargo logbook. If significant deviations from the agreed plan are detected, cargo or ballast operations or both shall be adjusted to ensure that the deviations are corrected.
Chapt
er VII
Car
riage of dangerous goods
Part A-1
Car
riage of dangerous goods in solid form in bulk
Regu
lation 7
Definitions
Dan
gerous goods in solid form in bulk means any material, other than liquid or gas, consisting of a combination of particles, granules or any larger pieces of material, generally uniform in composition, which is covered by the IMDG Code and is loaded directly into the cargo spaces of a ship without any intermediate form of containment, and includes such materials loaded in a barge on a barge-carrying ship.
Regu
lation 7-1
Application
1 Unl
ess expressly provided otherwise, this part applies to the carriage of dangerous goods in solid form in bulk
---
SOURCE: MSC.539(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.539(107).pdf
Regu
lation 7-1
Application
1 Unl
ess expressly provided otherwise, this part applies to the carriage of dangerous goods in solid form in bulk in all ships to which the present regulations apply and in cargo ships of less than 500 gross tonnage.
2 The c