over the diving operations of the diving unit.

3.6 Cylinder means a pressure container for the storage and transport of gases under pressure.

3.7 Daughter-craft means a workboat deployed from and/or operating in conjunction with a diving platform; the workboat is used to deploy divers into and recover them from the water.

3.8 Dive basket (synonymous with diving basket, diving stage or diving cage) means a diver deployment and recovery device normally designed with an open cage structure.

3.9 Diving depth means the depth of water or equivalent pressure to which the diver is exposed at any time during a dive or inside a pressure vessel for human occupancy (PVHO).

3.10 Diving bell (synonymous with closed bell and submersible decompression chamber) means a submersible pressure vessel for human occupancy (PVHO), including its fitted

---

SOURCE: MSC.548(107).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf

means a submersible pressure vessel for human occupancy (PVHO), including its fitted equipment, for transfer of diving personnel between the work location and the surface compression chamber.

3.11 Diving operation means a planned activity where one or more persons are exposed to a pressure greater than 100 mbar above atmospheric pressure and which is supported by a pressure vessel for human occupancy (PVHO) and/or a launch and recovery system (LARS).

3.12 Diving organization means the legal entity responsible for conducting a diving operation.

3.13 Diving platform means the ship, floating structure or mobile offshore drilling unit (MODU) from which a diving operation is being conducted.

3.14 Diving system means the whole plant and equipment necessary for the conduct of diving operations and for the evacuation of divers.

3.15 Diving system internal muster point means the location within the surface

---

SOURCE: MSC.548(107).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
diving operations and for the evacuation of divers.

3.15 Diving system internal muster point means the location within the surface compression chamber complex where the divers gather before entering the hyperbaric survival craft (HBSC) access trunking.

3.16 Diving unit means the combined diving system and diving platform, installed and integrated to conduct diving operations.

3.17 Essential services means the services for maintaining the diving system functionality

with regard to the safety, health and environment of the divers in a hyperbaric environment and at the worksite.

3.18 FSS Code means the International Code for Fire Safety Systems, as defined in SOLAS chapter II-2.

3.19 FTP Code means the International Code for Application of Fire Test Procedures, 2010 (2010 FTP Code), as defined in SOLAS chapter II-2.

SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
RESOLUTION MSC.548(107) (adopted on 5 June 2023)
INTERNATIONAL CODE OF SAFETY OR DIVING OPERATIONS, 2023 (2023 DIVING CODE)
MSC 107/20/Add.1

3.20 Hazardous areas are those locations in which an explosive gas -air mixture is continuously present, or present for long periods (zone 0); in which an explosive gas -air mixture is likely to occur in normal operation (zone 1); in which an explosive gas-air mixture is not likely to occur, and if it does it will only exist for a short time (zone 2).

3.21 Hyperbaric evacuation means the emergency transport of divers under pressure from a diving unit to a place of safety where planned decompression can be completed.

3.22 Hyperbaric survival craft (HBSC) means a pressure vessel for human occupancy (PVHO) and associated support plant and equipment whereby divers under pressure can be
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
(PVHO) and associated support plant and equipment whereby divers under pressure can be safely evacuated from a diving unit until recovered to a position where planned decompression can be completed.

3.23 Launch and recovery system (LARS) means the plant and equipment necessary for lowering, raising and transporting divers between the diving platform and/or the surface compression chamber into and from the sea or onto a support vessel, as the case may be. These systems are used for the deployment and recovery of dive baskets, wet bells, diving bells, daughter-craft and HBSC.

3.24 Living compartment means the part of the surface compression chamber which is intended to be used as the main habitation for the divers during diving operations and which is equipped for such purpose.

3.25 LSA Code means the International Life-Saving Appliance Code, as defined in SOLAS

chapter III.

3.26 Mating device means the equipment necessary for the connection and disconnection
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
chapter III.

3.26 Mating device means the equipment necessary for the connection and disconnection
of a diving bell or an HBSC to a surface compression chamber.

3.27 MODU Code means the Code for the Construction and Equipment of Mobile Offshore
Drilling Units, adopted by resolution A.1023(26), as amended.

3.28 Organization means the International Maritime Organization (IMO).

3.29 Place of safety means a location where rescue operations are considered to
terminate. It is also a place where the survivors' safety of life is no longer threatened and their
basic human needs (such as food, shelter and medical/decompression needs) can be met.
A place of safety may be on land, or it may be on board a rescue unit or facility at sea that can
serve as a place of safety until the survivors are disembarked to their next destination.
An assisting ship should not be considered as a place of safety solely on the fact that survivors
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
An assisting ship should not be considered as a place of safety solely on the fact that survivors
are on board as it may not have appropriate facilities and equipment to sustain the survivors.

3.30 Pressure vessel means a container capable of withstanding an internal maximum
working pressure greater than or equal to 1 bar.

3.31 Pressure vessel for human occupancy (PVHO) means a container intended to be
occupied by one or more persons that is capable of withstanding an internal or external
pressure differential exceeding 0.14 bar (2 psi).

3.32 Saturation diving means a method of diving, using PVHO, that allows divers to remain
in the pressurized environment long enough for their body tissues to become saturated with
the inert components of the gas mixture they are breathing.5

5 When saturation is reached, long decompression periods are required. As a result, divers cannot safely be
brought to the surface quickly, even during an emergency.

SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
brought to the surface quickly, even during an emergency.
RESOLUTION MSC.548(107) (adopted on 5 June 2023)
INTERNATIONAL CODE OF SAFETY OR DIVING OPERATIONS, 2023 (2023 DIVING CODE)
MSC 107/20/Add.1

3.33 SOLAS means the International Convention for the Safety of Life at Sea, 1974.

3.34 Standby diving unit means a ship carrying plant and equipment solely to assist in the rescue of divers from another diving unit or units.

3.35 Surface compression chamber means a PVHO installed on the diving platform with means of controlling the pressure inside the chamber.

3.36 Surface compression chamber complex means a series of mechanically connected PVHOs including all associated trunkings.

3.37 Surface orientated diving means a method of diving in which it is not planned for the diver(s) to become saturated. The divers may be deployed using a dive basket, wet bell or
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
diver(s) to become saturated. The divers may be deployed using a dive basket, wet bell or diving bell or, for shallow dives, directly from the diving platform, depending on what water access is available.

3.38 Temporary diving system means a diving system installed on a diving platform for a period not exceeding one year.

3.39 Umbilical means the link between a PVHO, wet bell or diver and the rest of the diving system and may contain surveillance, communication and power supply cables, breathing gas and hot water hoses. The hoisting and lowering strength member may be part of the umbilical.

3.40 Water depth means the depth of the water in which the diving platform is operating.

3.41 Wet bell means a diver deployment and recovery device as a minimum fitted with a gas filled dome, a main supply umbilical from the surface (providing breathing gas and other service to a manifold inside the device), and diver excursion umbilicals terminated at the device.