5.10 A Certificate should be issued for a period specified by the Administration, and should not exceed five years from the date of issue.

5.11 An extension of the validity of the Certificate may be granted for a maximum period of five months at the discretion of the Administration, subject to an annual survey being carried out.

RESOLUTION MSC.548(107) (adopted on 5 June 2023)
INTERNATIONAL CODE OF SAFETY OR DIVING OPERATIONS, 2023 (2023 DIVING CODE)

6 Control

6.1 Every diving system or diving unit, issued with a Certificate under section 5.1 or 5.2 of this Code, is subject, while under the control of an Administration other than that which has
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
of this Code, is subject, while under the control of an Administration other than that which has issued the Certificate, to control by officers duly authorized by t hat Administration for verification that the Certificate is valid. Such Certificate should be accepted unless there are clear grounds for believing that the condition of the diving system or diving unit or its equipment does not correspond substantially with the particulars of that Certificate. In that case, the officer carrying out the control may take such steps as will allow the diving unit to operate on a temporary basis without undue risk to the divers and the personnel on board. ln the event of this control giving rise to intervention of any kind, the officer carrying out the control should inform the Administration or the Consul or in their absence, the nearest diplomatic representative of the State in which the diving unit is registered, in writing f orthwith of all
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
representative of the State in which the diving unit is registered, in writing f orthwith of all circumstances on the basis of which intervention was deemed to be necessary.

6.2 Notwithstanding paragraph 6.1, the provisions of this Code are without prejudice to any rights of the coastal State under international law to impose its own provisions relating to the regulation, surveying and inspection of diving units engaged, or in tending to engage, in diving operations on those parts of the seabed and subsoil over which that State is entitled to exercise sovereign rights.

7 Structure of the Code

This Code contains provisions for the suitability of ships, floating structures and MODUs as platforms for diving systems, the design and testing of diving equipment and plant, and the conduct of diving operations including hyperbaric evacuation. Appendix 1 contains additional guidance on the implementation of these provisions.

1 CHAPTER 1 GENERAL

SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
guidance on the implementation of these provisions.

1 CHAPTER 1 GENERAL

1.1 Structure of this Code

Each chapter consists of the overall goal of the chapter, functional criteria to fulfil the goal and provisions. A system or operational plan should be considered to meet the functional criteria set out in this Code when the design or arrangements comply with all the provisions associated with those functional criteria.

1.2 Certificate and survey

1.2.1 Every diving unit engaged in diving operations to which this Code applies should have a DUSC Part I. Every diving system used in conjunction with a diving unit should have a DUSC Part II.

1.2.2 The DUSC should be issued after an initial or renewal survey of a diving unit and/or diving system which complies with the relevant provisions of this Code.

1.2.3 The Certificate referred to in this Code should be issued either by the Administration
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
1.2.3 The Certificate referred to in this Code should be issued either by the Administration or by any person or organization recognized by it in accordance with SOLAS regulation XI-1/1. In every case, that Administration assumes full responsibility for the certificate.

1.2.4 The DUSC should be drawn up in the form corresponding to the model given in appendix 2 to this Code. If the language used is neither English, French nor Spanish, the text should include a translation into one of these languages.

1.3 Performance standards

Unless expressly provided otherwise, systems and equipment addressed in this Code should satisfy equivalent performance standards to those referred to in SOLAS.

2 CHAPTER 2 DIVING UNIT PRINCIPLES REDUNDANCY AND INTEGRATION
2.1 Goals

SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
2 CHAPTER 2 DIVING UNIT PRINCIPLES REDUNDANCY AND INTEGRATION
2.1 Goals
The goal of this chapter is to define the overall redundancy and integration provisions for the diving unit when integrating the diving system into the diving platform.
2.2 Functional criteria
In order to achieve its goal, this chapter embodies the following provisions.
2.3 Redundancy level and risks external to the diving activity
2.3.1 Goal

The goal of this section is to ensure that the diving unit has sufficient redundancy suitable for its intended operation and for all diving system equipment critical to life support, considering all relevant internal and external risk factors.
2.3.2 Functional criteria

In order to achieve the goal set out in section 2.3.1 above:

.1 the technical level of fault tolerance in the diving unit plant and equipment should be matched to the safety -critical aspects of the intended operation and define any additional levels of redundancy; and
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
should be matched to the safety -critical aspects of the intended operation and define any additional levels of redundancy; and

.2 interactions with other objects and non -diving activities both on board and external to the diving unit should not reduce the designed redundancy level.

2.3.3 In order to comply with the functional criteria of section 2.3.2 above, the following apply:

.1 When working on subsea objects where the termination of diving operations may lead to additional risks to the environment or other personnel, the redundancy of the diving unit should be at a level to cover the risks to both the diver and the environment.

.2 When working on subsea objects where the termination of diving operations may be achieved safely without risk at any time, the systematic review required under section 2.4 is considered to achieve an acceptable level.

.3 Where another onboard activity also requires access to systems or services
---
SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
.3 Where another onboard activity also requires access to systems or services

supporting the diving activity, these should be separated as far as possible. Where these cannot be separated, failures within the other activity 's equipment should be included within a systematic review required under section 2.4.

.4 Where communication, signals or other information are critical to safe diving unit operation, but originate externally to the diving unit or from a non-diving activity, the redundancy of these should be addressed in the systematic review required under section 2.4.

.5 Any findings from the above are to be clearly identified within the systematic review required under section 2.4.

2.4 Redundancy and essential services

2.4.1 Goal

SOURCE: MSC.548(107).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf
review required under section 2.4.

2.4 Redundancy and essential services

2.4.1 Goal

The goal of this section is to ensure that the diving unit can tolerate failures without creating a hazardous situation.

2.4.2 Functional criteria

In order to achieve the goal set out in section 2.4.1 above, the diving unit should be designed