4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

ANNEX
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
Part A

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
- 2 -
ANNEX
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
Part A
2 General
2.2 Definitions
1 The following new paragraph 2.2.43 is added after existing paragraph 2.2.42:
"2.2.43 Ship constructed on or after 1 January 2026 means:
.1 for which the building contract is placed on or after 1 January 2026;
or
.2 in the absence of a building contract, the keels of which are laid or which are at a similar stage of construction on or after 1 July 2026;
or
.3 the delivery of which is on or after 1 January 2030."
4 General requirements
4.2 Risk assessment
2 Paragraph 4.2.2 is replaced by the following:
"4.2.2 For ships to which part A-1 applies, the risk assessment required by 4.2.1 need only be conducted where explicitly required by paragraphs 5.10.5, 5.12.3, 6.4.1.1, 6.4.15.4.7.2, 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by paragraphs 4.4 and 6.8 of the annex."
Part A-1

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
6.4.1.1, 6.4.15.4.7.2, 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by paragraphs 4.4 and 6.8 of the annex."
Part A-1
Specific requirements for ships using natural gas as fuel
5 Ship design and arrangement
5.3 Regulation - General
3 Paragraph 5.3.3.3 is replaced by the following:

"5.3.3.3 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier of the fuel containment system). For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation."
4 Paragraph 5.3.4.4 is replaced by the following:
"5.3.4.4 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier of the fuel containment system). For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

5.12 Regulations for airlocks
5 Paragraph 5.12.1 is replaced by the following:
"5.12.1 For ships constructed on or after 1 January 2026, a n air lock is a space enclosed by gastight bulkheads with two substantially gastight doors spaced at least 1.5 m and not more than 2.5 m apart. Unless subject to the requirements of the International Convention on Load Line, the sill height of the door leading to the hazardous area shall not be less than 300 mm. The doors shall be self-closing without any holding back arrangements."
6 Fuel containment system
6.4 Regulations for liquefied gas fuel containment
6.4.15 Tank types
6.4.15.3 Type C independent tanks
6.4.15.3.1 Design basis
6 Paragraph 6.4.15.3.1.2 is replaced by the following:
"6.4.15.3.1.2 The design vapour pressure shall not be less than:

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
6.4.15.3.1 Design basis
6 Paragraph 6.4.15.3.1.2 is replaced by the following:
"6.4.15.3.1.2 The design vapour pressure shall not be less than:
0 = 0.2 + () 1.5 (MPa)
where:
 = 0.00185 (/) 2
with:
 = design primary membrane stress;
 = allowable dynamic membrane stress (double amplitude at probability level Q = 10-8) and equal to:
- 55 N/mm2 for ferritic-perlitic, martensitic and austenitic steel;
- 25 N/mm2 for aluminium alloy (5083-O);
 = a characteristic tank dimension to be taken as the greatest of the following:
h, 0.75b or 0.45,
with:

h = height of tank (dimension in ship's vertical direction) (m);
b = width of tank (dimension in ship's transverse direction) (m);
 = length of tank (dimension in ship's longitudinal direction) (m);
 = the relative density of the fuel (= 1 for fresh water) at the
design temperature."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).p
df
design temperature."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

6.7 Regulations for pressure relief system
6.7.3 Sizing of pressure relieving system
6.7.3.1 Sizing of pressure relief valves
7 The chapeau of paragraph 6.7.3.1.1 is replaced by the following:
"6.7.3.1.1 For ships constructed on or after 1 January 2026, the pressure relief
system for each liquefied gas fuel tank shall be designed so that, regardless of the
state of any one PRV, the capacity of the residual PRVs meets the combined relieving
capacity requirements of the system. The combined relieving capacity shall be the
greater of the following, with no more than 20% rise in liquefied gas fuel tank pressure
above the MARVS. The tank shall not be loaded until the full relieving capacity is
restored:"
8 Paragraph 6.7.3.1.1.2 is replaced by the following:

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).p
df
restored:"
8 Paragraph 6.7.3.1.1.2 is replaced by the following:
"6.7.3.1.1.2 vapours generated under fire exposure computed using the
following formula:
 = 0.82 (m3/s)
where:
 = minimum required rate of discharge of air at standard conditions
of 273.15 Kelvin (K) and 0.1013 MPa.
 = fire exposure factor for different liquefied gas fuel tank types:
 = 1.0 for tanks without insulation located on deck;
"
6.9 Regulations for the maintaining of fuel storage condition
6.9.1 Control of tank pressure and temperature
9 The chapeau of paragraph 6.9.1.1 is replaced by the following:
"6.9.1.1 For ships constructed on or after 1 January 2026, w ith the exception of
liquefied gas fuel tanks designed to withstand the full gauge vapour pressure of the
fuel under conditions of the upper ambient design temperature, liquefied gas fuel
tanks' pressure and temperature shall be maintained at all times wit hin their design
---
SOURCE: MSC.551(108).pdf

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
tanks' pressure and temperature shall be maintained at all times wit hin their design range by means acceptable to the Administration, e.g. by one or more of the following methods:"
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
- 5 -
7 Material and general pipe design
7.3 Regulations for general pipe design
7.3.2 Wall thickness
10 Paragraph 7.3.2.1 is replaced by the following:
"7.3.2.1 For ships constructed on or after 1 January 2026, the minimum wall thickness shall be calculated as follows:
t = (t0 + b + c) / (1 ||/100) (mm)
where:
t0 = theoretical thickness
t0 = PD / (2.0Ke + P) (mm)
with:
P = design pressure (MPa) referred to in 7.3.3;
D = outside diameter (mm);
K = allowable stress (N/mm²) referred to in 7.3.4; and
e = efficiency factor equal to 1.0 for seamless pipes and for
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
K = allowable stress (N/mm²) referred to in 7.3.4; and
e = efficiency factor equal to 1.0 for seamless pipes and for longitudinally or spirally welded pipes, delivered by approved manufacturers of welded pipes, that are considered equivalent to seamless pipes when non -destructive testing on welds is carried out in accordance with recognized standards. In other cases an efficiency factor of less than 1.0, in accordance with recognized standards, may be required depending on the manufacturing process;