Auditing of the firm
6 Paragraph 2.2 is replaced by the following:
"2.2 Upon reviewing of the documents submitted with satisfactory results, the firm
---
SOURCE: MSC.552(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.552(108).pdf
6 Paragraph 2.2 is replaced by the following:
"2.2 Upon reviewing of the documents submitted with satisfactory results, the firm
shall be audited by the Administration in order to ascertain that the firm is duly
organized and managed in accordance with the documents submitted and is capable
of conducting thickness measurement of the hull structure of ships."
RESOLUTION MSC.553(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE ON THE ENHANCED PROGRAMME
OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS AND OIL TANKERS, 2011 (2011 ESP CODE)
RESOLUTION MSC.553(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE ON THE ENHANCED PROGRAMME
OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS AND OIL TANKERS, 2011 (2011 ESP CODE)

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
RESOLUTION MSC.551(108)
(adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
THE MARITIME SAFETY COMMITTEE,
RECALLING Article 28(b) of the Convention on the International Maritime Organization
concerning the functions of the Committee,
NOTING resolution MSC.391(95), by which it adopted the International Code of Safety for
Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory
under chapters II-1 and II-2 of the International Convention for the Safety of Life at Sea, 1974
("the Convention"),
NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the
procedure for amending the IGF Code,
HAVING CONSIDERED, at its 108th session, amendments to the IGF Code proposed and
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
procedure for amending the IGF Code,
HAVING CONSIDERED, at its 108th session, amendments to the IGF Code proposed and
circulated in accordance with article VIII(b)(i) of the Convention:
1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments
to the IGF Code, the text of which is set out in the annex to the present resolution;
2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the
said amendments shall be deemed to have been accepted on 1 July 2025, unless, prior to that

date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified the Secretary -General of their objections to the amendments;
3 INVITES Contracting Governments to the Convention to note that, in accordance with
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
to the amendments;
3 INVITES Contracting Governments to the Convention to note that, in accordance with
article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2026 upon their acceptance in accordance with paragraph 2 above;
4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
- 2 -
ANNEX
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
Part A

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
- 2 -
ANNEX
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
Part A
2 General
2.2 Definitions
1 The following new paragraph 2.2.43 is added after existing paragraph 2.2.42:
"2.2.43 Ship constructed on or after 1 January 2026 means:
.1 for which the building contract is placed on or after 1 January 2026;
or
.2 in the absence of a building contract, the keels of which are laid or which are at a similar stage of construction on or after 1 July 2026;
or
.3 the delivery of which is on or after 1 January 2030."
4 General requirements
4.2 Risk assessment
2 Paragraph 4.2.2 is replaced by the following:
"4.2.2 For ships to which part A-1 applies, the risk assessment required by 4.2.1 need only be conducted where explicitly required by paragraphs 5.10.5, 5.12.3, 6.4.1.1, 6.4.15.4.7.2, 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by

paragraphs 4.4 and 6.8 of the annex."
Part A-1

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
6.4.1.1, 6.4.15.4.7.2, 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by
paragraphs 4.4 and 6.8 of the annex."
Part A-1
Specific requirements for ships using natural gas as fuel
5 Ship design and arrangement
5.3 Regulation - General
3 Paragraph 5.3.3.3 is replaced by the following:
"5.3.3.3 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier of the fuel containment system). For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation."
4 Paragraph 5.3.4.4 is replaced by the following:
"5.3.4.4 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier of the fuel containment system). For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
- 3 -
5.12 Regulations for airlocks
5 Paragraph 5.12.1 is replaced by the following:
"5.12.1 For ships constructed on or after 1 January 2026, a n air lock is a space enclosed by gastight bulkheads with two substantially gastight doors spaced at least 1.5 m and not more than 2.5 m apart. Unless subject to the requirements of the International Convention on Load Line, the sill height of the door leading to the hazardous area shall not be less than 300 mm. The doors shall be self-closing without any holding back arrangements."
6 Fuel containment system
6.4 Regulations for liquefied gas fuel containment
6.4.15 Tank types
6.4.15.3 Type C independent tanks
6.4.15.3.1 Design basis
6 Paragraph 6.4.15.3.1.2 is replaced by the following:
"6.4.15.3.1.2 The design vapour pressure shall not be less than:

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
6.4.15.3.1 Design basis
6 Paragraph 6.4.15.3.1.2 is replaced by the following:

"6.4.15.3.1.2 The design vapour pressure shall not be less than:
0 = 0.2 + () 1.5 (MPa)
where:
 = 0.00185 (/) 2
with:
 = design primary membrane stress;
 = allowable dynamic membrane stress (double amplitude at
probability level Q = 10-8) and equal to:
- 55 N/mm2 for ferritic-perlitic, martensitic and austenitic steel;
- 25 N/mm2 for aluminium alloy (5083-O);
 = a characteristic tank dimension to be taken as the greatest of the
following:
h, 0.75b or 0.45,
with:
h = height of tank (dimension in ship's vertical direction) (m);
b = width of tank (dimension in ship's transverse direction) (m);
 = length of tank (dimension in ship's longitudinal direction) (m);
 = the relative density of the fuel (= 1 for fresh water) at the
design temperature."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
design temperature."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

6.7 Regulations for pressure relief system
6.7.3 Sizing of pressure relieving system
6.7.3.1 Sizing of pressure relief valves
7 The chapeau of paragraph 6.7.3.1.1 is replaced by the following:
"6.7.3.1.1 For ships constructed on or after 1 January 2026, the pressure relief system for each liquefied gas fuel tank shall be designed so that, regardless of the state of any one PRV, the capacity of the residual PRVs meets the combined relieving capacity requirements of the system. The combined relieving capacity shall be the greater of the following, with no more than 20% rise in liquefied gas fuel tank pressure above the MARVS. The tank shall not be loaded until the full relieving capacity is