restored:"
8 Paragraph 6.7.3.1.1.2 is replaced by the following:

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
restored:"
8 Paragraph 6.7.3.1.1.2 is replaced by the following:
"6.7.3.1.1.2 vapours generated under fire exposure computed using the
following formula:
 = 0.82 (m3/s)
where:
 = minimum required rate of discharge of air at standard conditions
of 273.15 Kelvin (K) and 0.1013 MPa.
 = fire exposure factor for different liquefied gas fuel tank types:
 = 1.0 for tanks without insulation located on deck;
"
6.9 Regulations for the maintaining of fuel storage condition
6.9.1 Control of tank pressure and temperature
9 The chapeau of paragraph 6.9.1.1 is replaced by the following:
"6.9.1.1 For ships constructed on or after 1 January 2026, w ith the exception of
liquefied gas fuel tanks designed to withstand the full gauge vapour pressure of the
fuel under conditions of the upper ambient design temperature, liquefied gas fuel
tanks' pressure and temperature shall be maintained at all times wit hin their design
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
tanks' pressure and temperature shall be maintained at all times wit hin their design
range by means acceptable to the Administration, e.g. by one or more of the following
methods:"
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
- 5 -
7 Material and general pipe design
7.3 Regulations for general pipe design
7.3.2 Wall thickness
10 Paragraph 7.3.2.1 is replaced by the following:
"7.3.2.1 For ships constructed on or after 1 January 2026, the minimum wall thickness
shall be calculated as follows:
t = (t0 + b + c) / (1 ||/100) (mm)
where:
t0 = theoretical thickness
t0 = PD / (2.0Ke + P) (mm)
with:
P = design pressure (MPa) referred to in 7.3.3;
D = outside diameter (mm);
K = allowable stress (N/mm²) referred to in 7.3.4; and
 e = efficiency factor equal to 1.0 for seamless pipes and for
---
SOURCE: MSC.551(108).pdf

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
K = allowable stress (N/mm²) referred to in 7.3.4; and
e = efficiency factor equal to 1.0 for seamless pipes and for longitudinally or spirally welded pipes, delivered by approved manufacturers of welded pipes, that are considered equivalent to seamless pipes when non -destructive testing on welds is carried out in accordance with recognized standards. In other cases an efficiency factor of less than 1.0, in accordance with recognized standards, may be required depending on the manufacturing process;
b = allowance for bending (mm). The value of b shall be chosen so that the calculated stress in the bend, due to internal pressure only, does not exceed the allowable stress. Where such justification is not given, b shall be:
b = Dt0 / 2.5r (mm)
with:
r = mean radius of the bend (mm);
c = corrosion allowance (mm). If corrosion or erosion is expected the wall thickness of the piping shall be increased over that required by other
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
thickness of the piping shall be increased over that required by other design regulations. This allowance shall be consistent with the expected life of the piping; and
= negative manufacturing tolerance for thickness (%), i.e. where is the manufacturing tolerance of -5%, || is equal to 5 and shall be entered into the formula as 1- (5/100)."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)
- 6 -
8 Bunkering
8.4 Regulations for manifold
11 Paragraph 8.4.1 is replaced by the following:
"8.4.1 The bunkering manifold shall be designed to withstand the external loads during bunkering. The connections at the bunkering station shall be arranged in order to achieve a dry-disconnect operation in one of the followings ways:
.1 a dry-disconnect / connect coupling in accordance with a standard at least equivalent to those acceptable to the Organization; or
---
SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
.1 a dry-disconnect / connect coupling in accordance with a standard at least equivalent to those acceptable to the Organization; or
.2 a manual connect coupler or hydraulic connect coupler, used to connect the bunker system to the receiving vessel bunkering manifold presentation flange; or

.3 a bolted flange to flange assembly.
12 The following new paragraphs are added after existing paragraph 8.4.1:
8.4.2 When intended to use either of the connections specified in paragraphs 8.4.1.2 and 8.4.1.3, these shall be combined with operating procedures that ensure a dry-disconnect is achieved. The arrangement shall be subject to special consideration informed by a bunkering arrangement risk assessment conducted at the design stage and considering dynamic loads at the bunkering manifold connection to a recognized standard acceptable to the Administration, the safe operation of the ship and other hazards that may be r elevant to the ship during bunkering operation.

SOURCE: MSC.551(108).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
ship and other hazards that may be r elevant to the ship during bunkering operation.
The fuel handling manual required by 18.2.3 shall include documentation that the bunkering arrangement risk assessment was conducted, and that special consideration was granted under this requirement.
8.4.3 An emergency release coupler (ERC) / Emergency Release System (ERS) or equivalent means shall be provided, unless installed on the bunkering supply side of the bunkering line, and the said means shall be in accordance with a standard equivalent to those acceptable to the Organization; it shal l enable a quick physical disconnection dry break-away of the bunker system in an emergency event."
9 Fuel supply to consumers
9.3 Regulations on redundancy of fuel supply
13 Paragraph 9.3.1 is replaced by the following:
"9.3.1 For ships constructed on or after 1 January 2026, for single fuel installations the fuel supply system shall be arranged with redundancy and segregation, so that a
---
SOURCE: MSC.551(108).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
the fuel supply system shall be arranged with redundancy and segregation, so that a
leakage in one system, or failure of one of the fuel supply essential auxiliaries, does not lead to an unacceptable loss of power. In the event of a leakage or failure, and in accordance with SOLAS regulation II -1/26.3, the Administration, having regard to overall safety considerations, may accept a partial reduction in propulsion capabili ty from normal operation."
RESOLUTION MSC.551(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY
FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

9.4 Regulations on safety functions of gas supply system
14 Paragraph 9.4.7 is replaced by the following:
"9.4.7 For ships constructed on or after 1 January 2026, in cases where the master gas fuel valve is automatically shut down when the safety system as required in 15.2.2 is activated, the complete gas supply pipe between this master gas fuel valve and the
---
SOURCE: MSC.551(108).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf
is activated, the complete gas supply pipe between this master gas fuel valve and the

double block and bleed valves and between the double block and bleed valves and the consumer shall be automatically vented."

15 Paragraph 9.4.8 is replaced by the following:

"9.4.8 For ships constructed on or after 1 January 2026, there shall be one manually operated shutdown valve in the gas supply line to each gas consumer upstream of the double block and bleed valves to assure safe isolation during maintenance on the gas consumer."

9.6 Regulations for fuel supply to consumers in gas-safe machinery spaces

16 Paragraph 9.6.1.1 is replaced by the following:

"9.6.1 Gas fuel piping in gas-safe machinery spaces shall be completely enclosed by a double pipe or duct fulfilling one of the following conditions:

.1 the gas fuel piping shall be a double wall piping system with the gas fuel contained in the inner pipe. The space between the concentric

---

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf

.1 the gas fuel piping shall be a double wall piping system with the gas fuel contained in the inner pipe. The space between the concentric pipes shall be pressurized with inert gas at a pressure greater than the gas fuel pressure. Suitable alarms shall be provided to indicate a loss of inert gas pressure between the pipes; or"

9.8 Regulations for the design of ventilated duct, outer pipe against inner pipe gas leakage

17 Paragraph 9.8.1 is replaced by the following:

"9.8.1 For ships constructed on or after 1 January 2026, the design pressure of the outer pipe or duct of fuel systems shall not be less than the maximum working pressure of the inner pipe. Alternatively, the design pressure of the outer pipe or duct may be calculated in accordance with 9.8.2."

18 The chapeau of paragraph 9.8.2 is replaced by the following:

"9.8.2 For ships constructed on or after 1 January 2026, alternatively to 9.8.1, the

---

SOURCE: MSC.551(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf

"9.8.2 For ships constructed on or after 1 January 2026, alternatively to 9.8.1, the design pressure of the outer pipe or duct shall be taken as the higher of the following:"

19 Paragraph 9.8.4 is replaced by the following:

"9.8.4 For ships constructed on or after 1 January 2026, the duct shall be pressure-tested to show that it can withstand the expected maximum pressure at fuel pipe rupture."