Fixed fire detection and fire alarm systems
1 Application
2 Paragraph 1.1 is replaced by the following:
"1.1 This chapter details the specification of fixed fire detection and fire alarm systems as required by chapter II -2 of the Convention. Unless expressly provided otherwise, the requirements of this chapter shall apply to ships constructed on or after
---
SOURCE: MSC.555(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf
otherwise, the requirements of this chapter shall apply to ships constructed on or after 1 July 2 012. The requirements of 2.3.1.5 and 2.4.2.2 of this chapter shall apply to ships constructed on or after 1 January 2026."
2 Engineering specifications
2.3 Component requirements
3 Paragraphs 2.3.1.3 and 2.3.1.4 are replaced by the following:
"2.3.1.3 Heat detectors and linear heat detectors shall be certified to operate before the temperature exceeds 78ºC but not until the temperature exceeds 54ºC, when the temperature is raised to those limits at a rate less than 1ºC per min, when tested according to relevant parts of standards EN 54:2001 and IEC 60092-504. Alternative testing standards may be used as determined by the Administration. At higher rates of temperature rise, the heat detector and linear heat detector shall operate within temperature limits to the satisfaction of the Administration having regard to the avoidance of detector insensitivity or oversensitivity.

SOURCE: MSC.555(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf
temperature limits to the satisfaction of the Administration having regard to the avoidance of detector insensitivity or oversensitivity.
RESOLUTION MSC.555(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE)
- 4 -
2.3.1.4 The operation temperature of heat detectors and linear heat detectors in drying rooms and similar spaces of a normal high ambient temperature may be up to 130ºC, and up to 140ºC in saunas."
4 The following new paragraph 2.3.1.5 is inserted after the existing paragraph 2.3.1.4 and subsequent paragraphs are renumbered accordingly:
"2.3.1.5 Linear heat detectors shall be tested according to standards EN 54-22:2015 and IEC 60092-504. Alternative testing standards may be used as determined by the Administration."
2.4 Installation requirements
2.4.2 Positioning of detectors
5 Paragraph 2.4.2.2 and the associated table 9.1 (Spacing of detectors) therein are replaced by the following:

SOURCE: MSC.555(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf
2.4.2 Positioning of detectors
5 Paragraph 2.4.2.2 and the associated table 9.1 (Spacing of detectors) therein are

replaced by the following:
"2.4.2.2 The maximum spacing of detectors shall be in accordance with the table below:
Table 9.1 Spacing of detectors
Type of detector
Maximum floor area per detector (m2)
Maximum distance apart between centres (m)
Maximum distance away from bulkheads (m)
Heat 37 9 4.5
Smoke 74 11 5.5
Combined smoke and heat 74 9 4.5
2.4.2.2.1 The Administration may require or permit other spacing based upon test data which demonstrate the characteristics of the detectors. Detectors located below movable ro-ro decks shall be in accordance with the above.
2.4.2.2.2 The distance between two sensor cables of the linear heat detection system shall not be more than 9.0 m, while the distance between such cables and bulkheads shall not be more than 4.5 m."
2.5 System control requirements
2.5.1 Visual and audible fire signals

SOURCE: MSC.555(108).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf
bulkheads shall not be more than 4.5 m."
2.5 System control requirements
2.5.1 Visual and audible fire signals
6 The following new paragraphs 2.5.1.2, 2.5.1.3 and 2.5.1.4 are inserted after paragraph 2.5.1.1 and the subsequent paragraphs are renumbered accordingly:
"2.5.1.2 On ro -ro passenger ships constructed on or after 1 January 2026, alarm notifications shall follow a consistent alarm presentation scheme (wording, vocabulary, colour and position). Alarms shall be immediately recognizable on the navigation bridge and shall not be compromised by noise or poor placing.
2.5.1.3 On ro -ro passenger ships constructed on or after 1 January 2026, the interface shall provide alarm addressability, allow the crew to identify the alarm history, the most recent alarm and the means to suppress alarms while ensuring the alarms with ongoing trigger conditions are still clearly visible.
RESOLUTION MSC.555(108) (adopted on 23 May 2024)

SOURCE: MSC.555(108).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf
alarms with ongoing trigger conditions are still clearly visible.
RESOLUTION MSC.555(108) (adopted on 23 May 2024)

2.5.1.4 On ro-ro passenger ships constructed on or after 1 January 2026, the smoke detector function in special category and ro -ro spaces may be disconnected during loading and unloading of vehicles. The time of disconnection shall be adapted to the time of loading/unloading and be automatically reset after this predetermined t ime. The central unit shall indicate whether the detector sections are disconnected or not. Disconnection of the heat detection function or manual call points shall not be permitted."
RESOLUTION MSC.555(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE)
RESOLUTION MSC.555(108) (adopted on 23 May 2024)
AMENDMENTS TO THE INTERNATIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE)

SOURCE: MSC.557(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.557(108).pdf
RESOLUTION MSC.557(108) (adopted on 23 May 2024)
AMENDMENTS TO THE PERFORMANCE STANDARD FOR PROTECTIVE COATINGS FOR DEDICATED SEAWATER BALLAST TANKS IN ALL TYPES OF SHIPS AND DOUBLE-SIDE SKIN SPACES OF BULK CARRIERS (RESOLUTION MSC.215(82), AS AMENDED)
RESOLUTION MSC.557(108)
(adopted on 23 May 2024)
AMENDMENTS TO THE PERFORMANCE STANDARD FOR PROTECTIVE COATINGS FOR DEDICATED SEAWATER BALLAST TANKS IN ALL TYPES OF SHIPS AND DOUBLE-SIDE SKIN SPACES OF BULK CARRIERS
(RESOLUTION MSC.215(82), AS AMENDED)
THE MARITIME SAFETY COMMITTEE,
RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,
RECALLING ALSO resolution MSC.215(82), by which it adopted the Performance standard for protective coatings for dedicated seawater ballast tanks in all types of ships and double-side skin spaces of bulk carriers ("the Performance standard"), which has become mandatory under
---
SOURCE: MSC.557(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.557(108).pdf
skin spaces of bulk carriers ("the Performance standard"), which has become mandatory under chapter II-1 of the International Convention for the Safety of Life at Sea (SOLAS), 1974 ("the Convention"), as amended by resolution MSC.341(91),
RECALLING FURTHER article VIII(b) and regulation II -1/3-2.2 of the Convention concerning the procedure for amending the Performance standard,
RECOGNIZING the need to keep the Performance standard up to date with regard to references to other IMO instruments contained therein,
HAVING CONSIDERED, at its 108th session, amendments to the Performance standard, proposed and circulated in accordance with VIII(b)(i) of the Convention,
1 ADOPTS, in accordance with Article VIII(b)(iv) of the Convention, amendments to the Performance standard for protective coatings for dedicated seawater ballast tanks in all types of ships and double-side skin spaces of bulk carriers, the text of which is set out in the annex to the present resolution;

SOURCE: MSC.557(108).pdf
URL:

https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.557(108).pdf
of ships and double-side skin spaces of bulk carriers, the text of which is set out in the annex to the present resolution;
2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the amendments shall be deemed to have been accepted on 1 July 2025, unless, prior to that date, more than one third of the Contracting Governments to the Convention or Cont racting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified the Secretary -General of their objections to the amendments;
3 INVITES SOLAS Contracting Governments to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2026 upon their acceptance in accordance with paragraph 2 above;
4 REQUESTS the Secretary -General, in conformity with Article VIII(b)(v) of the
---
SOURCE: MSC.557(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.557(108).pdf
upon their acceptance in accordance with paragraph 2 above;
4 REQUESTS the Secretary -General, in conformity with Article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.
RESOLUTION MSC.557(108) (adopted on 23 May 2024)
AMENDMENTS TO THE PERFORMANCE STANDARD FOR PROTECTIVE COATINGS FOR DEDICATED SEAWATER BALLAST TANKS IN ALL TYPES OF SHIPS AND DOUBLE-SIDE SKIN SPACES OF BULK CARRIERS (RESOLUTION MSC.215(82), AS AMENDED)

ANNEX
AMENDMENTS TO THE PERFORMANCE STANDARD FOR PROTECTIVE COATINGS FOR DEDICATED SEAWATER BALLAST TANKS IN ALL TYPES OF SHIPS AND DOUBLE-SIDE SKIN SPACES OF BULK CARRIERS
(RESOLUTION MSC.215(82), AS AMENDED)

SOURCE: MSC.557(108).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.557(108).pdf
FOR DEDICATED SEAWATER BALLAST TANKS IN ALL TYPES OF SHIPS AND DOUBLE-SIDE SKIN SPACES OF BULK CARRIERS