URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
products, as shown in chapter 19, when carried in bulk".
1.2 A ship carrying liquefied hydrogen in bulk (hereinafter called "liquefied hydrogen carrier") should comply with the Code.
1.3 The Code requires that a gas carrier should comply with the minimum requirements for the cargo listed in chapter 19. However, the requirements for liquefied hydrogen are not specified in the Code.
1.4 This annex provides the Revised Interim Recommendations, as referred to in paragraph 5 of the preamble of the Code, for the carriage of liquefied hydrogen in bulk, which are intended to provide the basis for the future minimum requirements for the carriage of this cargo. The Revised Interim Recommendations are intended to facilitate the establishme nt of a tripartite agreement among the relevant Administrations for the carriage of liquefied hydrogen in bulk. However, they are not intended to prohibit the adoption of designs and arrangements
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
in bulk. However, they are not intended to prohibit the adoption of designs and arrangements other than those specified in the Code or in these Recommendations, at the discretion of the Administrations.
1.5 These recommendations have been developed under the assumption that a liquefied hydrogen carrier does not carry liquefied gases other than liquefied hydrogen. These recommendations, therefore, are not applicable to liquefied hydrogen carriers carrying gase s other than liquefied hydrogen.
1.6 In the Code, reference is made to paragraph 5 of the Preamble; paragraph 1.1.6.1; and Note No.8 on completion of certificate in "model form of international certificate of fitness for the carriage of liquefied gases in bulk" in appendix 2 to the Code.
1.7 These Revised Interim Recommendations consist of the following parts. Part A is applicable to ships with any type of cargo containment system. Part B and subsequent part(s)

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
applicable to ships with any type of cargo containment system. Part B and subsequent part(s) prescribe additional special requirements for cargo containment systems of specific types.
Part A: General (applicable to ships with any type of cargo containment system);
Part B: Cargo containment systems of independent cargo tanks using vacuum insulation; and
Part C: Cargo containment systems of independent cargo tanks using insulation materials and hydrogen gas in the inner insulation spaces.
RESOLUTION MSC.565(108) (adopted on 24 May 2024)
REVISED INTERIM RECOMMENDATIONS FOR CARRIAGE OF LIQUEFIED HYDROGEN IN BULK

1.8 Part A of this document was developed based on the design of parts B and C. If subsequent part(s) are added, the special requirements prescribed in part A may be reviewed.

Part A
General
(Applicable to ships with any type of cargo containment system)
2 GENERAL
2.1 Definition

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
reviewed.
Part A
General
(Applicable to ships with any type of cargo containment system)
2 GENERAL
2.1 Definition
2.1.1 The following definition should apply for the purpose of these Revised Interim Recommendations.
Permeation is flow of a fluid through another material by diffusion without a defect or opening of the latter.8
2.2 Requirements for carriage of liquefied hydrogen in bulk
2.2.1 The requirements for the carriage of liquefied hydrogen in bulk have been developed based on the results of a comparison study of similar cargoes listed in chapter 19 of the Code, e.g. liquefied natural gas.
2.2.2 Chapter 19 of the Code governs the application of general requirements for respective cargoes. Selections of the general requirements for respective cargoes are expressed in columns 'c' to 'g'. In addition to general requirements, special requirement s may apply to specific cargoes depending on the properties/hazards of the cargoes.

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
specific cargoes depending on the properties/hazards of the cargoes.
2.2.3 Tables 1 and 2 specify the proposed selection of the general requirements and the special requirements, respectively, for liquefied hydrogen. In addition to table 2, special requirements for cargo containment systems of specific types are prescribed in part B or subsequent part(s).
8 1 See paragraph 3.79 of ISO/TR 15916:2015.

Table 1: Requirements for carriage of liquefied hydrogen in bulk
a b c d e f g h i
Product name
Ship type
Independent
tank type C
required
Control of
vapour space

within cargo
tanks
Vapour
detection
Gauging
Special
requirements
Hydrogen 2G - - F C
See table 2
and, either
corresponding
table 4 or
table 5, as
appropriate for
the type of
cargo
containment
systems

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
Hydrogen 2G - - F C
See table 2
and, either
corresponding
table 4 or
table 5, as
appropriate for
the type of
cargo
containment
systems
Table 2: Special requirements for carriage of liquefied hydrogen in bulk
No. Special requirement Related hazard
A-1 Requirements for materials whose design temperature is lower than -165°C should be agreed with the Administration, paying attention to appropriate standards. Where minimum design temperature is lower than -196°C, property testing for insulation materials should be carried out with the appropriate medium, over a range of temperatures expected in service.
Low temperature
(see 4.2.1)
A-2 Materials of construction and ancillary equipment such as insulation should be resistant to the effects of high oxygen concentrations caused by condensation and enrichment at the low temperatures attained in parts of the cargo system (refer to the requirement for nitrogen). This special requirement is applied
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf

low temperatures attained in parts of the cargo system (refer to the requirement for nitrogen). This special requirement is applied to all locations where contact with condensed oxygen is anticipated under normal conditions and foreseeable single failure scenarios.
Low temperature
(see 4.2.2)
A-3 For cargo pipes containing liquid hydrogen and cold hydrogen vapour, measures should be taken to prevent the exposed surfaces from reaching -183°C. For places where preventive measures against low temperature are not sufficiently effective, such as cargo m anifolds, other appropriate measures such as ventilation which avoids the formation of highly enriched oxygen and the installation of trays recovering liquid air may be permitted in lieu of the preventive measures. Insulation on liquid hydrogen piping syst ems exposing to air should be of non -combustible material and should be designed to have a seal in the outer covering to prevent the condensation of air and subsequent
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
material and should be designed to have a seal in the outer covering to prevent the condensation of air and subsequent oxygen enrichment within the insulation.
Low temperature
(see 4.2.2)
A-4 Appropriate means, e.g. filtering, should be provided in cargo piping systems to remove impure substances condensed at low temperature.
Low temperature
(see 4.2.3)