10.91
116.79
NIST RefProp10)
NIST RefProp10)
Flame temperature in air (°C) 2396 2230 Calculated using Cantera and GRI 3.0 mechanism
Maximum burning velocity (m/s) 3.15 0.385 Calculated using Cantera and GRI 3.0 mechanism
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
Maximum burning velocity (m/s) 3.15 0.385 Calculated using Cantera and GRI 3.0 mechanism
Heat of vaporization (J/g)* 454.6 510.4 ISO1), Annex A, Table A.3
Lower flammability limit
(% vol. fraction)*** 4 5.3 ISO1), Annex B, Table B.2
Upper flammability limit
(% vol. fraction)*** 77 17.0 ISO1), Annex B, Table B.2
Minimum ignition energy (mJ)*** 0.017 0.274 ISO1), Annex B, Table B.2
Auto-ignition temperature*** 858 810 ISO1), Annex B, Table B.2
Toxicity Non Non Orange book5)
Temperature at critical point (K) 33.19**** 190.55
Hydrogen: ISO1), Annex A,
Table A.1
Methane: The Japan
Society of Mechanical
Engineers, Data Book,
Thermophysical
Properties of Fluids (1983)
Pressure at critical point (kPaA) 1315**** 4595
Hydrogen: ISO1), Annex A,
Table A.1
Methane: The Japan
Society of Mechanical
Engineers, Data Book,
Thermophysical
Properties of Fluids (1983)
Remarks: * At their normal boiling points for comparison purpose.
** At normal temperature and pressure.

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
Properties of Fluids (1983)
Remarks: * At their normal boiling points for comparison purpose.
** At normal temperature and pressure.
*** Ignition and combustion properties for air mixtures at 25°C
and 101.3 kPaA.
**** Normal Hydrogen.
3.2 Explanation on respective requirements
3.2.1 Ship type (column 'c')
As the hazard associated with hydrogen cargo is flammability but not toxicity, the ship type is
considered 2G.
3.2.2 Independent tank type C required (column 'd')

Independent tank type C is allocated only to dangerous goods of class 2.3 whose vapour density is heavier than air. Independent tank type C is considered not to be required for liquefied hydrogen.
RESOLUTION MSC.565(108) (adopted on 24 May 2024)
REVISED INTERIM RECOMMENDATIONS FOR CARRIAGE OF
LIQUEFIED HYDROGEN IN BULK
MSC 108/20/Add.1
Annex 20, page 9
I:\MSC\108\MSC 108-20-Add.1.docx
3.2.3 Control of vapour space within cargo tank (column 'e')

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
MSC 108/20/Add.1
Annex 20, page 9
I:\MSC\108\MSC 108-20-Add.1.docx
3.2.3 Control of vapour space within cargo tank (column 'e')
Special environment controls such as drying and inerting are generally required for liquid chemical products in consideration of the reactivity of cargo vapour and air. As is the case for LNG, it is considered not to be necessary to apply such requirements for liquefied hydrogen.
3.2.4 Vapour detection (column 'f')
Because hydrogen is flammable and non -toxic, it is appropriate to require Flammable (F) as vapour detection for liquefied hydrogen.
3.2.5 Gauging (column 'g')
On the grounds that Closed (C) gauging is required, in principle, for flammable or toxic cargoes, such as methane, it is considered to be appropriate to require Closed (C) gauging for hydrogen, taking into account that hydrogen has high ignitability and a wide flammable range in air and that closed gauging is effective to prevent leakage of gases into air.

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
that closed gauging is effective to prevent leakage of gases into air.
4 SPECIAL REQUIREMENTS AGAINST HAZARDS OF LIQUEFIED HYDROGEN
4.1 Hazards of liquefied hydrogen to be considered
4.1.1 The hazards related to liquefied hydrogen are low ignition energy , a wide range of flammability limits, low visibility of flames in case of fire, high flame velocity which may lead to the detonation with shockwave, low temperature and liquefaction/solidification of inert gas and constituents of air which may result in an oxygen-enriched atmosphere, high permeation, low viscosity, and hydrogen embrittlement including weld metals. Where vacuum insulation is adopted, due consideration should be given to the possibility of untimely deterioration of insulation properties at the envisaged carriage temperatures of liquid hydrogen. The vacuum insulation evaluation should be specified for the normal range or upper limit of cold vacuum
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
insulation evaluation should be specified for the normal range or upper limit of cold vacuum
pressure (CVP), and loss of vacuum should be defined with respect to this value. Accordingly, effect of vacuum pressure should be taken into account at the time of design and testing of piping with vacuum insulation. Supporting structure and adjacent hull structure should be

designed taking into account the cooling owing to loss of vacuum insulation.
4.1.2 Hydrogen is essentially a mixture of ortho - and para-hydrogen, with an equilibrium concentration of 75% ortho-hydrogen and 25% para-hydrogen at ambient temperature. When liquefied at 20K, there is a slow but continuous transformation of ortho -hydrogen to para-hydrogen. The exothermic conversion of the nuclear spin isomers of hydrogen (ortho- to para-hydrogen) may take place and the effect of the conversion may have an impact on the cooling capacity and relief valve capacity of the vessel's equipment.

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
the cooling capacity and relief valve capacity of the vessel's equipment.
4.1.3 Trace amounts of air will condense or solidify in an environment with liquid hydrogen possibly resulting in an unstable and explosive mixture. Precautions should be taken to assure that the possibility of condensed air is accounted within properly secured hazard areas.

4.2 Low temperature hazard
4.2.1 Selection of appropriate material
4.2.1.1 Tables 6.3 and 6.4 in the Code prescribe material selection for piping or cargo tanks whose design temperature is -165°C or higher. According to Note 2 of table 6.3 and Note 3 of table 6.4 of the Code, the requirements for materials whose design temperatures are lower than -165°C should be specially agreed with the Administration. In this regard, the publication
---
SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
than -165°C should be specially agreed with the Administration. In this regard, the publication
by AIAA2) introduces some appropriate materials corresponding to the design temperature and the Administration should take into account such references for the material selection.
4.2.1.2 Although paragraph 4.19.3 in the Code requires testing of materials used for thermal insulation for various properties adequate for the intended service temperature, the minimum test temperature is -196°C. The requirements in the Code do not refer to the normal boiling point of hydrogen, being -253°C. In case of carriage of liquefied hydrogen, special requirements should be provided to consider the lower design temperature.
4.2.2 Measures for condensed air
4.2.2.1 In the case of nitrogen whose normal boiling point is -196°C, for which air condensation and oxygen enrichment are concerns, the following special requirement has already been included in paragraph 17.17 in the Code:

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf
condensation and oxygen enrichment are concerns, the following special requirement has already been included in paragraph 17.17 in the Code:
"Material of construction and ancillary equipment such as insulation shall be resistant to the effect of high oxygen concentrations caused by condensation and enrichment

at the low temperatures attained in parts of the cargo system. Due consideration shall be given to ventilation in such areas where condensation might occur to avoid the stratification of oxygen-enriched atmosphere."

A similar special requirement is applicable to hydrogen.

4.2.2.2 A vent may be blocked by accumulation of ice formed from moisture in the air, which may result in excessive pressure leading to rupture of the vent and relevant piping (see paragraph 4.2.4).

4.2.3 Removal of impure substances condensed

The removal of impure substances, such as those contained in condensate in pipes, should

---

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf

4.2.3 Removal of impure substances condensed

The removal of impure substances, such as those contained in condensate in pipes, should be separately considered. Installation of filters can be an appropriate measure and should be stipulated as a special requirement.

4.2.4 Prevention of blockage due to formation of water or ice

Pressure relief systems may become blocked due to formation of water or ice, depending on the temperature and humidity of air, resulting from the low temperature of the cargo and its vapour (see paragraph 4.2.2) . Appropriate means should be provided to prevent such phenomena.

4.3 Hydrogen embrittlement

4.3.1 Selection of appropriate materials should be required to prevent failures owing to hydrogen embrittlement. The publication by AIAA 2) introduces some appropriate materials resistant to hydrogen embrittlement, and concludes that aluminium is the material least affected.

SOURCE: MSC.566(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.566(109).pdf

resistant to hydrogen embrittlement, and concludes that aluminium is the material least affected.

4.3.2 International or national standards should be followed for the selection of materials